

Package ‘SpectralCIMixed’

August 31, 2023

Type Package

Title Spectral Clustering for Mixed Type Data

Version 1.0.1

Maintainer Cristina Tortora <grikris1@gmail.com>

Description Performs cluster analysis of mixed-type data using Spectral Clustering, see F. Mbuga and, C. Tortora (2022) <[doi:10.3390/stats5010001](https://doi.org/10.3390/stats5010001)>.

License GPL (>= 2)

Depends R (>= 3.5)

Imports RSpectra, cluster, ggplot2, GGally

Encoding UTF-8

RoxygenNote 7.1.2

NeedsCompilation no

Author Cristina Tortora [aut, cre, cph]
(<<https://orcid.org/0000-0001-8351-3730>>),
Felix Mbuga [aut],
Zander Bonnet [aut]

Repository CRAN

Date/Publication 2023-08-30 23:10:02 UTC

R topics documented:

mspec	2
plot.SpectralCIMixed	3
SpectralCIMix	4
summary.SpectralCIMixed	4

Index	5
--------------	----------

mspec

Performs spectral clustering on mix typed data

Description

Performs spectral clustering of mix-type data

Usage

```
mspec(
  z,
  k = 2,
  sigma = c(20, 20),
  c_wt = NULL,
  starts = 10,
  its = 300,
  verbose = FALSE
)
```

Arguments

<code>z</code>	data to be clustered
<code>k</code>	the number of clusters.
<code>sigma</code>	vector of lower,upper bounds for sigma
<code>c_wt</code>	the category weights, is assigned to <code>c(0.9999, 0.999, .99, seq(0.95, 0.05,-0.05), .01, 0.001, 0.0001)</code> if null.
<code>starts</code>	the number of random starts
<code>its</code>	the max number of iterations for the kmeans algorithm
<code>verbose</code>	if you would like printed output during running of function

Value

A class `SpectralCIMixed` list with components

<code>ct_wt</code>	the selected category weight
<code>bt/wt_ss</code>	the between divided by the within sum of squares
<code>tot_wt_ss</code>	the total within sum of squares
<code>cluster</code>	the cluster assignments
<code>data</code>	the original data

References

F. Mbuga and, C. Tortora. Spectral Clustering of Mixed-Type Data. *Stats*, 5(1) 2022

Examples

```
c1=data.frame(v1=rnorm(30,0),v2=rnorm(30,0),v3=factor(round(runif(30))+1))
c2=data.frame(v1=rnorm(30,2),v2=rnorm(30,4),v3=factor(round(runif(30))+4))
data=rbind(c1,c2)
res=mspec(data, k = 2)
summary(res)
plot(res)
```

plot.SpectralCIMixed *Plots the output of mspec*

Description

Plots the output of the function `mspec`, which performs Spectral clustering for mixed type data. The function displays up to 10 variables on a parrallel coordinate plot and on a scatter plot matrix, with colors representing the clustering partition

Usage

```
## S3 method for class 'SpectralCIMixed'
plot(x,cols=NULL,...)
```

Arguments

<code>x</code>	object of <code>SpectralCIMixed</code> class, the output of <code>mspec</code>
<code>cols</code>	For datasets with more than 10 columns, columns to plot
<code>...</code>	other graphic parameters

Value

No return value,the function produces a parallel coordinate plot and a scatter plot matrix

Examples

```
ex1=mspec(iris,3)
plot(ex1,cols=1:4)
```

SpectralClMix

SpectralCIMix

Description

Cluster analysis of mixed-type data using Spectral Clustering.

Author(s)

Felix Mbuga, Cristina Tortora, Zander Bonnet

References

F. Mbuga and, C. Tortora. Spectral Clustering of Mixed-Type Data. *Stats*, 5(1) 2022

summary.SpectralCIMixed

Summarizes the output of mspec

Description

Summarizes the output of mspec

Usage

```
## S3 method for class 'SpectralClMixed'
summary(object,...)
```

Arguments

object	object of SpectralCIMixed class, the output of mspec
...	other optional parameters

Value

It displays: The selected categorical variables weight, The between divided by within sum of squares, The total within sum of squares, and the cluster size.

Index

`mspec`, [2](#)

`plot.SpectralClMixed`, [3](#)

`SpectralClMix`, [4](#)

`SpectralClMixed-package`
(`SpectralClMix`), [4](#)

`summary.SpectralClMixed`, [4](#)