

# Package ‘this.path’

January 16, 2023

**Version** 1.2.0

**License** MIT + file LICENSE

**Title** Get Executing Script's Path, from 'Rgui', 'RStudio', 'VSCode',  
'source()', and 'Rscript' (Shells Including Windows Command Line /  
/ Unix Terminal)

**Description** Determine the path of the executing script. Works when  
running a line or selection in 'Rgui', 'RStudio', and 'VSCode',  
when using 'source()', 'sys.source()', 'debugSource()' in 'RStudio',  
'testthat::source\_file()', and 'knitr::knit()', and when running  
from a shell.

**Author** Andrew Simmons

**Maintainer** Andrew Simmons <akwsimmo@gmail.com>

**Suggests** utils, microbenchmark

**Enhances** knitr, rprojroot, rstudioapi, testthat

**URL** <https://github.com/ArcadeAntics/this.path>

**BugReports** <https://github.com/ArcadeAntics/this.path/issues>

**Biarch** TRUE

**Encoding** UTF-8

## R topics documented:

this.path-package . . . . .	2
Args . . . . .	3
as.relative.path . . . . .	5
basename2 . . . . .	6
check.path . . . . .	8
ext . . . . .	9
from.shell . . . . .	10
getinitwd . . . . .	11
here . . . . .	11
LINENO . . . . .	12
OS.type . . . . .	13
path.join . . . . .	14
R.from.shell . . . . .	15
shFILE . . . . .	17

Sys.putenv . . . . .	18
this.path . . . . .	19
this.path-defunct . . . . .	23
this.proj . . . . .	24
tryCatch2 . . . . .	24
wrap.source . . . . .	25

<b>Index</b>	<b>31</b>
--------------	-----------

---

this.path-package	<i>Get Executing Script's Path, from 'Rgui', 'RStudio', 'VSCode', source(), and Rscript (Shells Including Windows Command Line // Unix Terminal)</i>
-------------------	--

---

## Description

Determine the path of the executing script. Works when running a line or selection in 'Rgui', 'RStudio', and 'VSCode', when using `source`, `sys.source`, `debugSource` in 'RStudio', `testthat::source_file`, and `knitr::knit`, and when running from a shell.

## Details

`this.path()` returns the `normalized` path of the executing script.

`this.dir()` returns the `normalized` path of the directory in which the executing script is located.

`here()` constructs file paths relative to the executing script's directory.

`path.join()`, `basename2()`, and `dirname2()` are replacements for `file.path()`, `basename()`, and `dirname()` that better handle drives, network shares, and a few important edge cases.

`splitext()`, `removeext()`, `ext()`, and `ext<-()` split paths into root and extension, remove extensions, get extensions, and set extensions, respectively.

`check.path()` and `check.dir()` check that `this.path()` and `this.dir()` are functioning correctly.

`as.rel.path()` ( or `as.relative.path()` ) will turn absolute paths into relative paths.

`asArgs()`, `fileArgs()`, `progArgs()`, and `withArgs()` provide functionality for running scripts with arguments in the same session, as opposed to a new one with `Rscript`.

`is.main()` and `from.shell()` determine if an R script is the main executing script or is run from a shell.

`shFILE()` extracts 'FILE' from the command line arguments.

`tryCatch2()` adds argument `else.` that runs if no error is thrown. This helps to run extra code that is not intended to be protected by the condition handlers.

## Note

This package started from a stack overflow posting, found at:

<https://stackoverflow.com/questions/1815606/determine-path-of-the-executing-script>

If you like this package, please consider upvoting my answer so that more people will see it! If you have an issue with this package, please use `utils::bug.report(package = "this.path")` to report your issue.

**Author(s)**

Andrew Simmons

Maintainer: Andrew Simmons &lt;akwsimmo@gmail.com&gt;

**See Also**

[source](#), [sys.source](#), [debugSource](#) in ‘RStudio’, [testthat::source\\_file](#), [knitr::knit](#)  
[R.from.shell](#)

---

Args

*Providing Arguments to a Script*

---

**Description**

`withArgs` allows you to [source](#) an R script while providing arguments. As opposed to running with [Rscript](#), the code will be evaluated in the same session, in an environment of your choosing.

`fileArgs()` // `progArgs()` are generalized versions of [commandArgs\(trailingOnly = TRUE\)](#), allowing you to access the script’s arguments whether it was sourced or run from a shell.

`asArgs` coerces R objects into a character vector, for use with command line applications and `withArgs`.

**Usage**

```
asArgs(...)  
fileArgs()  
progArgs()  
withArgs(...)
```

**Arguments**

... R objects to turn into script arguments; typically [logical](#), [numeric](#), [character](#), [Date](#), and [POSIXt](#) vectors.  
for `withArgs`, the first argument should be an (unevaluated) call to [source](#), [sys.source](#), [debugSource](#) in ‘RStudio’, [testthat::source\\_file](#), or [knitr::knit](#).

**Details**

`fileArgs()` will return the arguments associated with the executing script, or `character(0)` when there is no executing script.

`progArgs()` will return the arguments associated with the executing script, or `commandArgs(trailingOnly = TRUE)` when there is no executing script.

`asArgs()` coerces objects into command-line arguments. ... is first put into a list, and then each non-list element is converted to character. They are converted as follows:

**Factors** (class `"factor"`) using [as.character.factor](#)

**Date-Times** (class `"POSIXct"` and `"POSIXlt"`) using format `"%Y-%m-%d %H:%M:%OS6"` (retains as much precision as possible)

**Numbers** (class `"numeric"` and `"complex"`) with 17 significant digits (retains as much precision as possible) and `"."` as the decimal point character.

**Raw Bytes** (class "raw") using `sprintf("0x%02x", )` (can easily convert back to raw with `as.raw()` or `as.vector(, "raw")`)

All others will be converted to character using `as.character` and its methods.

The arguments will then be unlisted, and all attributes will be removed. Arguments that are `NA_character_` after conversion will be converted to "NA" (since the command-line arguments also never have missing strings).

### Value

for `asArgs`, `fileArgs`, and `progArgs`, a character vector.

for `withArgs`, the result of evaluating `expr`.

### Examples

```
this.path::asArgs(
  NULL,
  c(TRUE, FALSE, NA),
  1:5,
  pi,
  exp(6i),
  letters[1:5],
  as.raw(0:4),
  as.Date("1970-01-01"),
  as.POSIXct("1970-01-01 00:00:00"),
  list(
    list(
      list(
        "lists are recursed"
      )
    )
  )
)

FILE <- tempfile(fileext = ".R")
this.path::write.code({
  withAutoprint({
    this.path::this.path()
    this.path::fileArgs()
    this.path::progArgs()
  }, spaced = TRUE, verbose = FALSE, width.cutoff = 60L)
}, FILE)

# wrap your source call with a call to 'withArgs'
this.path::withArgs(
  source(FILE, local = TRUE, verbose = FALSE),
  letters, pi, exp(1)
)
this.path::withArgs(
  sys.source(FILE, environment()),
  letters, pi + 1i * exp(1)
)
this.path::.Rscript(c("--default-packages=this.path", "--vanilla", FILE,
  this.path::asArgs(letters, pi, as.POSIXct("2022-07-17 04:25"))))
```

```

# with R >= 4.1.0, use the forward pipe operator '|>' to
# make calls to 'withArgs' more intuitive:
# source(FILE, local = TRUE, verbose = FALSE) |> this.path::withArgs(
#   letters, pi, exp(1)
# )
# sys.source(FILE, environment()) |> this.path::withArgs(
#   letters, pi + 1i * exp(1)
# )

# withArgs() also works with inside.source() and wrap.source()
sourcelike <- function (file, envir = parent.frame())
{
  file <- inside.source(file)
  envir <- as.environment(envir)
  exprs <- parse(n = -1, file = file, srcfile = NULL, keep.source = FALSE)
  for (i in seq_along(exprs)) eval(exprs[i], envir)
}
this.path::withArgs(sourcelike(FILE), letters)

sourcelike2 <- function (file, envir = parent.frame())
{
  envir <- as.environment(envir)
  exprs <- parse(n = -1, file = file, srcfile = NULL, keep.source = FALSE)
  for (i in seq_along(exprs)) eval(exprs[i], envir)
}
sourcelike3 <- function (file, envir = parent.frame())
{
  envir <- as.environment(envir)
  wrap.source(sourcelike2(file = file, envir = envir))
}
this.path::withArgs(sourcelike3(FILE), letters)
this.path::withArgs(wrap.source(sourcelike2(FILE)), letters)

```

---

as.relative.path

*Make a Path Relative to Another Path*


---

## Description

When working with **this.path**, you will be dealing with a lot of absolute paths. These paths are not good for saving within files, so you will need to use `as.relative.path()` to turn your absolute paths into relative paths.

## Usage

```

as.relative.path(path, relative.to = this.dir(verbose = FALSE))
as.rel.path      (path, relative.to = this.dir(verbose = FALSE))
relpath         (path, relative.to = getwd())

```

**Arguments**

path                    character vector of file // URL paths.  
 relative.to            character string; the file // URL path to make path relative to.

**Details**

Tilde-expansion (see [path.expand](#)) is first done on path and relative.to.

If path and relative.to are equivalent, "." will be returned. If path and relative.to have no base in common, the [normalized](#) path will be returned.

**Value**

character vector of the same length as path.

**Note**

relpath and as.rel.path are the same function with different default arguments.

**Examples**

```
## Not run:
relpath(
  c(
    # paths which are equivalent will return "."
    "C:/Users/effective_user/Documents/this.path/man",

    # paths which have no base in common return as themselves
    "https://raw.githubusercontent.com/ArcadeAntics/this.path/main/tests/this.path_w_URLs.R",
    "D:/",
    "//host-name/share-name/path/to/file",

    "C:/Users/effective_user/Documents/testing",
    "C:\\Users\\effective_user",
    "C:/Users/effective_user/Documents/R/this.path.R"
  ),
  relative.to = "C:/Users/effective_user/Documents/this.path/man"
)

## End(Not run)
```

**Description**

basename2 removes all of the path up to and including the last path separator (if any).

dirname2 returns the part of the path up to but excluding the last path separator, or "." if there is no path separator.

## Usage

```
basename2(path)
dirname2(path)
```

## Arguments

path                    character vector, containing path names.

## Details

[tilde expansion](#) of the path will be performed.

Trailing path separators are removed before dissecting the path, and for `dirname2()` any trailing file separators are removed from the result.

## Value

A character vector of the same length as path.

## Behaviour on Windows

If path is an empty string, then both `dirname2()` and `basename2()` return an empty string.

`\` and `/` are accepted as path separators, and `dirname2()` does **NOT** translate the path separators.

Recall that a network share looks like `//host/share` and a drive looks like `d:`.

For a path which starts with a network share or drive, the path specification is the portion of the string immediately afterward, e.g. `/path/to/file` is the path specification of `//host/share/path/to/file` and `d:/path/to/file`. For a path which does not start with a network share or drive, the path specification is the entire string.

And lastly, the path specification of a network share will always be empty or absolute, but the path specification of a drive does not have to be, e.g. `d:file` is a valid path despite the fact that the path specification does not begin with `/`.

If the path specification of path is empty or is `/`, then `dirname2()` will return path and `basename2()` will return an empty string.

## Behaviour Elsewhere

If path is an empty string, then both `dirname2()` and `basename2()` return an empty string.

Recall that a network share looks like `//host/share`.

For a path which starts with a network share, the path specification is the portion of the string immediately afterward, e.g. `/path/to/file` is the path specification of `//host/share/path/to/file`. For a path which does not start with a network share, the path specification is the entire string.

If the path specification of path is empty or is `/`, then `dirname2()` will return path and `basename2()` will return an empty string.

## Examples

```
path <- c("/usr/lib", "/usr/", "usr", "/", ".", "..")
print(cbind(
  path, dirname = dirname2(path), basename = basename2(path)),
  quote = FALSE, print.gap = 3)
```

---

`check.path`*Check this.path() is Functioning Correctly*

---

### Description

Add `check.path("path/to/file")` to the beginning of your script to initialize `this.path()`, and check that `this.path()` is returning the path you expect.

### Usage

```
check.path(...)  
check.dir(...)
```

### Arguments

... further arguments passed to `path.join` which must return a character string; the path you expect `this.path()` or `this.dir()` to return. The specified path can be as deep as necessary (just the basename, the last directory and the basename, the last two directories and the basename, ...), but using an absolute path is not intended (recommended against). `this.path()` makes R scripts portable, but using an absolute path in `check.path` or `check.dir` makes an R script non-portable, defeating the whole purpose of this package.

### Value

If the expected path // directory matches `this.path()` // `this.dir()`, then TRUE invisibly. Otherwise, an error is raised.

### Examples

```
# I have a project called 'EOAdjusted'  
#  
# Within this project, I have a folder called 'code'  
# where I place all of my scripts.  
#  
# One of these scripts is called 'provr.R'  
#  
# So, at the top of that R script, I could write:  
  
# this.path::check.path("EOAdjusted", "code", "provr.R")  
#  
# or  
#  
# this.path::check.path("EOAdjusted/code/provr.R")
```

---

ext	<i>File Extensions</i>
-----	------------------------

---

**Description**

`splitext` splits an extension from a path.  
`removeext` removes an extension from a path.  
`ext` gets the extension of a path.  
`ext<-` sets the extension of a path.

**Usage**

```
splitext(path, compression = FALSE)
removeext(path, compression = FALSE)
ext(path, compression = FALSE)
ext(path, compression = FALSE) <- value
```

**Arguments**

<code>path</code>	character vector, containing path names.
<code>compression</code>	should compression extensions <code>'gz'</code> , <code>'bz2'</code> , and <code>'xz'</code> be taken into account when removing/getting an extension?
<code>value</code>	a character vector, typically of length 1 or <code>length(path)</code> , or <code>NULL</code> .

**Details**

[tilde expansion](#) of the path will be performed.  
Trailing path separators are removed before dissecting the path.  
It will always be true that `path == paste0(removeext(path), ext(path))`.

**Value**

for `splitext`, a matrix with 2 rows and `length(path)` columns. The first row will be the roots of the paths, the second row will be the extensions of the paths.  
for `removeext` and `ext`, a character vector the same length as `path`.  
for `ext<-`, the updated object.

**Examples**

```
splitext(character(0))
splitext("")

splitext("file.ext")

splitext(c("file.tar.gz", "file.tar.bz2", "file.tar.xz"), compression = FALSE)
splitext(c("file.tar.gz", "file.tar.bz2", "file.tar.xz"), compression = TRUE)

x <- "this.path_1.0.0.tar.gz"
ext(x) <- ".png"
x
```

```
x <- "this.path_1.0.0.tar.gz"
ext(x, compression = TRUE) <- ".png"
x
```

---

 from.shell

*Top-Level Code Environment*


---

## Description

Determine if a program is the main program, or if an R script was run from a shell.

## Usage

```
from.shell()
is.main()
```

## Details

When an R script is run from a shell, `from.shell()` and `is.main()` will both be TRUE. If that script sources another R script, `from.shell()` and `is.main()` will both be FALSE for the duration of the second script.

Otherwise, `from.shell()` will be FALSE. `is.main()` will be TRUE when there is no executing script or when source-ing a script in a toplevel context, and FALSE otherwise.

## Value

TRUE or FALSE.

## Examples

```
FILES <- tempfile(c("file1_", "file2_"), fileext = ".R")
this.path::write.code(file = FILES[1], bquote(withAutoprint({
  from.shell()
  is.main()
  source(.FILES[2]), echo = TRUE, verbose = FALSE,
    prompt.echo = "file2> ", continue.echo = "file2+ ")
}), spaced = TRUE, verbose = FALSE, width.cutoff = 60L,
  prompt.echo = "file1> ", continue.echo = "file1+ "))
this.path::write.code({
  from.shell()
  is.main()
}, FILES[2])
```

```
this.path::.Rscript(c("--default-packages=this.path", "--vanilla", FILES[1]))
```

```
this.path::.Rscript(c("--default-packages=this.path", "--vanilla",
  "-e", "cat(\\\"\\n> from.shell()\\\"\\n\\")",
  "-e", "from.shell()",
  "-e", "cat(\\\"\\n> is.main()\\\"\\n\\")",
  "-e", "is.main()",
```

```
"-e", "cat(\n\n> source(commandArgs(TRUE)[1L], verbose = FALSE)\n\n)",
"-e", "source(commandArgs(TRUE)[1L], verbose = FALSE)",
FILES[1]))
```

---

getinitwd

*Get Initial Working Directory*


---

### Description

getinitwd returns an absolute filepath representing the working directory at the time of loading this package.

### Usage

```
getinitwd()
initwd
```

### Value

getinitwd returns a character string or NULL if the working directory is not available.

### Examples

```
cat("initial working directory:\n")
getinitwd()

cat("current working directory:\n")
getwd()
```

---

here

*Construct Path to File, Beginning with this.dir()*


---

### Description

Construct the path to a file from components/paths in a platform-**DEPENDENT** way, starting with [this.dir\(\)](#).

### Usage

```
here(..., .. = 0)
ici(..., .. = 0)
```

### Arguments

```
...      further arguments passed to path.join\(\).
..       the number of directories to go back.
```

### Details

The path to a file begins with a base. The base is .. number of directories back from the executing script's directory ([this.dir\(\)](#)). The argument is named .. because "." refers to the parent directory in Windows, Unix, and URL paths alike.

**Value**

A character vector of the arguments concatenated term-by-term, beginning with the executing script's directory.

**Examples**

```
FILE <- tempfile(fileext = ".R")
this.path::write.code({

  this.path::here()
  this.path::here(.. = 1)
  this.path::here(.. = 2)

  # use 'here' to read input from a file located nearby
  this.path::here(.. = 1, "input", "file1.csv")

  # or maybe to run another script
  this.path::here("script2.R")

}, FILE)

source(FILE, echo = TRUE, verbose = FALSE)
```

---

 LINENO

---

*Line Number of Executing Script*


---

**Description**

Get the line number of the executing script.

**Usage**

```
LINENO()
```

**Value**

An integer, NA\_integer\_ if the line number cannot be determined.

**Note**

LINENO() only works if the executing script has a [srcref](#) and a [srcfile](#). Scripts run with [Rscript](#) do not store their [srcref](#), even when [getOption\("keep.source"\)](#) is TRUE.

For [source](#) or [sys.source](#), make sure to supply argument `keep.source = TRUE` directly, or set the options `"keep.source"` or `"keep.source.pkgs"` to TRUE.

For [debugSource](#) in 'RStudio', it has no argument `keep.source`, so set the option `"keep.source"` to TRUE before calling.

For `testthat::source_file`, the `srcref` is always stored, so you do not need to do anything special before calling.

For `knitr::knit`, there is nothing that can be done, the `srcref` is never stored. I am looking into a fix for such a thing.

## Examples

```
FILE <- tempfile(fileext = ".R")
writelines(c(
  "LINENO()",
  "LINENO()",
  "# LINENO() respects #line directives",
  "#line 1218",
  "LINENO()"
), FILE)

# previously used:
#
# ```
# source(FILE, echo = TRUE, verbose = FALSE,
#   max.deparse.length = Inf, keep.source = TRUE)
# ```
#
# but it echoes incorrectly with #line directives.
# `source2()` echoes correctly!
this.path:::source2(FILE, echo = TRUE, verbose = FALSE,
  max.deparse.length = Inf, keep.source = TRUE)
```

---

OS.type

*Detect the Operating System Type*

---

## Description

OS.type is a list of TRUE/FALSE values dependent of the platform under which this package was built.

## Usage

```
OS.type
```

## Value

A list with at least the following components:

AIX	Built under IBM AIX.
HPUX	Built under Hewlett-Packard HP-UX.
linux	Built under some distribution of Linux.
darwin	Built under Apple OSX and iOS (Darwin).
iOS.simulator	Built under iOS in Xcode simulator.
iOS	Built under iOS on iPhone, iPad, etc.

macOS	Built under OSX.
solaris	Built under Solaris (SunOS).
cygwin	Built under Cygwin POSIX under Microsoft Windows.
windows	Built under Microsoft Windows.
win64	Built under Microsoft Windows (64-bit).
win32	Built under Microsoft Windows (32-bit).
UNIX	Built under a UNIX-style OS.

**Source**

[http://web.archive.org/web/20191012035921/http://nadeausoftware.com/articles/2012/01/c\\_c\\_tip\\_how\\_use\\_compiler\\_p](http://web.archive.org/web/20191012035921/http://nadeausoftware.com/articles/2012/01/c_c_tip_how_use_compiler_p)

---

path.join	<i>Construct Path to File</i>
-----------	-------------------------------

---

**Description**

Construct the path to a file from components/paths in a platform-**DEPENDENT** way.

**Usage**

```
path.join(...)
```

**Arguments**

... character vectors.

**Details**

When constructing a path to a file, the last absolute path is selected and all trailing paths are appended. This is different from [file.path](#) where all trailing paths are treated as components.

**Value**

A character vector of the arguments concatenated term-by-term and separated by "/".

**Examples**

```
path.join("C:", "test1")
path.join("C:/", "test1")
path.join("C:/path/to/file1", "/path/to/file2")
path.join("//host-name/share-name/path/to/file1", "/path/to/file2")
path.join("C:testing", "C:/testing", "~", "~/testing", "//host",
  "//host/share", "//host/share/path/to/file", "not-an-abs-path")
path.join("c:/test1", "c:test2", "C:test3")
path.join("test1", "c:/test2", "test3", "//host/share/test4", "test5",
  "c:/test6", "test7", "c:test8", "test9")
```

## Description

How to use R from a shell (including the Windows command-line // Unix terminal).

## Details

For the purpose of running R scripts, there are four ways to do it. Suppose our R script has filename 'script1.R', we could write any of:

- R -f script1.R
- R --file=script1.R
- R CMD BATCH script1.R
- Rscript script1.R

The first two are different ways of writing equivalent statements. The third statement is the first statement plus options '--restore' '--save' (plus option '--no-readline' under Unix-alikes), and it also saves the `stdout` and `stderr` in a file of your choosing. The fourth statement is the second statement plus options '--no-echo' '--no-restore'. You can try:

- R --help
- R CMD BATCH --help
- Rscript --help

for a help message that describes what these options mean. In general, Rscript is the one you want to use. It should be noted that Rscript has some exclusive [environment variables](#) (not used by the other executables) that will make its behaviour different from R.

For the purpose of making packages, R CMD is what you will need. Most commonly, you will use:

- R CMD build
- R CMD INSTALL
- R CMD check

R CMD build will turn an R package (specified by a directory) into tarball. This allows for easy sharing of R packages with other people, including [submitting a package to CRAN](#). R CMD INSTALL will install an R package (specified by a directory or tarball), and is used by `utils::install.packages`. R CMD check will check an R package (specified by a tarball) for possible errors in code, documentation, tests, and much more.

If, when you execute one of the previous commands, you see the following error message: “‘R’ is not recognized as an internal or external command, operable program or batch file.”, see section **Ease of Use on Windows**.

## Ease of Use on Windows

Under Unix-alikes, it is easy to invoke an R session from a shell by typing the name of the R executable you wish to run. On Windows, you should see that typing the name of the R executable you wish to run does not run that application, but instead signals an error. Instead, you will have to type the full path of the directory where your R executables are located (see section **Where are my R executable files located?**), followed by the name of the R executable you wish to run.

This is not very convenient to type everytime something needs to be run from a shell, plus it has another issue of being computer dependent. The solution is to add the path of the directory where your R executables are located to the Path environment variable. The Path environment variable is a list of directories where executable programs are located. When you type the name of an executable program you wish to run, Windows looks for that program through each directory in the Path environment variable. When you add the full path of the directory where your R executables are located to your Path environment variable, you should be able to run any of those executable programs by their basenames ('R', 'Rcmd', 'Rscript', and 'Rterm') instead of their full paths.

To add a new path to your Path environment variable:

1. Open the **Control Panel**
2. Open category **User Accounts**
3. Open category **User Accounts** (again)
4. Open **Change my environment variables**
5. Click the variable Path
6. Click the button **Edit...**
7. Click the button **New**
8. Type (or paste) the full path of the directory where your R executables are located, and press **OK**

This will modify your environment variable Path, not the systems. If another user wishes to run R from a shell, they will have to add the directory to their Path environment variable as well.

If you wish to modify the system environment variable Path (you will need admin permissions):

1. Open the **Control Panel**
2. Open category **System and Security**
3. Open category **System**
4. Open **Advanced system settings**
5. Click the button **Environment Variables...**
6. Modify Path same as before, just select Path in **System variables** instead of **User variables**

To check that this worked correctly, open a shell and execute the following commands:

- R --help
- R --version

You should see that the first prints the usage message for the R executable while the second prints information about the version of R currently being run. If you have multiple versions of R installed, make sure this is the version of R you wish to run.

### Where are my R executable files located?

In an R session, you can find the location of your R executable files with the following command:

```
cat(sQuote(normalizePath(R.home("bin"))), "\n")
```

For me, this is:

```
'C:\Program Files\R\R-4.2.2\bin\x64'
```

---

shFILE *Get Argument 'FILE' Provided to R by a Shell*

---

### Description

Look through the command line arguments, extracting 'FILE' from either of the following: '-f' 'FILE' or '--file=FILE'

### Usage

```
shFILE(original = FALSE, for.msg = FALSE, default, else.)
```

### Arguments

original	TRUE, FALSE, or NA; should the original or the normalized path be returned? NA means the normalized path will be returned if it has already been forced, and the original path otherwise.
for.msg	TRUE or FALSE; do you want the path for the purpose of printing a diagnostic message // warning // error? for.msg = TRUE will ignore original = FALSE, and will use original = NA instead.
default	if 'FILE' is not found, this value is returned.
else.	missing or a function to apply if 'FILE' is found. See <a href="#">tryCatch2</a> for inspiration.

### Value

character string, or default if the command line argument 'FILE' was not found.

### Note

The original and the normalized path are saved; this makes them faster when called subsequent times.

In Windows, the normalized path will use / as the file separator.

### See Also

[this.path, here](#)

### Examples

```
FILE <- tempfile(fileext = ".R")
this.path::write.code({
  withAutoprint({
    shFILE(original = TRUE)
    shFILE()
    shFILE(default = {
      stop("since 'FILE' will be found, argument 'default' will not\n",
          " be evaluated, so this error will not be thrown! you can\n",
          " use this to your advantage in a similar manner, doing\n",
          " arbitrary things only if 'FILE' is not found")
    })
  }, spaced = TRUE, verbose = FALSE, width.cutoff = 60L)
}, FILE)
```

```

this.path::.Rscript(c("--default-packages=this.path", "--vanilla", FILE))

for (expr in c("shFILE(original = TRUE)",
              "shFILE(original = TRUE, default = NULL)",
              "shFILE()",
              "shFILE(default = NULL)"))
{
  cat("\n\n")
  this.path::.Rscript(c("--default-packages=this.path", "--vanilla", "-e", expr))
}

```

---

Sys.putenv

*Set Environment Variables*


---

### Description

Sys.putenv sets environment variables (for other processes called from within R or future calls to [Sys.getenv](#) from this R process).

### Usage

```
Sys.putenv(x)
```

### Arguments

x a character vector, or an object coercible to character. Strings must be of the form "name=value".

### Value

A logical vector, with elements being true if setting the corresponding variable succeeded.

### See Also

[Sys.setenv](#)

### Examples

```

Sys.putenv(c("R_TEST=testit", "A+C=123"))
Sys.getenv("R_TEST")
Sys.unsetenv("R_TEST") # on Unix-alike may warn and not succeed
Sys.getenv("R_TEST", unset = NA)

```

---

this.path	<i>Determine Executing Script's Filename</i>
-----------	--

---

### Description

this.path() returns the [normalized](#) path of the executing script.

this.dir() returns the [normalized](#) path of the directory in which the executing script is located.

See also [here](#)() for constructing paths to files, starting with this.dir().

Sys.path() and Sys.dir() are versions of this.path() and this.dir() that takes no arguments.

### Usage

```
this.path(verbose = getOption("verbose"), original = FALSE,
          for.msg = FALSE, default, else.)
```

```
this.dir (verbose = getOption("verbose"), default, else.)
```

```
Sys.path() # short for 'this.path(verbose = FALSE)'
```

```
Sys.dir () # short for 'this.dir (verbose = FALSE)'
```

### Arguments

verbose	TRUE or FALSE; should the method in which the path was determined be printed?
original	TRUE, FALSE, or NA; should the original or the normalized path be returned? NA means the normalized path will be returned if it has already been forced, and the original path otherwise.
for.msg	TRUE or FALSE; do you want the path for the purpose of printing a diagnostic message // warning // error? This will return <code>NA_character_</code> in most cases where an error would have been thrown. for.msg = TRUE will ignore original = FALSE, and will use original = NA instead.
default	if there is no executing script, this value is returned.
else.	missing or a function to apply if there is an executing script. See <a href="#">tryCatch2</a> for inspiration.

### Details

There are three ways in which R code is typically run:

1. in 'RStudio' // 'Rgui' // 'VSCode' by running the current line // selection with the **Run** button // appropriate keyboard shortcut
2. through a source call: a call to function `source`, `sys.source`, `debugSource` in 'RStudio', `testthat::source_file`, or `knitr::knit`
3. from a shell, such as the Windows command-line // Unix terminal

To retrieve the executing script's filename, first an attempt is made to find a source call. The calls are searched in reverse order so as to grab the most recent source call in the case of nested source calls. If a source call was found, the file argument is returned from the function's evaluation environment. If you have your own source-like function that you would like to be recognized by this.path, please contact the package maintainer so that it can be implemented or use [inside.source](#)() .

If no source call is found up the calling stack, then an attempt is made to figure out how R is currently being used.

If R is being run from a shell, the shell arguments are searched for `'-f' 'FILE'` or `'--file=FILE'` (the two methods of taking input from `'FILE'`). `this.path()` used to insist that exactly one of either type of argument must be supplied, but this has since been changed. Now, the last `'FILE'` argument is extracted (ignoring `'-f' '-'` and `'--file=-'`) and returned. It is an error to use `this.path()` if no arguments of either type are supplied.

If R is being run from a shell under Unix-alikes with `'-g' 'Tk'` or `'--gui=Tk'`, `this.path()` will signal an error. `'Tk'` does not make use of its `'-f' 'FILE'`, `'--file=FILE'` arguments.

If R is being run from `'RStudio'`, the active document's filename (the document in which the cursor is active) is returned (at the time of evaluation). If the active document is the R console, the source document's filename (the document open in the current tab) is returned (at the time of evaluation). Please note that the source document will *NEVER* be a document open in another window (with the **Show in new window** button). It is important to not leave the current tab (either by closing or switching tabs) while any calls to `this.path()` have yet to be evaluated in the run selection. It is an error for no documents to be open or for a document to not exist (not saved anywhere).

If R is being run from `'Rgui'`, the source document's filename (the document most recently interacted with besides the R Console) is returned (at the time of evaluation). Please note that minimized documents *WILL* be included when looking for the most recently used document. It is important to not leave the current document (either by closing the document or interacting with another document) while any calls to `this.path()` have yet to be evaluated in the run selection. It is an error for no documents to be open or for a document to not exist (not saved anywhere).

If R is being run `'VSCode'`, the source document's filename is returned (at the time of evaluation). It is important to not leave the current tab (either by closing or switching tabs) while any calls to `this.path()` have yet to be evaluated in the run selection. It is an error for a document to not exist (not saved anywhere).

If R is being run from `'AQUA'`, the executing script's path cannot be determined. Unlike `'RStudio'`, `'Rgui'`, and `'VSCode'`, there is currently no way to request the path of an open document. Until such a time that there is a method for requesting the path of an open document, consider using `'RStudio'` or `'VSCode'`.

If R is being run in another manner, it is an error to use `this.path`.

If your GUI of choice is not implemented with `this.path`, please contact the package maintainer so that it can be implemented.

## Value

character string; the executing script's filename.

## Note

The first time `this.path()` is called within a script, it will [normalize](#) the script's path, checking that the script exists (throwing an error if it does not), and save it in the appropriate environment. When `this.path()` is called subsequent times within the same script, it returns the saved path. This will be faster than the first time, will not check for file existence, and will be independent of the working directory.

As a side effect, this means that a script can delete itself using [file.remove](#) or [unlink](#) but still know its own path for the remainder of the script.

Within a script that contains calls to both `this.path()` and `setwd()`, `this.path()` *MUST* be used *AT LEAST* once before the first call to `setwd()`. This is not always necessary; if you ran a script

using its absolute path as opposed to its relative path, changing the working directory has no effect. However, it is still advised against.

The following is *NOT* an example of bad practice:

```
setwd(this.path::this.dir())
```

setwd() is most certainly written before this.path(), but this.path() will be evaluated first. It is not the written order that is bad practice, but the order of evaluation. Do not change the working directory before calling this.path() at least once.

Please **DO NOT** use this.path() inside the site-wide startup profile file, the user profile, nor the function .First (see ?Startup). This has inconsistent results dependent on the GUI, and often incorrect. For example:

**in ‘RStudio’** in all three cases, it throws an error:

```
> this.path(original = TRUE)
Error in (.rs.api.getActiveDocumentContext)() :
  RStudio has not finished loading
```

**in ‘VSCode’** in the site-wide startup profile file and the function .First, it throws an error:

```
> this.path(original = TRUE)
Error : RStudio not running
```

but in the user profile, it returns:

```
> this.path(original = TRUE)
Source: call to function source
[1] "~/Rprofile"
```

```
> this.path()
[1] "C:/Users/iris/Documents/.Rprofile"
```

**in ‘Rgui’** in all three cases, it throws an error:

```
> this.path(original = TRUE)
Error in .this.path(verbose, original, for.msg) :
  'this.path' used in an inappropriate fashion
* no appropriate source call was found up the calling stack
* R is being run from Rgui with no documents open
```

**in ‘Rterm’** in all three cases, it returns the command line argument ‘FILE’:

```
> this.path(original = TRUE)
Source: shell argument 'FILE'
[1] "./file569c63d647ba.R"
```

```
> this.path()
[1] "C:/Users/iris/AppData/Local/Temp/RtmpGMmR3A/file569c63d647ba.R"
```

Sometimes it returns the command line argument ‘FILE’, sometimes it returns the path of the user profile, and other times it throws an error. Alternatively, you could use `shFILE()`, supplying a default argument when no ‘FILE’ is specified, and supplying an `else.` function for when one is specified.

**See Also**

[here](#)  
[shFILE](#)  
[wrap.source, inside.source](#)  
[this.path-package](#)  
[source, sys.source, debugSource](#) in ‘RStudio’, [testthat::source\\_file](#), [knitr::knit](#)  
[R.from.shell](#)

**Examples**

```

FILE <- tempfile(fileext = ".R")
this.path::write.code({
  withAutoprint({
    cat(sQuote(this.path::this.path(verbose = TRUE, default = {
      stop("since the executing script's path will be found, argument\n",
        " 'default' will not be evaluated, so this error will not\n",
        " be thrown! you can use this to your advantage in a\n",
        " similar manner, doing arbitrary things only if the\n",
        " executing script does not exist")
    })), "\n\n")
  }, spaced = TRUE, verbose = FALSE, width.cutoff = 60L)
}, FILE)

```

```

source(FILE, verbose = FALSE)
sys.source(FILE, envir = environment())
if (.Platform$GUI == "RStudio")
  get("debugSource", "tools:rstudio", inherits = FALSE)(FILE)
if (requireNamespace("testthat"))
  testthat::source_file(FILE, chdir = FALSE, wrap = FALSE)
if (requireNamespace("knitr")) {
  writelines(con = FILE2 <- tempfile(fileext = ".Rmd"), c(
    "```\n",
    # same expression as above
    deparse(parse(FILE)[[c(1L, 2L, 2L)]]),
    "```\n"
  ))
  knitr::knit(input = FILE2, output = FILE3 <- tempfile(fileext = ".md"),
    quiet = TRUE)
  cat(sprintf("\n$ cat -bsT %s\n", shQuote(FILE2)))
  this.path::cat.file(FILE2, number.nonblank = TRUE,
    squeeze.blank = TRUE, show.tabs = TRUE)
  cat(sprintf("\n$ cat -bsT %s\n", shQuote(FILE3)))
  this.path::cat.file(FILE3, number.nonblank = TRUE,
    squeeze.blank = TRUE, show.tabs = TRUE)
  cat("\n")
  unlink(c(FILE3, FILE2))
}

```

```
this.path::.Rscript(c("--default-packages=NULL", "--vanilla", FILE))
```

```
# this.path also works when source-ing a URL
```

```

# (included tryCatch in case an internet connection is not available)
tryCatch({
  source("https://raw.githubusercontent.com/ArcadeAntics/this.path/main/tests/this.path_w_URLs.R")
}, condition = message)

for (expr in c("this.path()",
              "this.path(default = NULL)",
              "this.dir()",
              "this.dir(default = NULL)",
              "this.dir(default = getwd())"))
{
  cat("\n\n")
  this.path:::Rscript(c("--default-packages=this.path", "--vanilla", "-e", expr))
}

# an example from R package 'logr'
this.path::this.path(verbose = FALSE, default = "script.log",
  else. = function(path) {
    # replace extension (probably .R) with .log
    this.path:::ext(path) <- ".log"
    path
    # or you could use paste0(this.path:::removeext(path), ".log")
  })

```

---

this.path-defunct      *Defunct Functions in Package* **this.path**

---

## Description

The functions or variables listed here are no longer part of **this.path** as they are no longer needed.

## Usage

```

# Defunct in 1.1.0
this.path2(...)      # use 'this.path(..., default = NULL)' instead
this.dir2(...)      # use 'this.dir(..., default = NULL)' instead
this.dir3(...)      # use 'this.dir(..., default = getwd())' instead
normalized.shFILE(...) # use 'shFILE()' instead

```

## Arguments

...

## See Also

[this.path](#), [this.dir](#)

---

 this.proj
 

---



---

*Construct Path to File, Beginning with Your Project Directory*


---

**Description**

this.proj behaves very similarly to here::here except that you can have multiple projects in use at once, and it will choose which project directory is appropriate based on `this.dir()`. Arguably, this makes it better than here::here.

**Usage**

```
this.proj(...)
```

**Arguments**

... further arguments passed to `path.join()`.

**Value**

A character vector of the arguments concatenated term-by-term, beginning with the project directory.

**See Also**

[here](#)

---

 tryCatch2
 

---



---

*Condition Handling and Recovery*


---

**Description**

A variant of `tryCatch` that accepts an `else.` argument, similar to `try except` in ‘Python’.

**Usage**

```
tryCatch2(expr, ..., else., finally)
```

**Arguments**

`expr` expression to be evaluated.

... condition handlers.

`else.` expression to be evaluated if evaluating `expr` does not throw an error nor a condition is caught.

`finally` expression to be evaluated before returning or exiting.

**Details**

The use of the `else.` argument is better than adding additional code to `expr` because it avoids accidentally catching a condition that was not being protected by the `tryCatch` call.

## Examples

```
FILES <- tempfile(c("existent-file_", "non-existent-file_"))
writeLines("line1\nline2", FILES[[1L]])
for (FILE in FILES) {
  con <- file(FILE)
  tryCatch2({
    open(con, "r")
  }, condition = function(cond) {
    cat("cannot open", FILE, "\n")
  }, else. = {
    cat(FILE, "has", length(readLines(con)), "lines\n")
  }, finally = {
    close(con)
  })
}
unlink(FILES)
```

---

 wrap.source

*Implement this.path() For Arbitrary source-Like Functions*


---

## Description

A source-like function is any function which evaluates code from a file.

Currently, `this.path()` is implemented to work with `source`, `sys.source`, `debugSource` in ‘RStudio’, `testthat::source_file`, and `knitr::knit`.

`wrap.source()` and `inside.source()` can be used to implement `this.path()` for any other source-like functions.

`set.this.path()` is just an alias for `inside.source()`.

## Usage

```
wrap.source(expr,
  path.only = FALSE,
  character.only = path.only,
  file.only = path.only,
  conv2utf8 = FALSE,
  allow.blank.string = FALSE,
  allow.clipboard = !file.only,
  allow.stdin = !file.only,
  allow.url = !file.only,
  allow.file.uri = !path.only,
  allow.unz = !path.only,
  allow.pipe = !file.only,
  allow.terminal = !file.only,
  allow.textConnection = !file.only,
  allow.rawConnection = !file.only,
  allow.sockconn = !file.only,
  allow.servsockconn = !file.only,
  allow.customConnection = !file.only,
  ignore.all = FALSE,
  ignore.blank.string = ignore.all,
```

```
ignore.clipboard = ignore.all,  
ignore.stdin = ignore.all,  
ignore.url = ignore.all,  
ignore.file.uri = ignore.all)  
  
inside.source(file,  
  path.only = FALSE,  
  character.only = path.only,  
  file.only = path.only,  
  conv2utf8 = FALSE,  
  allow.blank.string = FALSE,  
  allow.clipboard = !file.only,  
  allow.stdin = !file.only,  
  allow.url = !file.only,  
  allow.file.uri = !path.only,  
  allow.unz = !path.only,  
  allow.pipe = !file.only,  
  allow.terminal = !file.only,  
  allow.textConnection = !file.only,  
  allow.rawConnection = !file.only,  
  allow.sockconn = !file.only,  
  allow.servsockconn = !file.only,  
  allow.customConnection = !file.only,  
  ignore.all = FALSE,  
  ignore.blank.string = ignore.all,  
  ignore.clipboard = ignore.all,  
  ignore.stdin = ignore.all,  
  ignore.url = ignore.all,  
  ignore.file.uri = ignore.all)  
  
set.this.path(file,  
  path.only = FALSE,  
  character.only = path.only,  
  file.only = path.only,  
  conv2utf8 = FALSE,  
  allow.blank.string = FALSE,  
  allow.clipboard = !file.only,  
  allow.stdin = !file.only,  
  allow.url = !file.only,  
  allow.file.uri = !path.only,  
  allow.unz = !path.only,  
  allow.pipe = !file.only,  
  allow.terminal = !file.only,  
  allow.textConnection = !file.only,  
  allow.rawConnection = !file.only,  
  allow.sockconn = !file.only,  
  allow.servsockconn = !file.only,  
  allow.customConnection = !file.only,  
  ignore.all = FALSE,  
  ignore.blank.string = ignore.all,  
  ignore.clipboard = ignore.all,  
  ignore.stdin = ignore.all,
```

```
ignore.url = ignore.all,
ignore.file.uri = ignore.all)
```

## Arguments

expr	an (unevaluated) call to a source-like function.
file	a <a href="#">connection</a> or a character string giving the pathname of the file or URL to read from.
path.only	must file be an existing path? This implies character.only and file.only are TRUE and implies allow.file.uri and allow.unz are FALSE, though these can be manually changed.
character.only	must file be a character string?
file.only	must file refer to an existing file?
conv2utf8	if file is a character string, should it be converted to UTF-8?
allow.blank.string	may file be a blank string, i.e. ""?
allow.clipboard	may file be "clipboard" or a clipboard connection?
allow.stdin	may file be "stdin"? Note that "stdin" refers to the C-level 'standard input' of the process, differing from <a href="#">stdin()</a> which refers to the R-level 'standard input'.
allow.url	may file be a URL pathname or a connection of class "url-libcurl" // "url-wininet"?
allow.file.uri	may file be a 'file://' URI?
allow.unz, allow.pipe, allow.terminal, allow.textConnection, allow.rawConnection, allow.sockconn, a	may file be a connection of class "unz" // "pipe" // "terminal" // "textConnection" // "rawConnection" // "sockconn" // "servsockconn"?
allow.customConnection	may file be a custom connection?
ignore.all, ignore.blank.string, ignore.clipboard, ignore.stdin, ignore.url, ignore.file.uri	ignore the special meaning of these types of strings, treating it as a path instead?

## Details

`inside.source()` should be added to the body of your source-like function before reading // evaluating the expressions.

`wrap.source()`, unlike `inside.source()`, does not accept an argument `file`. Instead, an attempt is made to extract the file from `expr`, after which `expr` is evaluated. It is assumed that the file is the first argument of the function, as is the case with [source](#), [sys.source](#), [debugSource](#) in 'RStudio', [testthat::source\\_file](#), and [knitr::knit](#). The function of the call is evaluated, its [formals\(\)](#) are retrieved, and then the arguments of `expr` are searched for a name matching the name of the first formal argument. If a match cannot be found by name, the first unnamed argument is taken instead. If no such argument exists, the file is assumed missing.

`wrap.source()` does non-standard evaluation and does some guess work to determine the file. As such, it is less desirable than `inside.source()` when the option is available. I can think of exactly one scenario in which `wrap.source()` might be preferable: suppose there is a source-like function `sourcelike()` in a foreign package (a package for which you do not have write permission). Suppose that you write your own function in which the `formals` are (...) to wrap `sourcelike()`:

```

wrapper <- function (...)
{
  # possibly more args to wrap.source()
  wrap.source(sourcelike(...))
}

```

This is the only scenario in which `wrap.source()` is preferable, since extracting the file from the `...` list would be a pain. Then again, you could simply change the formals of `wrapper()` from `(...)` to `(file, ...)`. If this does not describe your exact scenario, use `inside.source()` instead.

### Value

for `wrap.source`, the result of evaluating `expr`.

for `inside.source`, if `file` is a path, then the normalized path with the same attributes, otherwise file itself. The return value of `inside.source()` should be assigned to a variable before use, something like:

```

{
  file <- inside.source(file, ...)
  sourcelike(file)
}

```

### Note

Both functions should only be called within another function.

Suppose that the functions `source`, `sys.source`, `debugSource` in 'RStudio', `testthat::source_file`, and `knitr::knit` were not implemented with this `path()`. You could use `inside.source()` to implement each of them as follows:

```

source wrapper <- function(file, ...) {
  file <- inside.source(file)
  source(file = file, ...)
}

sys.source wrapper <- function(file, ...) {
  file <- inside.source(file, path.only = TRUE)
  sys.source(file = file, ...)
}

debugSource in 'RStudio' wrapper <- function(fileName, ...) {
  fileName <- inside.source(fileName, character.only = TRUE,
    conv2utf8 = TRUE, allow.blank.string = TRUE)
  debugSource(fileName = fileName, ...)
}

testthat::source_file wrapper <- function(path, ...) {
  # before testthat_3.1.2, source_file() used base::readLines() to
  # read the input lines. changed in 3.1.2, source_file() uses
  # brio::read_lines() which normalizes 'path' before reading,
  # disregarding the special meaning of the strings listed above
  path <- inside.source(path, path.only = TRUE,
    ignore.all = as.numeric_version(getNamespaceVersion("testthat")) >= "3.1.2")
  testthat::source_file(path = path, ...)
}

```

```
knitr::knit wrapper <- function(input, ...) {
  # this works for the most part, but will not work in child mode
  input <- inside.source(input)
  knitr::knit(input = input, ...)
}
```

## Examples

```
FILE <- tempfile(fileext = ".R")
this.path::write.code({
  this.path::this.path(verbose = TRUE)
}, FILE)
```

```
# here we have a source-like function, suppose this
# function is in a package for which you have write permission
sourcelike <- function (file, envir = parent.frame())
{
  file <- inside.source(file)
  envir <- as.environment(envir)
  exprs <- parse(n = -1, file = file, srcfile = NULL, keep.source = FALSE)
  # this prints nicely
  source(local = envir, echo = TRUE, exprs = exprs,
         spaced = TRUE, verbose = FALSE, max.deparse.length = Inf)
  # you could alternatively do:
  # 'for (i in seq_along(exprs)) eval(exprs[i], envir)'
  # which does no pretty printing
}
```

```
sourcelike(FILE)
sourcelike(con <- file(FILE)); close(con)
```

```
# here we have another source-like function, suppose this function
# is in a foreign package for which you do not have write permission
sourcelike2 <- function (pathname, envir = globalenv())
{
  if (!(is.character(pathname) && file.exists(pathname)))
    stop(gettextf("%s' is not an existing file",
                 pathname, domain = "R-base"))
  envir <- as.environment(envir)
  exprs <- parse(n = -1, file = pathname, srcfile = NULL, keep.source = FALSE)
  source(local = envir, echo = TRUE, exprs = exprs,
         spaced = TRUE, verbose = FALSE, max.deparse.length = Inf)
}
```

```
# the above function is similar to sys.source(), and it
# expects a character string referring to an existing file
#
# with the following, you should be able to use 'this.path()' within 'FILE':
wrap.source(sourcelike2(FILE), path.only = TRUE)
```

```
# with R >= 4.1.0, use the forward pipe operator '|>' to
# make calls to 'wrap.source' more intuitive:
```

```
# sourcelike2(FILE) |> wrap.source(path.only = TRUE)

# 'wrap.source' can recognize arguments by name, so they
# do not need to appear in the same order as the formals
wrap.source(sourcelike2(envir = new.env(), pathname = FILE), path.only = TRUE)

# it is much easier to define a new function to do this
sourcelike3 <- function (...)
  wrap.source(sourcelike2(...), path.only = TRUE)

# the same as before
sourcelike3(FILE)

# however, this is preferable:
sourcelike4 <- function (pathname, ...)
{
  # pathname is now normalized
  pathname <- inside.source(pathname, path.only = TRUE)
  sourcelike2(pathname = pathname, ...)
}
sourcelike4(FILE)
```

# Index

- \* **package**
  - this.path-package, 2
- Args, 3
- as.character, 4
- as.character.factor, 3
- as.raw, 4
- as.rel.path, 2
- as.rel.path (as.relative.path), 5
- as.relative.path, 2, 5
- as.vector, 4
- asArgs, 2
- asArgs (Args), 3
  
- basename, 2
- basename2, 2, 6
  
- character, 3
- check.dir, 2
- check.dir (check.path), 8
- check.path, 2, 8
- commandArgs, 3
- connection, 27
  
- Date, 3
- dirname, 2
- dirname2, 2
- dirname2 (basename2), 6
  
- ext, 2, 9
- ext<- (ext), 9
  
- file.path, 2, 14
- file.remove, 20
- fileArgs, 2
- fileArgs (Args), 3
- formals, 27
- from.shell, 2, 10
  
- getinitwd, 11
- getOption, 12
  
- here, 2, 11, 17, 19, 22, 24
  
- ici (here), 11
  
- initwd (getinitwd), 11
- inside.source, 19, 22
- inside.source (wrap.source), 25
- is.main, 2
- is.main (from.shell), 10
  
- knitr::knit, 2, 3, 13, 19, 22, 25, 27–29
  
- LINENO, 12
- logical, 3
  
- NA\_character\_, 19
- normalize, 20
- normalized, 2, 6, 19
- normalized.shFILE (this.path-defunct), 23
- numeric, 3
  
- OS.type, 13
  
- path.expand, 6
- path.join, 2, 8, 11, 14, 24
- POSIXt, 3
- progArgs, 2
- progArgs (Args), 3
  
- R.from.shell, 3, 15, 22
- relpath (as.relative.path), 5
- removeext, 2
- removeext (ext), 9
- Rscript, 2, 3, 12
  
- set.this.path (wrap.source), 25
- setwd, 20
- shFILE, 2, 17, 21, 22
- source, 2, 3, 12, 19, 22, 25, 27, 28
- splitext, 2
- splitext (ext), 9
- sprintf, 4
- srcfile, 12
- srcref, 12
- Startup, 21
- stderr, 15
- stdin, 27
- stdout, 15

`Sys.dir (this.path)`, 19  
`Sys.getenv`, 18  
`Sys.path (this.path)`, 19  
`Sys.putenv`, 18  
`Sys.setenv`, 18  
`sys.source`, 2, 3, 12, 19, 22, 25, 27, 28

`testthat::source_file`, 2, 3, 13, 19, 22, 25, 27, 28  
`this.dir`, 2, 11, 23, 24  
`this.dir (this.path)`, 19  
`this.dir2 (this.path-defunct)`, 23  
`this.dir3 (this.path-defunct)`, 23  
`this.path`, 2, 17, 19, 23, 25  
`this.path-defunct`, 23  
`this.path-package`, 2  
`this.path2 (this.path-defunct)`, 23  
`this.proj`, 24  
`tryCatch`, 24  
`tryCatch2`, 2, 17, 19, 24

`unlink`, 20  
`utils::bug.report`, 2  
`utils::install.packages`, 15

`withArgs`, 2  
`withArgs (Args)`, 3  
`wrap.source`, 22, 25