

Package ‘PGM2’

October 12, 2022

Type Package

Title Nested Resolvable Designs and their Associated Uniform Designs

Version 1.0-1

Date 2016-12-17

Imports stats

Author Mohamed Laib, Abla Boudraa and Zebida Gheribi-Aoulmi

Maintainer Mohamed Laib <laib.med@gmail.com>

URL <<https://sites.google.com/site/mohamedlaibwebpage/>>

Description Construction method of nested resolvable designs from a projective geometry defined on Galois field of order 2. The obtained Resolvable designs are used to build uniform design. The presented results are based on <<https://eudml.org/doc/219563>> and A. Boudraa et al. (See references).

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2016-12-17 22:23:52

R topics documented:

PGM2-package	2
BIB	3
Gen	4
Resolvable	5
Steps	6
Uniform	7
Index	9

Description

Construction method of nested resolvable designs from a projective geometry defined on Galois field of order 2. The obtained Resolvable designs are used to build uniform design. The presented results are based on <<https://eudml.org/doc/219563>> and A. Boudraa et al. (See references).

Note

This work established in same time with the article intituled: Abla Boudraa et al., Recursive method for construction of nested resolvable designs and uniform designs associated, International Journal of Research and Reviews in Applied Sciences, (17), Issue 2 (2013).

Author(s)

Mohamed Laib, Abla Boudraa and Zebida Gheribi-Aoulmi

Maintainer: Mohamed Laib <laib.med@gmail.com>

References

D. Dugué *Traité de statistique théorique et appliquée*, Masson et Cie, 1958.

Gheribi-Aoulmi. Z and M. Bousseboua Recursive methods for construction of balanced n-ary block designs. *Serdica Math.J* (31), 2005,189-200

Fang.K.T et al., Constructions of uniform designs by using resolvable packings and coverings. *Discrete Math.* (19), 2003, 692-711.

Abla Boudraa, Zebida Gheribi-Aoulmi and Mohamed Laib. Recursive method for construction of nested resolvable designs and uniform designs associated. *International Journal of Research and Reviews in Applied Sciences*. Vol. 17, Issue 2 (2013).

Fang.K.T et al., Construction of uniform designs via super-simple resolvable t-designs. *Util. Math.* (66).2004, 15-32.

Examples

```
m<-4
X<-BIB(m)
n<-1
mat<-X$BIB
Y<-Resolvable(n,mat) #Extract the RBIB
n<-1
mat<-X$BIB
X2<-Gen(n,mat) #Extract the BIBD of the second generation
## Not run:
#Algorithm of the 3rd example in the paper : (Abla Boudraa & al) IJRRAS.
#(17), Issue 2 (2013).
```

```

bib<-BIB(3)$BIB
mat<-NULL
for(i in 1:15){mat[[i]]<-Gen(i,bib)$BIB2}
x<-Reduce("rbind",mat)
e<-dim(x)[1]
b<-dim(x)[2]
v<-bib[1,]
for (i in 1:e) {for (j in 1:b) {if (any (x[i,j]==v)) {x[i,j]<-0}}}
for (i in e:1) { if (all (x[i,]==0)) {x<-x[-i,]}}
s<-x[1,]
s<-s[s>0]
h<-length(s)
f<-dim(x)[1]
x1<-matrix(nrow=f, ncol=h)
for (i in 1:f) {x1[i,]<-x[i,][x[i,]>0]}
A<-unique(x1)
UD<-Uniform(A)

## End(Not run)

```

BIB

Balanced Incomplete binary Blocks Designs

Description

Gives the configuration of a Balanced Incomplete binary Blocks Designs (BIBD) using a projective geometry on a Galois Field of order 2 GF(2).

Usage

BIB(m)

Arguments

m Dimension of the projective geometry defined on GF(2)

Value

A LIST of:

1. V Number of treatments in the BIBD.
2. B Number of blocks of the BIBD.
3. R Repetition of each treatment.
4. K Size of each block.
5. BIB The configuration of the BIBD.

Author(s)

Mohamed Laib, Abla Boudraa and Zebida Gheribi-Aoulmi

References

D. Dugué *Traité de statistique théorique et appliquée*, Masson et Cie, 1958.

Examples

```
m<-4
X<-BIB(m) #BIB from PG(4,2)
```

Gen

Balanced Incomplete binary Blocks Designs of second Generation.

Description

Gives the configuration of a Balanced Incomplete binary Blocks Designs of seconde generation.

Usage

Gen(n, mat)

Arguments

n	The sub-variety of the block to be deleted.
mat	The matrix of the BIB.

Value

A LIST of:

1. V Number of treatments in the BIBD.
2. B Number of blocks of the BIBD.
3. R Repetition of each treatment.
4. K Size of each block.
5. BIB The configuration of the BIBD.

Author(s)

Mohamed Laib, Abla Boudraa and Zebida Gheribi-Aoulmi

References

D. Dugué *Traité de statistique théorique et appliquée*, Masson et Cie, 1958.

Examples

```
## Not run:
m<-4
X<-BIB(m) #BIB from PG(4,2)

n<-1
mat<-X$BIB
X2<-Gen(n,mat) #Extracts the BIB second generation

## End(Not run)
```

Resolvable

Resolvable Balanced Incomplete Block Design RBIBD

Description

Extracts the Resolvable Balanced Incomplete Block Design (RBIBD) of any BIBD constructed from a projective geometry.

Usage

```
Resolvable(n, mat)
```

Arguments

n	The sub-variety of the block to be deleted.
mat	The matrix of the BIB.

Value

A LIST of:

1. V Number of treatments in the RBIBD.
2. B Number of blocks of the RBIBD.
3. R Repetition of each treatment.
4. K Size of each block.
5. BIB The configuration of the RBIBD.

Author(s)

Mohamed Laib, Abia Boudraa and Zebida Gheribi-Aoulmi

References

D. Dugué *Traité de statistique théorique et appliquée*, Masson et Cie, 1958.

Examples

```
## Not run:
m<-4
X<-BIB(m) #BIBD from PG(4,2)

n<-1
mat<-X$BIB
Y<-Resolvable(n,mat) #Extracts the RBIBD

## End(Not run)
```

Steps	<i>Nested Resolvable Designs and associated Uniform Designs in different stages.</i>
-------	--

Description

Gives the different stages of nested design beginning from a projective geometry, BIBD, BIBD seconde generation, RBIBD and associated uniform designs.

Usage

```
Steps(m, n, stage = "all")
```

Arguments

m	Dimension of the projective geometry defined on GF(2).
n	The sub-variety of the block to be deleted.
stage	Stage of recurrence wanted (single value or vector) : 'all' Print all designs. 'S1' Print the configurations of BIB of first generation. 'S2' Print the configurations of BIB of seconde generation. 'S3' Print the configurations of RBIB. 'S4' Print the configurations of the uniform designs associate to each nested resolvable.

Value

A LIST, with the parametrs and the configurations on each stages of recurrence.

Author(s)

Mohamed Laib, Abia Boudraa and Zebida Gheribi-Aoulmi

References

Gheribi-Aoulmi. Z and M. Bousseboua Recursive methods for construction of balanced n-ary block designs. *Serdica Math.J* (31), 2005,189-200

Examples

```
## Not run:
list1<-Steps(4,1) #Get all stages : of the PG(4,2)

list2<-Steps(4,1,c('S1','S2')) #Get the 2 first stages : of the PG(4,2)

list3<-Steps(4,1,c('S1','S4')) #Get the first & the last stage : of the PG(4,2)

list4<-Steps(4,1,'S4') #Get the last stage : of the PG(4,2)

## End(Not run)
```

Uniform

Uniform designs

Description

Builds the uniform design (UD) using a Resolvable Balanced Incomplete Block Design (RBIBD)

Usage

Uniform(mat)

Arguments

mat The matrix of the RBIBD.

Value

A LIST of:

1. n Number of experiments.
2. F The dimension of the design.
3. UD The configuration of the uniform design.

Author(s)

Mohamed Laib, Abia Boudraa and Zebida Gheribi-Aoulmi

References

- Fang.K.T et al., Constructions of uniform designs by using resolvable packings and coverings. Discrete Math. (19), 2003, 692-711.
- Fang.K.T et al., Construction of uniform designs via super-simple resolvable t-designs. Util. Math. (66).2004, 15-32.

Examples

```
## Not run:  
  
m<-4  
X<-BIB(m)  
  
n<-1  
mat<-X$BIB  
Y<-Resolvable(n,mat)  
  
ud<-Uniform(Y$RBIB) #Uniform design  
  
## End(Not run)
```


Index

BIB, [3](#)

Gen, [4](#)

PGM2 (PGM2-package), [2](#)

PGM2-package, [2](#)

Resolvable, [5](#)

Steps, [6](#)

Uniform, [7](#)