

Package ‘f1dataR’

January 25, 2024

Title Access Formula 1 Data

Version 1.5.0

Description Obtain Formula 1 data via the 'Ergast API' <<https://ergast.com/mrd/>> and the unofficial API <<https://www.formula1.com/en/f1-live.html>> via the 'fastf1' Python library <<https://docs.fastf1.dev/>>.

Config/reticulate list(packages = list(list(package = ``fastf1", pip = TRUE)))

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Depends R (>= 2.10), reticulate (>= 1.14),

Imports glue, magrittr, tibble, jsonlite, httr2, memoise, janitor, dplyr, tidyr, rlang, lifecycle, cli, rappdirs, cachem, withr

Suggests ggplot2, httpptest, knitr, rmarkdown, testthat (>= 3.0.0), usethis

VignetteBuilder knitr

URL <https://scasanova.github.io/f1dataR/>,
<https://github.com/scasanova/f1dataR/>

BugReports <https://github.com/scasanova/f1dataR/issues>

Config/testthat/edition 3

NeedsCompilation no

Author Santiago Casanova [aut, cre, cph],
Philip Bulsink [aut] (<<https://orcid.org/0000-0001-9668-2429>>)

Maintainer Santiago Casanova <santiago.casanova@yahoo.com>

Repository CRAN

Date/Publication 2024-01-25 01:10:08 UTC

R topics documented:

change_cache	2
clear_f1_cache	3
constructor_data	4
correct_track_ratio	4
get_current_season	5
get_fastf1_version	5
load_circuits	6
load_circuit_details	6
load_constructors	7
load_drivers	7
load_driver_telemetry	8
load_laps	9
load_pitstops	10
load_quali	10
load_race_session	11
load_results	12
load_schedule	12
load_session_laps	13
load_sprint	14
load_standings	14
plot_fastest	15
setup_fastf1	16
theme_dark_f1	17
time_to_sec	17
Index	18

change_cache	<i>Change Caching Settings</i>
--------------	--------------------------------

Description

Change caching settings for the package. By default, the cache will be set to keep the results of function calls in memory to reduce the number of requests made to online services for the same data. However, if preferred, the cache can be set to a file directory to make the results persist between sessions.

This is a particularly good idea if you're using functions like `load_driver_telemetry()`, `load_session_laps()`, `load_race_session()` or `plot_fastest()` as they take significant time and download large amounts of data each time you run the function.

If preferred for testing or waiting for data updates on race weekends, you may wish to set the cache to 'off' instead.

Changes to cache can be made for the session (mark the argument `persist` as `FALSE`) or apply to the next session(s) by setting `persist` to `TRUE`

Usage

```
change_cache(cache = "memory", create_dir = FALSE, persist = FALSE)
```

Arguments

cache	One of 'memory', 'filesystem', 'off' or a directory. If the selection is 'filesystem' the package will automatically write the cache to the operating system's default location for permanent or temporary caches (see persist)
create_dir	Whether to create the directory if it doesn't already exist if a path cache directory is provided. By default this doesn't occur for provided cache paths, but will always happen if the cache choice is set to 'filesystem'.
persist	Whether to make this change permanent (TRUE) or a temporary cache change only (default, FALSE). Note if you set cache to 'off' and persist to TRUE the existing cache will be cleared by calling clear_cache(). If filesystem is chosen for cache and persist is set to TRUE, then a cache directory will be placed in the default location for the operating system. If instead persist is set to FALSE, then a temporary directory will be used instead, and this will be removed at the end of the session. This essentially has the same effect as having cache set to 'memory'.

Value

No return, called for side effects

Examples

```
## Not run:
change_cache("~/f1dataRcache", create_dir = TRUE)

change_cache("off", persist = FALSE)

## End(Not run)
```

clear_f1_cache	<i>Clear f1dataR Cache</i>
----------------	----------------------------

Description

Clears the cache for f1dataR telemetry and Ergast API results. Note that the cache directory can be set by setting `option(f1dataR.cache = [cache dir])`, but the default is a temporary directory. You can also call the alias `clear_cache()` for the same result

Usage

```
clear_f1_cache()

clear_cache()
```

Value

No return value, called to erase cached data

Examples

```
## Not run:
clear_f1_cache()

## End(Not run)
```

constructor_data	<i>Constructor Data</i>
------------------	-------------------------

Description

This contains the following columns: constructor_id, constructor_color, constructor_color2, constructor_logo

References

derived from fastf1 data

correct_track_ratio	<i>Correct Track Ratios</i>
---------------------	-----------------------------

Description

Correct Track Ratios helps ensure that ggplot objects are plotted with 1:1 unit ratio. Without this function, plots have different x & y ratios and the tracks come out misshapen. This is particularly evident at long tracks like Saudi Arabia or Canada.

Note that this leaves the plot object on a dark background, any plot borders will be maintained

Usage

```
correct_track_ratio(trackplot, x = "x", y = "y", background = "grey10")
```

Arguments

trackplot	A GGPlot object, ideally showing a track layout for ratio correction
x, y	Names of columns in the original data used for the plot's x and y values. Defaults to 'x' and 'y'
background	Background colour to use for filling out the plot edges. Defaults to "grey10" which is the default background colour if you use <code>theme_dark_f1()</code> to theme your plots.

Value

a ggplot object with `ggplot2::scale_x_continuous()` and `ggplot2::scale_y_continuous()` set to the same limits to produce an image with shared x and y limits and with `ggplot2::coord_fixed()` set.

Examples

```
## Not run:  
# Note that plot_fastest plots have already been ratio corrected  
fast_plot <- plot_fastest(season = 2022, round = 1, session = "Q", driver = V)  
correct_track_ratio(fast_plot)  
  
## End(Not run)
```

get_current_season *Get Current Season*

Description

Looks up current season from ergast, fallback to manual determination

Usage

```
get_current_season()
```

Value

Year (four digit number) representation of current season, as numeric.

get_fastf1_version *Get current FastF1 version*

Description

Gets the current installed FastF1 version available (via reticulate) to the function. Displays a note if significantly out of date.

Usage

```
get_fastf1_version()
```

Value

integer for major version number (or NA if any error)

load_circuits	<i>Load Circuit Info</i>
---------------	--------------------------

Description

Loads circuit info for all circuits in a given season. Use `.load_circuits()` for an uncached version of this function

Usage

```
load_circuits(season = get_current_season())
```

Arguments

season number from 1950 to current season (defaults to current season).

Value

A tibble with one row per circuit

load_circuit_details	<i>Load Circuit Information</i>
----------------------	---------------------------------

Description

Loads circuit details for a specific race session. Note that different track layouts are used at some circuits depending on the year of the race.

Useful for visualizing or annotating data. Contains information on corners, marshal_lights and marshal_sectors.

Each set of these track marker types is returned as a tibble.

Also returns an angle (in degrees) to indicate the amount of rotation of the telemetry to visually align the two.

More information on the data provided (and uses) can be seen at https://docs.fastf1.dev/circuit_info.html#fastf1.mvapi.Circuit

Note that this is an exposition of FastF1 data. As such, caching is recommended (and default behavior). Cache directory can be set by setting `option(f1dataR.cache = [cache dir])`, default is the current working directory.

If you have trouble with errors mentioning 'fastf1' or 'get_fastf1_version()' read the 'Setup FastF1 Connection' vignette (run `vignette('setup_fastf1', 'f1dataR')`).

Usage

```
load_circuit_details(
  season = get_current_season(),
  round = 1,
  log_level = "WARNING"
)
```

Arguments

season	number from 2018 to current season. Defaults to current season.
round	number from 1 to 23 (depending on season selected). Also accepts race name.
log_level	Detail of logging from fastf1 to be displayed. Choice of: 'DEBUG', 'INFO', 'WARNING', 'ERROR' and 'CRITICAL'. See fastf1 documentation .

Value

A list of tibbles containing corner number, marshall post number, or marshall segment, plus a numeric value for rotational offset of the data compared to telemetry data.

The tibbles all have the following structure: x and y specify the position on the track map number is the number of the corner. Letter is optionally used to differentiate corners with the same number on some circuits, e.g. "2A". angle is an angle in degrees, used to visually offset the marker's placement on a track map in a logical direction (usually orthogonal to the track). distance is the location of the marker as a distance from the start/finish line.

load_constructors	<i>Load Constructor Info</i>
-------------------	------------------------------

Description

Loads constructor info for all participants in a given season. Use `.load_constructors()` for an uncached version of this function

Usage

```
load_constructors()
```

Value

A tibble with one row per constructor

load_drivers	<i>Load Driver Info</i>
--------------	-------------------------

Description

Loads driver info for all participants in a given season. Use `.load_drivers()` for an uncached version of this function.

Usage

```
load_drivers(season = get_current_season())
```

Arguments

season number from 1950 to current season (defaults to current season).

Value

A tibble with columns driver_id (unique and recurring), first name, last name, nationality, date of birth (yyyy-mm-dd format), driver code, and permanent number (for post-2014 drivers).

load_driver_telemetry *Load Telemetry Data for a Driver*

Description

Receives season, race number, driver code, and an optional fastest lap only argument to output car telemetry for the selected situation. Example usage of this code can be seen in the Introduction vignette (run vignette('introduction', 'f1dataR') to read). Multiple drivers' telemetry can be appended to one data frame by the user.

If you have trouble with errors mentioning 'fastf1' or 'get_fastf1_version()' read the "Setup FastF1 Connection" vignette (run vignette('setup_fastf1', 'f1dataR')).

Usage

```
load_driver_telemetry(
  season = get_current_season(),
  round = 1,
  session = "R",
  driver,
  laps = "fastest",
  log_level = "WARNING",
  race = lifecycle::deprecated(),
  fastest_only = lifecycle::deprecated()
)
```

Arguments

season number from 2018 to current season (defaults to current season).

round number from 1 to 23 (depending on season selected). Also accepts race name.

session the code for the session to load Options are 'FP1', 'FP2', 'FP3', 'Q', 'S', 'SS', and 'R'. Default is 'R', which refers to Race.

driver three letter driver code (see load_drivers() for a list)

laps which lap's telemetry to return. One of an integer lap number (<= total laps in the race), fastest, or all. Note that integer lap choice requires fastf1 version 3.0 or greater.

log_level Detail of logging from fastf1 to be displayed. Choice of: 'DEBUG', 'INFO', 'WARNING', 'ERROR' and 'CRITICAL'. See [fastf1 documentation](#).

race **[Deprecated]** race is no longer supported, use round.
fastest_only **[Deprecated]** fastest_only is no longer supported, indicated preferred laps in laps.

Value

A tibble with telemetry data for selected driver/session.

Examples

```

if (interactive()) {
  telem <- load_driver_telemetry(
    season = 2023,
    round = "Bahrain",
    session = "Q",
    driver = "HAM",
    laps = "fastest"
  )
}

```

load_laps	<i>Load Lap by Lap Time Data</i>
-----------	----------------------------------

Description

Loads basic lap-by-lap time data for all drivers in a given season and round. Lap time data is available from 1996 onward. Use `.load_laps()` for a uncached version.

Usage

```

load_laps(
  season = get_current_season(),
  round = "last",
  race = lifecycle::deprecated()
)

```

Arguments

season number from 1996 to current season (defaults to current season).
round number from 1 to 23 (depending on season selected) and defaults to most recent. Also accepts 'last'.
race **[Deprecated]** race is no longer supported, use round.

Value

A tibble with columns `driver_id` (unique and recurring), position during lap, time (in clock form), lap number, time (in seconds), and season.

load_pitstops	<i>Load Pitstop Data</i>
---------------	--------------------------

Description

Loads pit stop info (number, lap, time elapsed) for a given race in a season. Pit stop data is available from 2012 onward. Call `.load_pitstops()` for an uncached version.

Usage

```
load_pitstops(
  season = get_current_season(),
  round = "last",
  race = lifecycle::deprecated()
)
```

Arguments

season	number from 2011 to current season (defaults to current season).
round	number from 1 to 23 (depending on season selected) and defaults to most recent. Also accepts 'last'.
race	[Deprecated] race is no longer supported, please use round.

Value

A tibble with columns driver_id, lap, stop (number), time (of day), and stop duration

load_quali	<i>Load Qualifying Results</i>
------------	--------------------------------

Description

Loads qualifying session results for a given season and round. Use `.load_quali()` for an uncached version.

Usage

```
load_quali(season = get_current_season(), round = "last")
```

Arguments

season	number from 2003 to current season (defaults to current season).
round	number from 1 to 23 (depending on season), and defaults to most recent. Also accepts 'last'.

Value

A tibble with one row per driver

load_race_session	<i>Load Session Data</i>
-------------------	--------------------------

Description

Loads telemetry and general data from the official F1 data stream via the fastf1 python library. Data is available from 2018 onward.

The data loaded can optionally be assigned to a R variable, and then interrogated for session data streams. See the [fastf1 documentation](#) for more details on the data returned by the python API.

If you have trouble with errors mentioning 'fastf1' or 'get_fastf1_version()' read the 'Setup FastF1 Connection vignette (run `vignette('setup_fastf1', 'f1dataR')`).

Usage

```
load_race_session(
  obj_name = "session",
  season = get_current_season(),
  round = 1,
  session = "R",
  log_level = "WARNING",
  race = lifecycle::deprecated()
)
```

Arguments

obj_name	name assigned to the loaded session to be referenced later. Leave as 'session' unless otherwise required.
season	number from 2018 to current season. Defaults to current season.
round	number from 1 to 23 (depending on season selected) and defaults to most recent. Also accepts race name.
session	the code for the session to load Options are 'FP1', 'FP2', 'FP3', 'Q', 'S', 'SS' and 'R'. Default is 'R', which refers to Race. Cache directory can be set by setting <code>option(f1dataR.cache = [cache_dir])</code> , default is the current working directory.
log_level	Detail of logging from fastf1 to be displayed. Choice of: 'DEBUG', 'INFO', 'WARNING', 'ERROR' and 'CRITICAL.' See fastf1 documentation .
race	[Deprecated] race is no longer supported, use round

Value

A session object to be used in other functions invisibly.

See Also

[load_session_laps\(\)](#) [plot_fastest\(\)](#)

Examples

```
# Load the quali session from 2019 first round
if (interactive()) {
  session <- load_race_session(season = 2019, round = 1, session = "Q")
}
```

load_results	<i>Load Results</i>
--------------	---------------------

Description

Loads final race results for a given year and round. Use `.load_results()` for an uncached version

Usage

```
load_results(season = get_current_season(), round = "last")
```

Arguments

season	number from 1950 to current season (or the word 'current') (defaults to current season).
round	number from 1 to 23 (depending on season), and defaults to most recent. Also accepts 'last'.

Value

A tibble with one row per driver

load_schedule	<i>Load Schedule</i>
---------------	----------------------

Description

Loads schedule information for a given F1 season. Use `.load_schedule()` for an uncached version.

Usage

```
load_schedule(season = get_current_season())
```

Arguments

season number from 1950 to current season (defaults to current season). 'current' also accepted.

Value

A tibble with one row per round in season. Indicates in sprint_date if a specific round has a sprint race

load_session_laps *Load Lapwise Data*

Description

Loads lapwise data for a race session.

Includes each driver's each lap's laptime, pit in/out time, tyre information, track status, and (optionally) weather information. The resulting data frame contains a column for the session type. Note that quali sessions are labelled Q1, Q2 & Q3.

Cache directory can be set by setting `option(f1dataR.cache = [cache dir])`, default is the current working directory.

If you have trouble with errors mentioning 'fastf1' or 'get_fastf1_version()' read the 'Setup FastF1 Connection vignette (run `vignette('setup_fastf1', 'f1dataR')`).

Usage

```
load_session_laps(
  season = get_current_season(),
  round = 1,
  session = "R",
  log_level = "WARNING",
  add_weather = FALSE,
  race = lifecycle::deprecated()
)
```

Arguments

season number from 2018 to current season. Defaults to current season.

round number from 1 to 23 (depending on season selected). Also accepts race name.

session the code for the session to load Options are 'FP1', 'FP2', 'FP3', 'Q', 'S', 'SS' and 'R' Default is 'R', which refers to Race.

log_level Detail of logging from fastf1 to be displayed. Choice of: 'DEBUG', 'INFO', 'WARNING', 'ERROR' and 'CRITICAL'. See [fastf1 documentation](#).

add_weather Whether to add weather information to the laps. See [fastf1 documentation](#) for info on weather.

race **[Deprecated]** race is no longer supported, use round.

Value

A tibble. Note time information is in seconds, see [fastf1 documentation](#) for more information on timing.

load_sprint	<i>Load Sprint Results</i>
-------------	----------------------------

Description

Loads final race results for a given year and round. Note not all rounds have sprint results. Use `.load_sprint()` for an uncached version of this function.

Usage

```
load_sprint(season = get_current_season(), round = "last")
```

Arguments

season	number from 2021 to current season (defaults to current season).
round	number from 1 to 23 (depending on season), and defaults to most recent. Also accepts 'last'.

Value

A dataframetibble with columns driver_id, constructor_id, points awarded, finishing position, grid position, laps completed, race status (finished or otherwise), gap to first place, fastest lap, fastest lap time, fastest lap in seconds, or NULL if no sprint exists for this season/round combo

load_standings	<i>Load Standings</i>
----------------	-----------------------

Description

Loads standings at the end of a given season and round for drivers' or constructors' championships. Use `.load_standings()` for an uncached version of this function.

Usage

```
load_standings(season = get_current_season(), round = "last", type = "driver")
```

Arguments

season	number from 2003 to current season (defaults to current season).
round	number from 1 to 23 (depending on season), and defaults to most recent. Also accepts 'last'.
type	select 'driver' or 'constructor' championship data. Defaults to 'driver'

Value

A tibble with columns driver_id (or constructor_id), position, points, wins (and constructors_id in the case of drivers championship).

plot_fastest	<i>Plot Fastest Lap</i>
--------------	-------------------------

Description

Creates a ggplot graphic that details the fastest lap for a driver in a race. Complete with a gearshift or speed analysis.

Usage

```
plot_fastest(
  season = get_current_season(),
  round = 1,
  session = "R",
  driver,
  color = "gear",
  race = lifecycle::deprecated()
)
```

Arguments

season	number from 2018 to current season (defaults to current season).
round	number from 1 to 23 (depending on season selected) and defaults to most recent.
session	the code for the session to load Options are 'FP1', 'FP2', 'FP3', 'Q', 'S', 'SS', and 'R'. Default is 'R', which refers to Race.
driver	three letter driver code (see load_drivers() for a list).
color	argument that indicates which variable to plot along the circuit. Choice of 'gear' or 'speed', default 'gear'.
race	number from 1 to 23 (depending on season selected) and defaults to most recent.

Value

A ggplot object that indicates grand prix, driver, time and selected color variable.

Examples

```
# Plot Verstappen's fastest lap (speed) from Bahrain 2023:
if (interactive()) {
  plot_fastest(2023, 1, "R", "VER", "speed")
}
```

`setup_fastf1`*Setup fastf1 connection*

Description

Installs or optionally updates fastf1 Python package in the current active Python environment/virtualenv/conda env.

More information on how to manage complex environment needs can be read in the [reticulate docs](#), and tools for managing virtual environments are documented in [virtualenv-tools](#) and [conda-tools](#)

Usage

```
setup_fastf1(  
    ...,  
    envname = "f1dataR_env",  
    new_env = identical(envname, "f1dataR_env")  
)
```

Arguments

<code>...</code>	Additional parameters to pass to py_install
<code>envname</code>	Optionally pass an environment name used. Defaults to package default of <code>f1dataR_env</code> .
<code>new_env</code>	Whether or not to completely remove and recreate the environment provided in <code>envname</code> . This will fix any issues experienced by fastf1 related to package dependencies.

Value

No return value, called to install or update fastf1 Python package.

Examples

```
## Not run:  
# Install fastf1 into the currently active Python environment  
setup_fastf1()  
  
# Reinstall fastf1 and recreate the environment.  
setup_fastf1(envname = "f1dataR_env", new_env = TRUE)  
  
## End(Not run)
```

theme_dark_f1	<i>Dark F1-style Theme for ggplot</i>
---------------	---------------------------------------

Description

Theme for all f1dataR plot functions. Mimics Formula 1 style.

Usage

```
theme_dark_f1(axis_marks = FALSE)
```

Arguments

axis_marks	True or false, whether axis line, ticks and title should be shown or not. Defaults to false
------------	---

Value

A ggplot object that indicates grand prix, driver, time and selected color variable.

time_to_sec	<i>Convert Clock time to seconds</i>
-------------	--------------------------------------

Description

This function converts clock format time (0:00.000) to seconds (0.000s)

Usage

```
time_to_sec(time)
```

Arguments

time	character string with clock format (0:00.000)
------	---

Value

A numeric variable that represents that time in seconds

Index

* data

- constructor_data, 4
- change_cache, 2
- clear_cache (clear_f1_cache), 3
- clear_f1_cache, 3
- conda-tools, 16
- constructor_data, 4
- correct_track_ratio, 4
- get_current_season, 5
- get_fastf1_version, 5
- load_circuit_details, 6
- load_circuits, 6
- load_constructors, 7
- load_driver_telemetry, 8
- load_drivers, 7
- load_laps, 9
- load_pitstops, 10
- load_quali, 10
- load_race_session, 11
- load_results, 12
- load_schedule, 12
- load_session_laps, 13
- load_session_laps(), 12
- load_sprint, 14
- load_standings, 14
- plot_fastest, 15
- plot_fastest(), 12
- py_install, 16
- setup_fastf1, 16
- theme_dark_f1, 4, 17
- time_to_sec, 17
- virtualenv-tools, 16