

Package ‘RXMCDA’

October 12, 2022

Version 1.5.5

Date 2015-11-16

Title Functions to Parse and Create XMCDA Files

Author Patrick Meyer and Sebastien Bigaret, with contributions from Krzysztof Ciomek.

Maintainer Patrick Meyer <patrick.meyer@telecom-bretagne.eu>

Description Functions which allow to read many XMCDA tags and transform them into R variables which are then usable in MCDA algorithms written in R. It also allows to write certain R variables into XML files respecting the XMCDA standard.

Depends XML

Imports kappalab

Encoding latin1

License CeCILL-2

URL <https://github.com/paterijk/RXMCDA>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-12-11 16:50:02

R topics documented:

checkXSD	2
getAlternativesAffectations	3
getAlternativesComparisons	4
getAlternativesComparisonsLabels	6
getAlternativesComparisonsValues	7
getAlternativesIDs	8
getAlternativesIntervalValues	10
getAlternativesValues	11
getCategoriesIDs	12
getCategoriesIntervalValues	13
getCategoriesValues	14
getCriteriaComparisons	15

getCriteriaComparisonsLabels	16
getCriteriaIDs	17
getCriteriaIntervalValues	18
getCriteriaPairsComparisons	19
getCriteriaPairsIntervalValues	20
getCriteriaPairsValues	21
getCriteriaValues	22
getMobiusCapacities	23
getNumberOfAlternatives	24
getNumberOfCategories	25
getNumberOfCriteria	26
getNumericValue	27
getParameters	28
getPerformanceTables	29
putAlternativesAffectations	30
putAlternativesAffectationsWithValues	31
putAlternativesComparisonsLabels	32
putAlternativesIDs	33
putAlternativesPlot	34
putAlternativesValues	35
putAlternativeValue	36
putCapacity	37
putCategoriesIntervalValues	38
putCategoriesValues	39
putCriteriaMatrix	40
putCriteriaPairsValues	41
putCriteriaPlot	42
putCriteriaValues	42
putCriterionValue	43
putErrorMessage	44
putLogMessage	45
putMessage	45
putPerformanceTable	46
putPointsCriterionFunction	47

Index	49
--------------	-----------

checkXSD	<i>XMCDA tree validation.</i>
----------	-------------------------------

Description

Checks if an XML tree is valid according to an XML schema.

Usage

checkXSD(tree)

Arguments

tree Object containing the XMCDA XML tree.

Value

The function returns 1 if the XML tree is validated by the XMCDA schema (currently XMCDA-2.*), else it returns 0.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

criteria<-newXMLNode("criteria", parent=root[[1]], namespace=c())
criterion<-newXMLNode("criterion", attrs = c(id="g1"),
                       parent=criteria, namespace=c())

y<-checkXSD(tree)
```

getAlternativesAffectations

Get alternative affectations

Description

Gets alternative affectations, stored in the <alternativesAffectations> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getAlternativesAffectations(tree, alternativesIDs, categoriesIDs,
                           mcdaConcept = NULL)
```

Arguments

tree Object containing the XMCDA XML tree.

alternativesIDs

A vector containing the IDs of the alternatives to be considered for the extractions.

categoriesIDs A vector containing the IDs of the categories to be considered for the extractions.

mcdaConcept A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

- The first elements contain $n \times m$ matrices representing each an <alternativesAffectations>, where n is number of considered alternatives and m is number of considered categories. Each cell $[i, j]$ of each matrix is boolean and corresponds to encoded relation between i -th alternative and j -th category. Elements of returned list are named according to the mcdaConcept attribute if it can be found.
- status Either OK if all the <alternativesAffectations> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                                 useInternalNodes=TRUE)

alternativesIDs <- getAlternativesIDs(tree)
categoriesIDs <- getCategoriesIDs(tree)
altAff <- getAlternativesAffectations(tree,
                                       alternativesIDs[[1]], categoriesIDs[[1]])
```

getAlternativesComparisons

Get comparisons of alternatives

Description

Extracts <alternativesComparisons> from an XML tree written according to the XMCDA standard and stores the performances of the concerned alternatives.

Usage

```
getAlternativesComparisons(tree, performanceTable, mcdaConcept = NULL)
```

Arguments

- tree Object containing the XMCDA XML tree.
- performanceTable A matrix containing the performance table to be considered, whose dimnames are the alternatives' IDs (rows) and the criteria's IDs (columns).
- mcdaConcept A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

- The first elements contain the <alternativesComparisons> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "alternative a is preferred to alternative b with preference threshold delta". A line is structured as follows: the first n elements encode alternative a (via the values it takes in performanceTable), the next n elements encode alternative b, and the last element contains the preference threshold delta.
- status Either OK if all the <criteria> tags could be correctly read, or the description of the error.

Examples

```

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

aC<-newXMLNode("alternativesComparisons", parent=root[[1]] , namespace=c())

pairs<-newXMLNode("pairs", parent=aC, namespace=c())
pair<-newXMLNode("pair", parent=pairs, namespace=c())

initial<-newXMLNode("initial", parent=pair)
newXMLNode("alternativeID", "a01", parent=initial, namespace=c())

terminal<-newXMLNode("terminal", parent=pair, namespace=c())
newXMLNode("alternativeID", "a02", parent=terminal, namespace=c())

value<-newXMLNode("value", parent=pair, namespace=c())
newXMLNode("real", "0.5", parent=value, namespace=c())

alternativesIDs <- c("a01","a02")
criteriaIDs <- c("g1","g2")

performance.table<-matrix(nrow=length(alternativesIDs),
                           ncol=length(criteriaIDs),
                           dimnames = list(alternativesIDs,criteriaIDs))

for (i in 1:length(alternativesIDs)){
  for (j in 1:length(criteriaIDs)){
    performance.table[i,j] = runif(1)
  }
}

```

```
y<-getNodeSet(tree,"//alternativesComparisons")
x<-getAlternativesComparisons(y[[1]], performance.table)
```

getAlternativesComparisonsLabels
Get comparisons of alternatives

Description

Extracts <alternativesComparisons> from an XML tree written according to the XMCDA standard and stores the IDs of the concerned alternatives.

Usage

```
getAlternativesComparisonsLabels(tree, altIDs=NULL, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
altIDs	A vector containing the IDs of the alternatives to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <alternativesComparisons> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "alternative a is preferred to alternative b with preference threshold delta". A line is structured as follows: the first element encodes the ID of alternative a, the second element encodes the ID of alternative b, and the last element contains the preference threshold delta.
status	Either OK if all the <alternativesComparisons> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()
newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                       "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)
```

```

root<-getNodeSet(tree, "/xmcda:XMCDA")

aC<-newXMLNode("alternativesComparisons", parent=root[[1]], namespace=c())

pairs<-newXMLNode("pairs", parent=aC, namespace=c())
pair<-newXMLNode("pair", parent=pairs, namespace=c())

initial<-newXMLNode("initial", parent=pair, namespace=c())
newXMLNode("alternativeID", "a01", parent=initial, namespace=c())

terminal<-newXMLNode("terminal", parent=pair, namespace=c())
newXMLNode("alternativeID", "a02", parent=terminal, namespace=c())

value<-newXMLNode("value", parent=pair, namespace=c())
newXMLNode("real", "0.5", parent=value, namespace=c())

alternativesIDs <- c("a01", "a02")

y<-getNodeSet(tree, "//alternativesComparisons")

x<-getAlternativesComparisonsLabels(y[[1]], alternativesIDs)

```

getAlternativesComparisonsValues*Get alternatives comparisons values***Description**

Gets alternatives comparisons values stored in the `<alternativesComparisons>` tag, from an XML tree written according to the XMCDA standard.

Usage

```
getAlternativesComparisonsValues(tree, alternativesIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>alternativesIDs</code>	A vector containing the IDs of the alternatives to be considered for the extractions.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain matrices representing each an <alternativesComparisons>. Each row c(i, j, v) of each matrix corresponds to a comparison between i-th (<initial>) and j-th (<terminal>) alternatives with value v. Elements of returned list are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <alternativesComparisons> tags could be correctly read, or the description of the error.

Examples

```

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

root <- getNodeSet(tree, "/xmcda:XMCDA")
altComp <- newXMLNode("alternativesComparisons", parent=root[[1]], namespace=c())
pairs <- newXMLNode("pairs", parent=altComp, namespace=c())

pair <- newXMLNode("pair", parent=pairs, namespace=c())
initial <- newXMLNode("initial", parent=pair)
newXMLNode("alternativeID", "a01", parent=initial, namespace=c())
terminal <- newXMLNode("terminal", parent=pair, namespace=c())
newXMLNode("alternativeID", "a02", parent=terminal, namespace=c())
value <- newXMLNode("value", parent=pair, namespace=c())
newXMLNode("real", "1", parent=value, namespace=c())

pair <- newXMLNode("pair", parent=pairs, namespace=c())
initial <- newXMLNode("initial", parent=pair)
newXMLNode("alternativeID", "a01", parent=initial, namespace=c())
terminal <- newXMLNode("terminal", parent=pair, namespace=c())
newXMLNode("alternativeID", "a03", parent=terminal, namespace=c())
value <- newXMLNode("value", parent=pair, namespace=c())
newXMLNode("real", "9", parent=value, namespace=c())

alternativesIDs <- c("a01", "a02", "a03")

x <- getAlternativesComparisonsValues(tree, alternativesIDs)

```

Description

Gets the IDs of alternatives, stored in the <alternatives> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getAlternativesIDs(tree, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>mcdaConcept</code>	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain vectors with the alternatives' IDs which have been found in each <alternatives> tag. These elements are named according to the mcdaConcept attribute if it can be found.
<code>status</code>	Either OK if all the <alternatives> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

alternatives<-newXMLNode("alternatives", attrs=c(mcdaConcept="actions"),
                         parent=root[[1]],
                         namespace=c())

alternative<-newXMLNode("alternative", attrs = c(id="x1"),
                         parent=alternatives, namespace=c())
alternative<-newXMLNode("alternative", attrs = c(id="x2"),
                         parent=alternatives, namespace=c())
alternative<-newXMLNode("alternative", attrs = c(id="x3"),
                         parent=alternatives, namespace=c())

y<-getNodeSet(tree,"//alternatives")

x<-getAlternativesIDs(y[[1]])
```

getAlternativesIntervalValues
Get interval values related to alternatives

Description

Gets intervals of values related to alternatives, stored in the <alternativesValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getAlternativesIntervalValues(tree, alternativesIDs, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
alternativesIDs	A vector containing the IDs of the alternatives to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain matrices representing each an <alternativesValues>. Each line of each matrix corresponds to an element of the type "the interval of values assigned to alternative a is [x,y]". A line is structured as follows: the first element encodes the index of the ID of alternative a in alternativesIDs, the second element encodes the value x, and the last element encodes the value y. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <alternativesValues> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                                 useInternalNodes=TRUE)

altIDs <- getAlternativesIDs(tree)

altVals <- getAlternativesIntervalValues(tree, altIDs[[1]],
                                         mcdaConcept="alternativesIntervalValues")
```

getAlternativesValues *Get values related to alternatives*

Description

Gets values related to alternatives, stored in the <alternativesValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getAlternativesValues(tree, alternativesIDs, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
alternativesIDs	A vector containing the IDs of the alternatives to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain matrices representing each an <alternativesValues>. Each line of each matrix corresponds to an element of the type "the value assigned to alternative a is x". A line is structured as follows: the first element encodes the index of the ID of alternative a in alternativesIDs, the second element encodes the value x. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <alternativesValues> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                  "testFile.xml",
                                  package="RXMLCDA"),
                      useInternalNodes=TRUE)

altIDs <- getAlternativesIDs(tree)

altVals <- getAlternativesValues(tree, altIDs[[1]])
```

<code>getCategoriesIDs</code>	<i>Get IDs of categories</i>
-------------------------------	------------------------------

Description

Gets the IDs of categories, stored in the <categories> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCategoriesIDs(tree, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>mcdaConcept</code>	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

<code>--</code>	The first elements contain vectors with the categories' IDs which have been found in each <categories> tag. These elements are named according to the mcdaConcept attribute if it can be found.
<code>status</code>	Either OK if all the <categories> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCD")

categories<-newXMLNode("categories", attrs=c(mcdaConcept="classes"),
                        parent=root[[1]],
                        namespace=c())

newXMLNode("category", attrs = c(id="c1"), parent=categories, namespace=c())
newXMLNode("category", attrs = c(id="c2"), parent=categories, namespace=c())
newXMLNode("category", attrs = c(id="c3"), parent=categories, namespace=c())

y<-getNodeSet(tree,"//categories")

x<-getCategoriesIDs(y[[1]])
```

getCategoriesIntervalValues*Get interval values related to categories*

Description

Gets interval values related to categories, stored in the <categoriesValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCategoriesIntervalValues(tree, categoriesIDs, mcdaConcept = NULL)
```

Arguments

- tree Object containing the XMCDA XML tree.
- categoriesIDs A vector containing the IDs of the categories to be considered for the extractions.
- mcdaConcept A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

- The first elements contain matrices representing each an <categoriesValues>. Each line of each matrix corresponds to an element of the type "the interval value assigned to category c1 is [x, y]". A line is structured as follows: the first element encodes the index of the ID of category c1 in categoriesIDs, the second element encodes the value x and the third element encodes the value y. These elements are named according to the mcdaConcept attribute if it can be found.
- status Either OK if all the <categoriesValues> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                "testFile.xml",
                                package="RXMLCDA"),
                                useInternalNodes=TRUE)

categoriesIDs <- getCategoriesIDs(tree)
intervalValues <- getCategoriesIntervalValues(tree, categoriesIDs[[1]])
```

getCategoriesValues *Get values related to categories*

Description

Gets values related to categories, stored in the <categoriesValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCategoriesValues(tree, categoriesIDs, mcdaConcept = NULL)
```

Arguments

- | | |
|---------------|--|
| tree | Object containing the XMCDA XML tree. |
| categoriesIDs | A vector containing the IDs of the categories to be considered for the extractions. |
| mcdaConcept | A string containing the specific mcdaConcept attribute which should be searched for. |

Value

The function returns a list structured as follows:

- | | |
|--------|---|
| -- | The first elements contain matrices representing each an <categoriesValues>. Each line of each matrix corresponds to an element of the type "the value assigned to category c1 is x". A line is structured as follows: the first element encodes the index of the ID of category c1 in categoriesIDs, the second element encodes the value x. These elements are named according to the mcdaConcept attribute if it can be found. |
| status | Either OK if all the <categoriesValues> tags could be correctly read, or the description of the error. |

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                "testFile.xml",
                                package="RXMLCDA"),
                                useInternalNodes=TRUE)

categoriesIDs <- getCategoriesIDs(tree)
categoriesValues <- getCategoriesValues(tree, categoriesIDs[[1]])
```

```
getCriteriaComparisons
    Get comparisons of criteria
```

Description

Gets comparisons of criteria, stored in the <criteriaComparisons> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaComparisons(tree, critIDs, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
critIDs	A vector containing the IDs of the criteria to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <criteriaComparisons> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "criterion g1 is preferred to criterion g2 with preference threshold delta". A line is structured as follows: the first element encodes the index of criterion g1 in critIDs, the next element encodes the ID of criterion g2, and the last element contains the preference threshold delta.
status	Either OK if all the <criteriaComparisons> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                "testFile.xml",
                                package="RXMLCDA"),
                                useInternalNodes=TRUE)

critIDs <- getCriteriaIDs(tree)

comps <- getCriteriaComparisons(tree, critIDs[[1]])
```

getCriteriaComparisonsLabels
Get comparisons of alternatives

Description

Extracts <criteriaComparisons> from an XML tree written according to the XMCDA standard and stores the IDs of the concerned criteria.

Usage

```
getCriteriaComparisonsLabels(tree, critIDs=NULL, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
critIDs	A vector containing the IDs of the criteria to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <alternativesComparisons> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "criterion g1 is preferred to criterion g2 with preference threshold delta". A line is structured as follows: the first element encodes the ID of criterion g1, the second element encodes the ID of criterion g2, and the last element contains the preference threshold delta.
status	Either OK if all the <criteriaComparisons> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                     useInternalNodes=TRUE)

critIDs <- getCriteriaIDs(tree)

comps <- getCriteriaComparisonsLabels(tree, critIDs[[1]])
```

getCriteriaIDs	<i>Get IDs of criteria</i>
----------------	----------------------------

Description

Gets the IDs of criteria, stored in the <criteria> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaIDs(tree, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain vectors with the criteria's IDs which have been found in each <criteria> tag. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <criteria> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

criteria<-newXMLNode("criteria", parent=root[[1]], namespace=c())

newXMLNode("criterion", attrs = c(id="g1"), parent=criteria, namespace=c())
newXMLNode("criterion", attrs = c(id="g2"), parent=criteria, namespace=c())

y<-getNodeSet(tree, "//criteria")

x<-getCriteriaIDs(y[[1]])
```

getCriteriaIntervalValues*Get interval values related to criteria***Description**

Extracts the number of criteria from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaIntervalValues(tree, criteriaIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaIDs</code>	A vector containing the IDs of the criteria to be considered for the extractions.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

<code>--</code>	The first elements contain the number of criteria of each <code><criteria></code> found in <code><tree></code> . These elements are named according to the <code>mcdaConcept</code> attribute if it can be found.
<code>status</code>	Either OK if all the <code><criteria></code> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                                 useInternalNodes=TRUE)

critIDs <- getCriteriaIDs(tree)

intVals <- getCriteriaIntervalValues(tree, critIDs[[1]])
```

getCriteriaPairsComparisons*Get comparisons of pairs of criteria*

Description

Gets comparisons of pairs of criteria, stored in the <criteriaComparisons> tag (pairs are represented as sets of two elements), from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaPairsComparisons(tree, criteriaIDs, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
criteriaIDs	A vector containing the IDs of the criteria to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <criteriaComparisons> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "criterion g1 is preferred to criterion g2 with preference threshold delta". A line is structured as follows: the first element encodes the index of criterion g1 in criteriaIDs, the next element encodes the ID of criterion g2, and the last element contains the preference threshold delta.
status	Either OK if all the <criteriaComparisons> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                     useInternalNodes=TRUE)

critIDs <- getCriteriaIDs(tree)

comps <- getCriteriaPairsComparisons(tree, critIDs[[1]])
```

`getCriteriaPairsIntervalValues`

Get interval values related to pairs of criteria

Description

Gets interval values related to pairs of criteria, stored in the `<criteriaValues>` tag (pairs are represented as sets of two elements), from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaPairsIntervalValues(tree, criteriaIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaIDs</code>	A vector containing the IDs of the criteria to be considered for the extractions.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <criteriaValues> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one constraint of the type "the interval of values assigned to the couple of criteria (g1,g2) is [x,y]". A line is structured as follows: the first element encodes the index of criterion g1 in criteriaIDs, the next element encodes the ID of criterion g2, and the last two elements contain x and y.
status	Either OK if all the <criteriaValues> tags could be correctly read, or the description of the error.

Examples

getCriteriaPairsValues

Get values related to pairs of criteria

Description

Gets values related to pairs of criteria, stored in the <criteriaValues> tag (pairs are represented as sets of two elements), from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaPairsValues(tree, criteriaIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaIDs</code>	A vector containing the IDs of the criteria to be considered for the extractions.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <criteriaValues> found in <tree> as matrices. These elements are named according to the mcdaConcept attribute if it can be found. Each line of each matrix corresponds to one statement of the type "the value assigned to the couple of criteria (g1,g2) is x". A line is structured as follows: the first element encodes the index of criterion g1 in criteriaIDs, the next element encodes the ID of criterion g2, and the last elements contain x.
status	Either OK if all the <criteriaValues> tags could be correctly read, or the description of the error.

Examples

<code>getCriteriaValues</code>	<i>Get values related to criteria</i>
--------------------------------	---------------------------------------

Description

Gets values related to criteria, stored in the <criteriaValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getCriteriaValues(tree, criteriaIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaIDs</code>	A vector containing the IDs of the criteria to be considered for the extractions.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain matrices representing each an <criteriaValues>. Each line of each matrix corresponds to an element of the type "the value assigned to criterion g1 is x". A line is structured as follows: the first element encodes the index of the ID of criterion g1 in <code>criteriaIDs</code> , the second element encodes the value x. These elements are named according to the <code>mcdaConcept</code> attribute if it can be found.
<code>status</code>	Either OK if all the <criteriaValues> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata",
                                 "testFile.xml",
                                 package="RXMLCDA"),
                                 useInternalNodes=TRUE)

critIDs <- getCriteriaIDs(tree)

critVals <- getCriteriaValues(tree, critIDs[[1]])
```

`getMobiusCapacities` *Get Möbius capacities*

Description

Gets Mobius capacities, stored in the <criteriaValues> tag, from an XML tree written according to the XMCDA standard.

Usage

```
getMobiusCapacities(tree, criteriaIDs, number_of_criteria,  
                     kadditivity, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaIDs</code>	A vector containing the IDs of the criteria to be considered for the extractions.
<code>numberOfCriteria</code>	The total number of criteria to be considered.
<code>kadditivity</code>	The level of k-additivity to be considered.
<code>mcdConcept</code>	A string containing the specific <code>mcdConcept</code> attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the <criteriaValues> found in <tree> as capacities (see kappa1ab package for details). These elements are named according to the mcdConcept attribute if it can be found.
status	Either OK if all the <criteriaValues> tags could be correctly read, or the description of the error.

Examples

getNumberOfAlternatives
Get number of alternatives

Description

Extracts the number of alternatives from the <alternatives> tag from an XML tree written according to the XMCDA standard.

Usage

```
getNumberOfAlternatives(tree, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the number of alternatives of each <alternatives> tag found in <tree>. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <alternatives> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

alternatives<-newXMLNode("alternatives", parent=root[[1]], namespace=c())
newXMLNode("alternative", attrs = c(id="x1"), parent=alternatives, namespace=c())
newXMLNode("alternative", attrs = c(id="x2"), parent=alternatives, namespace=c())

y<-getNodeSet(tree,"//alternatives")
x<-getNumberOfAlternatives(y[[1]])
```

getNumberOfCategories *Get number of categories*

Description

Extracts the number of categories from the <categories> tag from an XML tree written according to the XMCDA standard.

Usage

```
getNumberOfCategories(tree, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the number of categories of each <categories> tag found in <tree>. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <categories> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

categories<-newXMLNode("categories", parent=root[[1]], namespace=c())

newXMLNode("category", attrs = c(id="c1"), parent=categories, namespace=c())
newXMLNode("category", attrs = c(id="c2"), parent=categories, namespace=c())

y<-getNodeSet(tree,"//categories")

x<-getNumberOfCategories(y[[1]])
```

getNumberOfCriteria *Get number of criteria*

Description

Extracts the number of criteria from an XML tree written according to the XMCDA standard.

Usage

```
getNumberOfCriteria(tree, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the number of criteria of each <criteria> found in <tree>. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <criteria> tags could be correctly read, or the description of the error.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

criteria<-newXMLNode("criteria", parent=root[[1]], namespace=c())

criterion<-newXMLNode("criterion", attrs = c(id="g1"),
                       parent=criteria, namespace=c())

y<-getNodeSet(tree,"//criteria")

x<-getNumberOfCriteria(y[[1]])
```

getNumericValue	<i>Get a numeric value</i>
-----------------	----------------------------

Description

Extracts a numeric value (integer, real or rational) from an XML tree written according to the XMCDA standard and returns it as a real number.

Usage

```
getNumericValue(tree)
```

Arguments

tree	Object containing the XMCDA XML tree (in practice, only the part containing the <value> to be read).
------	--

Value

The function returns a float based on the numeric value read.

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

val<-newXMLNode("value", parent=root[[1]], namespace=c())
newXMLNode("real", 3.14, parent=val, namespace=c())

y<-getNodeSet(tree, "//value")
x<-getNumericValue(y)
```

`getParameters`*Get parameters*

Description

Gets the parameters defined in the <methodParameters> tag from an XML tree written according to the XMCDA standard.

Usage

```
getParameters(tree, name = NULL)
```

Arguments

- | | |
|------|---|
| tree | Object containing the XMCDA XML tree. |
| name | A string containing the specific name attribute which should be searched for. |

Value

The function returns a list structured as follows:

- | | |
|--------|---|
| -- | The first elements contain the parameters which have been read in each parameter tag (either a <label>, <real>, <integer> or <boolean>). These elements are named according to the name attribute if it can be found. |
| status | Either OK if all the <methodParameters> tags could be correctly read, or the description of the error. |

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.0.0"),
           parent=tree)

root<-getNodeSet(tree, "/xmcda:XMCDA")

parameters<-newXMLNode("methodParameters", parent=root[[1]], namespace=c())

parameter <- newXMLNode("parameter", attrs = c(name="numIt"),
                           parent=parameters, namespace=c())

value <- newXMLNode("value", parent=parameter, namespace=c())

newXMLNode("integer", value=3, parent=value, namespace=c())

y<-getNodeSet(tree,"//methodParameters")

x<-getParameters(y[[1]])
```

getPerformanceTables *Get performance tables*

Description

Extracts the performance tables stored in the <performanceTable> tags from an XML tree written according to the XMCDA standard.

Usage

```
getPerformanceTables(tree, altIDs = NULL, critIDs = NULL,  
                     mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
altIDs	A vector containing the IDs of the alternatives to be considered for the extractions.
critIDs	A vector containing the IDs of the criteria to be considered for the extractions.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

--	The first elements contain the performance tables found in each <performanceTable> of <tree> as matrices. The rows of each matrix are labelled according to the alternatives' IDs and the columns according to the criteria IDs. These elements are named according to the mcdaConcept attribute if it can be found.
status	Either OK if all the <performanceTable> tags could be correctly read, or the description of the error.

Examples

```
tree <- xmlTreeParse(system.file("extdata","testFile.xml",package="RXMLCDA"),  
                     useInternalNodes=TRUE)  
  
tables <- getPerformanceTables(tree)
```

putAlternativesAffectations
Puts alternative affectations

Description

Puts alternative affectations as an <alternativesAffectations> tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesAffectations(tree, alternativesAffectations,
                           alternativesIDs, categoriesIDs,
                           asIntervalsIfPossible = FALSE, mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
alternativesAffectations	An $n \times m$ matrix representing <alternativesAffectations>, where n is number of considered alternatives and m is number of considered categories. Each cell $[i, j]$ of each matrix is boolean and corresponds to encoded relation between i -th alternative and j -th category.
alternativesIDs	A vector containing the IDs of the alternatives to be considered for the extractions.
categoriesIDs	A vector containing the IDs of the categories to be considered for the extractions.
asIntervalsIfPossible	Whether put each affectation as a <categoriesInterval> tag (if possible) or as a <categoriesSet> tag.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

status	Either OK if all the <alternativesAffectations> tags could be correctly put, or the description of the error.
--------	---

Examples

```
alternativesIDs <- c("a01", "a02", "a03", "a04")
categoriesIDs <- c("c01", "c02", "c03", "c04")
altAff = rbind(c(FALSE, TRUE, TRUE, TRUE),
              c(FALSE, TRUE, FALSE, FALSE),
              c(TRUE, TRUE, TRUE, TRUE),
```

```
c(TRUE, TRUE, TRUE, FALSE))

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putAlternativesAffectations(tree, altAff, alternativesIDs, categoriesIDs, TRUE)
```

putAlternativesAffectationsWithValues*Puts alternative affectations with values***Description**

Puts alternative affectations as an <alternativesAffectations> tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesAffectationsWithValues(tree, alternativesAffectations,
                                      alternativesIDs, categoriesIDs, mcdaConcept = NULL)
```

Arguments

tree Object containing the XMCDA XML tree.

alternativesAffectations

An $n \times 3$ matrix representing <alternativesAffectations>, where n is the number of alternative affectations to write. Each row $[i,]$ of the matrix represents affectation of $[i, 1]$ -th alternative to $[i, 2]$ -th category with value $[i, 3]$.

alternativesIDs

A vector containing the IDs of the alternatives to be considered for the extractions.

categoriesIDs A vector containing the IDs of the categories to be considered for the extractions.

mcdaConcept A string containing the specific mcdaConcept attribute which should be searched for.

Value

The function returns a list structured as follows:

status Either OK if all the <alternativesAffectations> tags could be correctly put, or the description of the error.

Examples

```

alternativesIDs <- c("a01", "a02", "a03", "a04")
categoriesIDs <- c("c01", "c02", "c03")
altAff = rbind(c(1, 2, 0.1),
              c(1, 3, 0.0),
              c(2, 3, 1.0),
              c(4, 1, 0.5))

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putAlternativesAffectationsWithValues(tree, altAff, alternativesIDs, categoriesIDs)

```

putAlternativesComparisonsLabels
Put comparisons of alternatives

Description

Writes <alternativesComparisons> in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesComparisonsLabels(tree, alternativesComparisons,
                                 mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
alternativesComparisons	A matrix containing the <alternativesComparisons> as a matrix. Each line of each matrix corresponds to one constraint of the type "alternative a is preferred to alternative b with preference threshold delta". A line is structured as follows: the first element encodes the ID of alternative a, the second element encodes the ID of alternative b, and the last element contains a valuation.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be written.

Value

The function returns a list structured as follows:

status	Either OK if all the <alternativesComparisons> tags could be correctly put, or the description of the error.
--------	--

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

comps <- rbind(c("x", "y", "0.07"), c("y", "z", "0.01"))

altIDs <- c("x", "y", "z")

putAlternativesComparisonsLabels(tree, comps, mcdaConcept="newComparisons")
```

`putAlternativesIDs` *Put ids of alternatives*

Description

Puts ids of alternatives in an `alternatives` tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesIDs(tree, alternativesIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>alternativesIDs</code>	A vector containing the alternatives' IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if all the <code><alternative></code> tags could be correctly put, or the description of the error.
---------------------	---

Examples

```
altIDs <- c("x", "y", "z")

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
```

```
"xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
parent=tree)

putAlternativesIDs(tree, altIDs, mcdaConcept="test")

altIDs2 <- getAlternativesIDs(tree)
```

putAlternativesPlot *Put plot in base64 related to alternatives*

Description

Puts a plot coded in base64 as an `alternativeValue` tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesPlot(tree, base64plot, alternativesIDs,
mcdaConcept=NULL, name=NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>base64plot</code>	String containing the base64 encoding of the plot.
<code>alternativesIDs</code>	A vector of alternatives' IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.
<code>name</code>	A string containing the specific <code>name</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <code><alternativeValue></code> tag could be correctly put, or the description of the error.
---------------------	---

putAlternativesValues *Put values related to alternatives*

Description

Puts values related to alternatives as an `alternativesValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativesValues(tree, alternativesValues, alternativesIDs,  
                      mcdaConcept = NULL)
```

Arguments

`tree` Object containing the XMCDA XML tree.
`alternativesValues` A matrix containing the values of the alternatives which have to be stored. Each line of this matrix represents a statement of the form "alternative x has value y". The first element of each line stores the index of the alternative x in `alternativesIDs`, the second element stores the value y.
`alternativesIDs` A vector containing the alternatives' IDs.
`mcdaConcept` A string containing the specific `mcdaConcept` attribute which should be written.

Value

The function returns a list structured as follows:

`status` Either OK if all the `<alternativesValues>` tags could be correctly put, or the description of the error.

Examples

```
altIDs <- c("x", "y", "z")  
  
altVals <- rbind(c(1,1),c(2,0.5),c(3,0.2))  
  
tree = newXMLDoc()  
  
newXMLNode("xmcda:XMCDA",  
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",  
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),  
           parent=tree)  
  
putAlternativesValues(tree,altVals,altIDs)  
  
altVals2 <- getAlternativesValues(tree, altIDs)
```

`putAlternativeValue` *Put a value related to an alternative*

Description

Puts a value related to an alternative (or a set of alternatives) as a `alternativeValue` tag in an XML tree written according to the XMCDA standard.

Usage

```
putAlternativeValue(tree, alternativeValue,
                    alternativesIDs = NULL, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>alternativeValue</code>	A float representing the value assigned to the alternative.
<code>alternativesIDs</code>	A string representing the alternative's ID or a vector representing a set of alternatives IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <code><alternativeValue></code> tag could be correctly put, or the description of the error.
---------------------	---

Examples

```
altID <- c("x")

tree = newXMLDoc()

newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                       "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putAlternativeValue(tree, 0.8, alternativesIDs = altID)
```

putCapacity	<i>Put a capacity</i>
-------------	-----------------------

Description

Puts values related to a capacity as a `criteriaValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCapacity(tree, capacity, critIDs, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>capacity</code>	An object of type <code>capacity</code> (see <code>kappalab</code> package).
<code>critIDs</code>	A vector containing the criteria's IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if all the <code><criteriaValues></code> tags could be correctly put, or the description of the error.
---------------------	--

Examples

```
library(kappalab)

tree = newXMLDoc()

newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

mu<-capacity(0:15)

a <- Mobius(mu)

critIDs <- c("g1", "g2", "g3", "g4")

putCapacity(tree, a, critIDs, mcdaConcept="capacity")
```

putCategoriesIntervalValues*Put interval values related to categories*

Description

Puts interval values related to categories as a `categoriesValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCategoriesIntervalValues(tree, categoriesValues, categoriesIDs,
                           mcdaConcept = NULL)
```

Arguments

- | | |
|-------------------------------|--|
| <code>tree</code> | Object containing the XMCDA XML tree. |
| <code>categoriesValues</code> | A matrix representing a < <code>categoriesValues</code> >. Each line of each matrix corresponds to an element of the type "the interval value assigned to category c1 is [x, y]". A line is structured as follows: the first element encodes the index of the ID of category c1 in <code>categoriesIDs</code> , the second element encodes the value x and the third element encodes the value y. These elements are named according to the <code>mcdaConcept</code> attribute if it can be found. |
| <code>categoriesIDs</code> | A vector containing the categories' IDs. |
| <code>mcdaConcept</code> | A string containing the specific <code>mcdaConcept</code> attribute which should be written. |

Value

The function returns a list structured as follows:

- | | |
|---------------------|--|
| <code>status</code> | Either OK if all the < <code>categoriesValues</code> > tags could be correctly put, or the description of the error. |
|---------------------|--|

Examples

```
categoriesIDs <- c("c01", "c02", "c03", "c04")
categoriesIntervalValues <- rbind(c(1, 0.4, 0.7), c(2, 0.5, 0.5), c(4, 0.2, 0.9))

tree = newXMLDoc()

newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putCategoriesIntervalValues(tree, categoriesIntervalValues, categoriesIDs)
```

putCategoriesValues	<i>Put values related to categories</i>
---------------------	---

Description

Puts values related to categories as a `categoriesValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCategoriesValues(tree, categoriesValues, categoriesIDs,
                    mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
categoriesValues	A matrix representing a <categoriesValues>. Each line of each matrix corresponds to an element of the type "the value(s) assigned to category c1 is (are) x (x1, x2, ...)". A line is structured as follows: the first element encodes the index of the ID of category c1 in <code>categoriesIDs</code> , next elements encodes the values x1, x2... These elements are named according to the <code>mcdaConcept</code> attribute if it can be found.
categoriesIDs	A vector containing the categories' IDs.
mcdaConcept	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

status	Either OK if all the <categoriesValues> tags could be correctly put, or the description of the error.
--------	---

Examples

```
categoriesIDs <- c("c01", "c02", "c03", "c04")
categoriesValues <- rbind(c(1, 0.4), c(2, 0.5), c(4, 0.2))

tree = newXMLDoc()

newXMLNode("xmcda:XMCD", 
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCD-2.1.0"),
           parent=tree)

putCategoriesValues(tree, categoriesValues, categoriesIDs)
```

putCriteriaMatrix	<i>Puts values in a criteria matrix</i>
-------------------	---

Description

Puts values related to a matrix of criteria as a `criteriaMatrix` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCriteriaMatrix(tree, criteriaMatrix,
                  mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaMatrix</code>	A matrix representing a <code><criteriaMatrix></code></code>. The lines and the columns are named according to criteria IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <code><criteriaMatrix></code></code> tag could be correctly put, or the description of the error.
---------------------	--

Examples

```
critIDs <- c("x", "y", "z")

criteriaMatrix <- rbind(c(1,2,3),c(4,5,6),c(7,8,9))

rownames(criteriaMatrix) <- critIDs
colnames(criteriaMatrix) <- critIDs

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putCriteriaMatrix(tree,criteriaMatrix)
```

putCriteriaPairsValues*Put values related to pairs of criteria*

Description

Puts values related to pairs of criteria as a `criteriaValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCriteriaPairsValues(tree, criteriaPairsValues, criteriaIDs,
                      mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>criteriaPairsValues</code>	A matrix representing the values assigned to pairs of criteria. Each line of the matrix corresponds to one statement of the type "the value assigned to the couple of criteria (g1,g2) is x". A line is structured as follows: the first element encodes the index of criterion g1 in <code>criteriaIDs</code> , the next element encodes the index of the ID of criterion g2, and the last elements contain x.
<code>criteriaIDs</code>	A vector containing the criteria's IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if all the <code><criteriaValues></code> tags could be correctly put, or the description of the error.
---------------------	--

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                        "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

critIDs <- c("g1", "g2", "g3", "g4")

pairsVals <- rbind(c(1,2,0.17),c(2,3,0.5), c(3,4,0.16))

putCriteriaPairsValues(tree,pairsVals,critIDs)
```

putCriteriaPlot	<i>Put a plot in base64 related to criteria</i>
-----------------	---

Description

Puts a plot coded in base64 as a `criterionValue` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCriteriaPlot(tree, base64plot, criteriaIDs, mcdaConcept=NULL, name=NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>base64plot</code>	String containing the base64 encoding of the plot.
<code>criteriaIDs</code>	A vector of criteria's IDs.
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.
<code>name</code>	A string containing the specific <code>name</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <code><criterionValue></code> tag could be correctly put, or the description of the error.
---------------------	---

putCriteriaValues	<i>Put values related to criteria</i>
-------------------	---------------------------------------

Description

Puts values related to criteria as a `criteriaValues` tag in an XML tree written according to the XMCDA standard.

Usage

```
putCriteriaValues(tree, criteriaValues, criteriaIDs,
                  mcdaConcept = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
criteriaValues	A matrix representing a <criteriaValues>. Each line of each matrix corresponds to an element of the type "the value assigned to criterion g1 is x". A line is structured as follows: the first element encodes the index of the ID of criterion g1 in criteriaIDs, the second element encodes the value x. These elements are named according to the mcdaConcept attribute if it can be found.
criteriaIDs	A vector containing the criteria's IDs.
mcdaConcept	A string containing the specific mcdaConcept attribute which should be written.

Value

The function returns a list structured as follows:

status	Either OK if all the <criteriaValues> tags could be correctly put, or the description of the error.
--------	---

Examples

```

critIDs <- c("x", "y", "z")

critVals <- rbind(c(1,1),c(2,0.5),c(3,0.2))

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putCriteriaValues(tree,critVals,critIDs)

```

putCriterionValue *Put a value related to a criterion*

Description

Puts a value related to a criterion (or a set of criteria) as a criterionValue tag in an XML tree written according to the XMCDA standard.

Usage

```
putCriterionValue(tree, criterionValue, criteriaIDs = NULL,
                  mcdaConcept = NULL)
```

Arguments

- tree** Object containing the XMCDA XML tree.
criterionValue A float representing the value assigned to the criterion.
criteriaIDs A string representing the criterion's ID or a vector representing a set of criteria IDs.
mcdaConcept A string containing the specific mcdaConcept attribute which should be written.

Value

The function returns a list structured as follows:

- status** Either OK if all the <criterionValue> tags could be correctly put, or the description of the error.

Examples

```
critID <- c("x")

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putCriterionValue(tree,0.8,criteriaIDs = critID)
```

putErrorMessage *Put an error message*

Description

Puts an error message in a <methodMessages> tag of an XML tree written according to the XMCDA standard.

Usage

```
putErrorMessage(tree, errorMessage, name = NULL)
```

Arguments

- tree** Object containing the XMCDA XML tree.
errorMessage A string containing the text of the error message.
name A string containing the specific name attribute which should be searched for.

Value

The function returns a list structured as follows:

status	Either OK if the <errorMessage> tag could be correctly put, or the description of the error.
--------	--

putLogMessage	<i>Put a log message</i>
---------------	--------------------------

Description

Puts an log message in a <methodMessages> tag of an XML tree written according to the XMCDA standard.

Usage

```
putLogMessage(tree, logMessage, name = NULL)
```

Arguments

tree	Object containing the XMCDA XML tree.
logMessage	A string containing the text of the log message.
name	A string containing the specific name attribute which should be searched for.

Value

The function returns a list structured as follows:

status	Either OK if the <logMessage> tag could be correctly put, or the description of the error.
--------	--

putMessage	<i>Put a message</i>
------------	----------------------

Description

Puts an message in a <methodMessages> tag of an XML tree written according to the XMCDA standard.

Usage

```
putMessage(tree, message, name = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>message</code>	A string containing the text of the log message.
<code>name</code>	A string containing the specific name attribute which should be put.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <message> tag could be correctly put, or the description of the error.
---------------------	---

`putPerformanceTable` *Put a performance table in the XMCDA tree*

Description

Puts a performance table (`performanceTable` tag) in an XML tree written according to the XMCDA standard.

Usage

```
putPerformanceTable(tree, performanceTable, mcdaConcept = NULL)
```

Arguments

<code>tree</code>	Object containing the XMCDA XML tree.
<code>performanceTable</code>	A matrix representing the performance table (the lines are named according to the alternatives' IDs, the columns are named according to the criteria IDs).
<code>mcdaConcept</code>	A string containing the specific <code>mcdaConcept</code> attribute which should be written.

Value

The function returns a list structured as follows:

<code>status</code>	Either OK if the <performanceTable> tag could be correctly put, or the description of the error.
---------------------	--

Examples

```

performanceTable <- rbind(c(1,2,3),c(4,5,6))

rownames(performanceTable) <- c("x","y")

colnames(performanceTable) <- c("g1","g2","g3")

tree = newXMLDoc()

newXMLNode("xmcda:XMCDA",
           namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",
                         "xmcda" = "http://www.decision-deck.org/2009/XMCDA-2.1.0"),
           parent=tree)

putPerformanceTable(tree,performanceTable)

```

putPointsCriterionFunction

Put value functions defined by sets of points

Description

Puts value functions defined by sets of points in a `criterionFunction` tag under the `criterion` tag in an XML tree written according to the XMCDA standard.

Usage

```
putPointsCriterionFunction(tree, points, mcdaConcept = NULL)
```

Arguments

- | | |
|-------------|--|
| tree | Object containing the XMCDA XML tree. |
| points | A list, where each element is named by the ID of a criterion, and contains a matrix representing the points (each line is a point, the first column represents the abscissa, the second the ordinate). |
| mcdaConcept | A string containing the specific <code>mcdaConcept</code> attribute which should be written. |

Value

The function returns a list structured as follows:

- | | |
|--------|---|
| status | Either OK if all the <code><criterionFunction></code> tags could be correctly put, or the description of the error. |
|--------|---|

Examples

```
tree = newXMLDoc()

newXMLNode("xmcda:XMCD",  
          namespace = c("xsi" = "http://www.w3.org/2001/XMLSchema-instance",  
                      "xmcda" = "http://www.decision-deck.org/2009/XMCD-2.1.0"),  
          parent=tree)

x<-list()  
x<-c(x, list(g1=rbind(c(1,2),c(3,4))))  
x<-c(x, list(g2=rbind(c(5,6),c(7,8),c(9,10))))  
x<-c(x, list(g3=rbind(c(11,12))))  
x<-c(x, list(g4=rbind(c(13,14),c(15,16))))  
  
putPointsCriterionFunction(tree,x)
```

Index

* methods

checkXSD, 2
getAlternativesAffectations, 3
getAlternativesComparisons, 4
getAlternativesComparisonsLabels,
 6
getAlternativesIDs, 8
getAlternativesIntervalValues, 10
getAlternativesValues, 11
getCategoriesIDs, 12
getCategoriesIntervalValues, 13
getCategoriesValues, 14
getCriteriaComparisons, 15
getCriteriaComparisonsLabels, 16
getCriteriaIDs, 17
getCriteriaIntervalValues, 18
getCriteriaPairsComparisons, 19
getCriteriaPairsIntervalValues, 20
getCriteriaPairsValues, 21
getCriteriaValues, 22
getMobiusCapacities, 23
getNumberOfAlternatives, 24
getNumberOfCategories, 25
getNumberOfCriteria, 26
getNumericValue, 27
getParameters, 28
getPerformanceTables, 29
putAlternativesAffectations, 30
putAlternativesAffectationsWithValues,
 31
putAlternativesComparisonsLabels,
 32
putAlternativesIDs, 33
putAlternativesPlot, 34
putAlternativesValues, 35
putAlternativeValue, 36
putCapacity, 37
putCategoriesIntervalValues, 38
putCategoriesValues, 39
putCriteriaMatrix, 40
putCriteriaPairsValues, 41
putCriteriaPlot, 42
putCriteriaValues, 42
putCriterionValue, 43
putErrorMessage, 44
putLogMessage, 45
putMessage, 45
putPerformanceTable, 46
putPointsCriterionFunction, 47

checkXSD, 2

getAlternativesAffectations, 3
getAlternativesComparisons, 4
getAlternativesComparisonsLabels, 6
getAlternativesComparisonsValues, 7
getAlternativesIDs, 8
getAlternativesIntervalValues, 10
getAlternativesValues, 11
getCategoriesIDs, 12
getCategoriesIntervalValues, 13
getCategoriesValues, 14
getCriteriaComparisons, 15
getCriteriaComparisonsLabels, 16
getCriteriaIDs, 17
getCriteriaIntervalValues, 18
getCriteriaPairsComparisons, 19
getCriteriaPairsIntervalValues, 20
getCriteriaPairsValues, 21
getCriteriaValues, 22
getMobiusCapacities, 23
getNumberOfAlternatives, 24
getNumberOfCategories, 25
getNumberOfCriteria, 26
getNumericValue, 27
getParameters, 28
getPerformanceTables, 29
putAlternativesAffectations, 30

putAlternativesAffectationsWithValues,
 31
putAlternativesComparisonsLabels, 32
putAlternativesIDs, 33
putAlternativesPlot, 34
putAlternativesValues, 35
putAlternativeValue, 36
putCapacity, 37
putCategoriesIntervalValues, 38
putCategoriesValues, 39
putCriteriaMatrix, 40
putCriteriaPairsValues, 41
putCriteriaPlot, 42
putCriteriaValues, 42
putCriterionValue, 43
putErrorMessage, 44
putLogMessage, 45
putMessage, 45
putPerformanceTable, 46
putPointsCriterionFunction, 47