

Package ‘escalation’

May 29, 2023

Type Package

Title Modular Approach to Dose Finding Clinical Trials

Version 0.1.5

Date 2023-05-26

Maintainer Kristian Brock <kristian.brock@gmail.com>

Description Methods for working with dose-finding clinical trials. We provide implementations of many dose-finding clinical trial designs, including the continual reassessment method (CRM) by O’Quigley et al. (1990) <doi:10.2307/2531628>, the toxicity probability interval (TPI) design by Ji et al. (2007) <doi:10.1177/1740774507079442>, the modified TPI (mTPI) design by Ji et al. (2010) <doi:10.1177/1740774510382799>, the Bayesian optimal interval design (BOIN) by Liu & Yuan (2015) <doi:10.1111/rssc.12089>, EffTox by Thall & Cook (2004) <doi:10.1111/j.0006-341X.2004.00218.x>; the design of Wages & Tait (2015) <doi:10.1080/10543406.2014.920873>, and the 3+3 described by Korn et al. (1994) <doi:10.1002/sim.4780131802>. All designs are implemented with a common interface. We also offer optional additional classes to tailor the behaviour of all designs, including avoiding skipping doses, stopping after n patients have been treated at the recommended dose, stopping when a toxicity condition is met, or demanding that n patients are treated before stopping is allowed. By daisy-chaining together these classes using the pipe operator from ‘magrittr’, it is simple to tailor the behaviour of a dose-finding design so it behaves how the trialist wants. Having provided a flexible interface for specifying designs, we then provide functions to run simulations and calculate dose-paths for future cohorts of patients.

License GPL (>= 3)

Encoding UTF-8

Depends magrittr

Imports dplyr, tidyr (>= 1.0), tidyselect, stringr, purrr, tibble, gtools, dferm, BOIN, trialr (>= 0.1.5), DiagrammeR, RColorBrewer, viridis, binom

RoxygenNote 7.1.1

Suggests testthat, knitr, rmarkdown, ggplot2, covr

VignetteBuilder knitr

NeedsCompilation no

Author Kristian Brock [aut, cre] (<<https://orcid.org/0000-0002-3921-0166>>),
Daniel Slade [ctb] (<<https://orcid.org/0000-0001-6063-1283>>)

Repository CRAN

Date/Publication 2023-05-29 18:10:02 UTC

R topics documented:

escalation-package	4
as_tibble.dose_paths	4
calculate_probabilities	5
cohort	6
cohorts_of_n	6
continue	7
crystallised_dose_paths	8
demand_n_at_dose	9
dont_skip_doses	10
doses_given	11
dose_admissible	12
dose_indices	13
dose_paths	13
dose_paths_function	14
eff	14
eff_at_dose	15
eff_limit	16
empiric_eff_rate	17
empiric_tox_rate	17
enforce_three_plus_three	18
fit	19
follow_path	19
get_boin	20
get_dferm	21
get_dose_paths	23
get_empiric_crm_skeleton_weights	24
get_mtpi	24
get_mtpi2	26
get_random_selector	28
get_three_plus_three	29
get_tpi	30
get_trialr_crm	32
get_trialr_efftox	34
get_trialr_nbg	35
get_wages_and_tait	37
graph_paths	39
is_randomising	40

mean_prob_eff	40
mean_prob_tox	41
median_prob_eff	42
median_prob_tox	43
model_frame	43
num_cohort_outcomes	44
num_doses	45
num_dose_path_nodes	45
num_eff	46
num_patients	47
num_tox	47
n_at_dose	48
n_at_recommended_dose	49
parse_phase1_2_outcomes	49
parse_phase1_outcomes	50
phase1_2_outcomes_to_cohorts	52
phase1_outcomes_to_cohorts	53
prob_administer	54
prob_eff_quantile	55
prob_recommend	56
prob_tox_exceeds	56
prob_tox_quantile	57
prob_tox_samples	58
recommended_dose	59
selector	60
selector_factory	63
select_boin_mtd	65
select_dose_by_cibp	66
simulate_trials	67
simulations	70
simulation_function	72
spread_paths	72
stop_at_n	73
stop_when_n_at_dose	74
stop_when_too_toxic	75
stop_when_tox_ci_covered	77
supports_sampling	79
three_plus_three	79
tox	80
tox_at_dose	81
tox_limit	82
tox_target	83
trial_duration	83
try_rescue_dose	84

escalation-package *The 'escalation' package.*

Description

escalation provides methods for working with dose-finding clinical trials. We provide implementations of many dose-finding clinical trial designs, including the continual reassessment method (CRM) by O'Quigley et al. (1990) <doi:10.2307/2531628>, the toxicity probability interval (TPI) design by Ji et al. (2007) <doi:10.1177/1740774507079442>, the modified TPI (mTPI) design by Ji et al. (2010) <doi:10.1177/1740774510382799>, the Bayesian optimal interval design (BOIN) by Liu & Yuan (2015) <doi:10.1111/rssc.12089>, EffTox by Thall & Cook (2004) <doi:10.1111/j.0006-341X.2004.00218.x>; the design of Wages & Tait (2015) <doi:10.1080/10543406.2014.920873>, and the 3+3 described by Korn et al. (1994) <doi:10.1002/sim.4780131802>. All designs are implemented with a common interface. We also offer optional additional classes to tailor the behaviour of all designs, including avoiding skipping doses, stopping after n patients have been treated at the recommended dose, stopping when a toxicity condition is met, or demanding that n patients are treated before stopping is allowed. By daisy-chaining together these classes using the pipe operator from 'magrittr', it is simple to tailor the behaviour of a dose-finding design so it behaves how the trialist wants. Having provided a flexible interface for specifying designs, we then provide functions to run simulations and calculate dose-paths for future cohorts of patients.

as_tibble.dose_paths *Cast `dose_paths` object to `tibble`.*

Description

Cast `dose_paths` object to `tibble`.

Usage

```
## S3 method for class 'dose_paths'  
as_tibble(x, ...)
```

Arguments

x Object of class `dose_finding_paths`.
... Extra args passed onwards.

Value

Object of class `tibble`

`calculate_probabilities`*Calculate dose-path probabilities*

Description

Crystallise a set of [dose_paths](#) with probabilities to calculate how likely each path is. Once probabilised in this way, the probabilities of the terminal nodes in this set of paths will sum to 1. This allows users to calculate operating characteristics.

Usage

```
calculate_probabilities(dose_paths, true_prob_tox, true_prob_eff = NULL, ...)
```

Arguments

<code>dose_paths</code>	Object of type dose_paths
<code>true_prob_tox</code>	Numeric vector, true probability of toxicity.
<code>true_prob_eff</code>	vector of true efficacy probabilities, optionally NULL if efficacy not analysed.
<code>...</code>	Extra parameters

See Also

[dose_paths](#)

Examples

```
# Phase 1 example.
# Calculate dose paths for the first three cohorts in a 3+3 trial of 5 doses:
paths <- get_three_plus_three(num_doses = 5) %>%
  get_dose_paths(cohort_sizes = c(3, 3, 3))

# Set the true probabilities of toxicity
true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)
# And calculate exact operating performance
x <- paths %>% calculate_probabilities(true_prob_tox)
prob_recommend(x)

# Phase 1/2 example.
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
selector_factory <- get_random_selector(prob_select = prob_select,
                                       supports_efficacy = TRUE)
paths <- selector_factory %>% get_dose_paths(cohort_sizes = c(2, 2))
true_prob_eff <- c(0.27, 0.35, 0.41, 0.44, 0.45)
x <- paths %>% calculate_probabilities(true_prob_tox = true_prob_tox,
                                     true_prob_eff = true_prob_eff)

prob_recommend(x)
```

cohort	<i>Cohort numbers of evaluated patients.</i>
--------	--

Description

Get a vector of integers that reflect the cohorts to which the evaluated patients belong.

Usage

```
cohort(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

an integer vector

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% cohort()
```

cohorts_of_n	<i>Sample times between patient arrivals using the exponential distribution.</i>
--------------	--

Description

Sample times between patient arrivals using the exponential distribution.

Usage

```
cohorts_of_n(n = 3, mean_time_delta = 1)
```

Arguments

n	integer, sample arrival times for this many patients.
mean_time_delta	the average gap between patient arrival times. I.e. the reciprocal of the rate parameter in an Exponential distribution.

Value

data.frame with column `time_delta` containing durations of time between patient arrivals.

Examples

```
cohorts_of_n()
cohorts_of_n(n = 10, mean_time_delta = 5)
```

continue

Should this dose-finding experiment continue?

Description

Should this dose-finding experiment continue? Or have circumstances prevailed that dictate this trial should stop? This method is critical to the automatic calculation of statistical operating characteristics and dose-pathways. You add stopping behaviours to designs using calls like [stop_at_n](#) and [stop_when_too_toxic](#).

Usage

```
continue(x, ...)
```

Arguments

`x` Object of type [selector](#).
`...` Extra args are passed onwards.

Value

logical

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model1 <- get_dfcrm(skeleton = skeleton, target = target)
fit1 <- model1 %>% fit('1NNN 2NTN')
fit1 %>% continue()

model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 6)
fit2 <- model2 %>% fit('1NNN 2NTN')
fit2 %>% continue()
```

crystallised_dose_paths

Dose-paths with probabilities attached.

Description

[dose_paths](#) reflect all possible paths a dose-finding trial may take. When the probability of those paths is calculated using an assumed set of true dose-event probabilities, in this package those paths are said to be crystallised. Once crystallised, operating characteristics can be calculated.

Usage

```
crystallised_dose_paths(  
  dose_paths,  
  true_prob_tox,  
  true_prob_eff = NULL,  
  terminal_nodes  
)
```

Arguments

dose_paths	Object of type dose_paths
true_prob_tox	vector of toxicity probabilities at doses 1..n
true_prob_eff	vector of efficacy probabilities at doses 1..n, optionally NULL if efficacy not evaluated.
terminal_nodes	tibble of terminal nodes on the dose-paths

Value

An object of type `crystallised_dose_paths`

Examples

```
# Calculate dose paths for the first three cohorts in a 3+3 trial of 5 doses:  
paths <- get_three_plus_three(num_doses = 5) %>%  
  get_dose_paths(cohort_sizes = c(3, 3, 3))  
  
# Set the true probabilities of toxicity  
true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)  
# Crystallise the paths with the probabilities of toxicity  
x <- paths %>% calculate_probabilities(true_prob_tox)  
# And then examine, for example, the probabilities of recommending each dose  
# at the terminal nodes of these paths:  
prob_recommend(x)
```

demand_n_at_dose *Demand there are n patients at a dose before considering stopping.*

Description

This method continues a dose-finding trial until there are n patients at a dose. Once that condition is met, it delegates stopping responsibility to its parent dose selector, whatever that might be. This class is greedy in that it meets its own needs before asking any other selectors in a chain what they want. Thus, different behaviours may be achieved by nesting dose selectors in different orders. See examples.

Usage

```
demand_n_at_dose(parent_selector_factory, n, dose)
```

Arguments

parent_selector_factory	Object of type selector_factory .
n	Continue at least until there are n at a dose.
dose	'any' to continue until there are n at any dose; 'recommended' to continue until there are n at the recommended dose; or an integer to continue until there are n at a particular dose-level.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# This model will demand 9 at any dose before it countenances stopping.
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  demand_n_at_dose(n = 9, dose = 'any')

# This model will recommend continuing:
model1 %>% fit('1NNT 1NNN 2TNN 2NNN') %>% continue()
# It tells you to continue because there is no selector considering when
# you should stop - dfcrm implements no stopping rule by default.

# In contrast, we can add a stopping selector to discern the behaviour of
# demand_n_at_dose. We will demand 9 are seen at the recommended dose before
# stopping is permitted in model3:
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12)
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
```

```

stop_at_n(n = 12) %>%
demand_n_at_dose(n = 9, dose = 'recommended')

# This model advocates stopping because 12 patients are seen in total:
model2 %>% fit('1NNN 1NNN 2TNN 2NNN') %>% continue()
# But this model advocates continuing because 9 patients have not been seen
# at any dose yet:
model3 %>% fit('1NNN 1NNN 2TNN 2NNN') %>% continue()
# This shows how demand_n_at_dose overrides stopping behaviours that come
# before it in the daisychain.

# Once 9 are seen at the recommended dose, the decision to stop is made:
fit <- model3 %>% fit('1NNN 1NNN 2TNN 2NNN 2TTN')
fit %>% continue()
fit %>% recommended_dose()

```

dont_skip_doses	<i>Prevent skipping of doses.</i>
-----------------	-----------------------------------

Description

This method optionally prevents dose selectors from skipping doses when escalating and / or deescalating. The default is that skipping when escalating is prevented but skipping when deescalating is permitted, but both of these behaviours can be altered.

Usage

```

dont_skip_doses(
  parent_selector_factory,
  when_escalating = TRUE,
  when_deescalating = FALSE
)

```

Arguments

`parent_selector_factory`
Object of type [selector_factory](#).

`when_escalating`
TRUE to prevent skipping when attempting to escalate.

`when_deescalating`
TRUE to prevent skipping when attempting to deescalate.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  dont_skip_doses()
fit1 <- model1 %>% fit('1NNN')

model2 <- get_dfcrm(skeleton = skeleton, target = target)
fit2 <- model2 %>% fit('1NNN')

# fit1 will not skip doses
fit1 %>% recommended_dose()
# But fit2 will:
fit2 %>% recommended_dose()

# Similar demonstration for de-escalation
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  dont_skip_doses(when_deescalating = TRUE)
fit1 <- model1 %>% fit('1NNN 2N 3TTT')

model2 <- get_dfcrm(skeleton = skeleton, target = target)
fit2 <- model2 %>% fit('1NNN 2N 3TTT')

# fit1 will not skip doses
fit1 %>% recommended_dose()
# But fit2 will:
fit2 %>% recommended_dose()
```

doses_given

Doses given to patients.

Description

Get a vector of the dose-levels that have been administered to patients.

Usage

```
doses_given(x, ...)
```

Arguments

x Object of type [selector](#).
... Extra args are passed onwards.

Value

an integer vector

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% doses_given()
```

dose_admissible	<i>Is each dose admissible?</i>
-----------------	---------------------------------

Description

Get a vector of logical values reflecting whether each dose is admissible. Admissibility is defined in different ways for different models, and may not be defined at all in some models. For instance, in the TPI method, doses are inadmissible when the posterior probability is high that the toxicity rate exceeds the target value. In contrast, admissibility is not defined in the general CRM model (but it can be added with auxiliary classes). In this latter case, doses are implicitly considered to be admissible, by default.

Usage

```
dose_admissible(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

a logical vector

Examples

```
outcomes <- '1NNN 2TTT'

# TPI example. This method defines admissibility.
fit1 <- get_tpi(num_doses = 5, target = 0.3, k1 = 1, k2 = 1.5,
               exclusion_certainty = 0.95) %>%
  fit(outcomes)
fit1 %>% dose_admissible()

# Ordinary CRM example with no admissibility function.
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
fit2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  fit(outcomes)
fit2 %>% dose_admissible()
```

```
# Same CRM example with added admissibility function
fit3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_too_toxic(dose = 1, tox_threshold = target, confidence = 0.8) %>%
  fit(outcomes)
fit3 %>% dose_admissible()
```

dose_indices

Dose indices

Description

Get the integers from 1 to the number of doses under investigation.

Usage

```
dose_indices(x, ...)
```

Arguments

x Object of type [selector](#).
 ... Extra args are passed onwards.

Value

an integer vector

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% dose_indices()
```

dose_paths

Dose pathways

Description

A dose-escalation design exists to select doses in response to observed outcomes. The entire space of possible responses can be calculated to show the behaviour of a design in response to all feasible outcomes. The [get_dose_paths](#) function performs that task and returns an instance of this object.

Usage

```
dose_paths()
```

See Also[selector](#)**Examples**

```
# Calculate dose-paths for the 3+3 design:
paths <- get_three_plus_three(num_doses = 5) %>%
  get_dose_paths(cohort_sizes = c(3, 3))
```

dose_paths_function *Get function for calculating dose pathways.*

Description

This function does not need to be called by users. It is used internally.

Usage

```
dose_paths_function(selector_factory)
```

Arguments

selector_factory
 Object of type [selector_factory](#).

Value

A function.

eff *Binary efficacy outcomes.*

Description

Get a vector of the binary efficacy outcomes for evaluated patients.

Usage

```
eff(x, ...)
```

Arguments

x Object of type [selector](#).
 ... Extra args are passed onwards.

Value

an integer vector

Examples

```
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select,
                             supports_efficacy = TRUE)
x <- model %>% fit('1NTN 2EN 5BB')
eff(x)
```

eff_at_dose	<i>Number of toxicities seen at each dose.</i>
-------------	--

Description

Get the number of toxicities seen at each dose under investigation.

Usage

```
eff_at_dose(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

an integer vector

Examples

```
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select,
                             supports_efficacy = TRUE)
x <- model %>% fit('1NTN 2EN 5BB')
eff_at_dose(x)
```

eff_limit	<i>Efficacy rate limit</i>
-----------	----------------------------

Description

Get the minimum permissible efficacy rate, if supported. NULL if not.

Usage

```
eff_limit(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

numeric

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
  beta_mean = 1.5482, beta_sd = 3.5018,
  gamma_mean = 0.7367, gamma_sd = 2.5423,
  zeta_mean = 3.4181, zeta_sd = 2.4406,
  eta_mean = 0, eta_sd = 0.2,
  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
  efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
  p_e = 0.1, p_t = 0.1,
  eff0 = 0.5, tox1 = 0.65,
  eff_star = 0.7, tox_star = 0.25,
  priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
eff_limit(x)
```

empiric_eff_rate	<i>Observed efficacy rate at each dose.</i>
------------------	---

Description

Get the empirical or observed efficacy rate seen at each dose under investigation. This is simply the number of efficacies divided by the number of patients evaluated.

Usage

```
empiric_eff_rate(x, ...)
```

Arguments

x	Object of class selector
...	arguments passed to other methods

Value

a numerical vector

Examples

```
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select,
                             supports_efficacy = TRUE)
x <- model %>% fit('1NTN 2EN 5BB')
empiric_tox_rate(x)
```

empiric_tox_rate	<i>Observed toxicity rate at each dose.</i>
------------------	---

Description

Get the empirical or observed toxicity rate seen at each dose under investigation. This is simply the number of toxicities divided by the number of patients evaluated.

Usage

```
empiric_tox_rate(x, ...)
```

Arguments

x	Object of class selector
...	arguments passed to other methods

Value

a numerical vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% empiric_tox_rate()
```

enforce_three_plus_three

Enforce that a trial path has followed the 3+3 method.

Description

This function stops with an error if it detects that outcomes describing a trial path have diverged from that advocated by the 3+3 method.

Usage

```
enforce_three_plus_three(outcomes, allow_deescalate = FALSE)
```

Arguments

`outcomes` Outcomes observed. See [parse_phase1_outcomes](#).
`allow_deescalate` TRUE to allow de-escalation, as described by Korn et al. Default is FALSE.

Value

Nothing. Function stops if problem detected.

Examples

```
## Not run:
enforce_three_plus_three('1NNN 2NTN 2NNN') # OK
enforce_three_plus_three('1NNN 2NTN 2N') # OK too, albeit in-progress cohort
enforce_three_plus_three('1NNN 1N') # Not OK because should have escalated

## End(Not run)
```

fit	<i>Fit a dose-finding model.</i>
-----	----------------------------------

Description

Fit a dose-finding model to some outcomes.

Usage

```
fit(selector_factory, outcomes, ...)
```

Arguments

selector_factory	Object of type selector_factory .
outcomes	Outcome string. See parse_phase1_outcomes .
...	Extra args are passed onwards.

Value

Object of generic type [selector](#).

See Also

[selector](#), [selector_factory](#)

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% recommended_dose() # Etc
```

follow_path	<i>Follow a pre-determined dose administration path.</i>
-------------	--

Description

This method creates a dose selector that will follow a pre-specified trial path. Whilst the trial path is matched by realised outcomes, the selector will recommend the next dose in the desired sequence. As soon as the observed outcomes diverge from the desired path, the selector stops giving dose recommendations. This makes it possible, for instance, to specify a fixed escalation plan that should be followed until the first toxicity is seen. This tactic is used by some model-based designs to get rapidly to the doses where the action is. See, for example, the `dfcrm` package and Cheung (2011).

Usage

```
follow_path(path)
```

Arguments

path Follow this outcome path. See [parse_phase1_outcomes](#).

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

References

Cheung. Dose Finding by the Continual Reassessment Method. 2011. Chapman and Hall/CRC. ISBN 9781420091519

Examples

```
model1 <- follow_path(path = '1NNN 2NNN 3NNN 4NNN')

fit1 <- model1 %>% fit('1NNN 2N')
fit1 %>% recommended_dose()
fit1 %>% continue()
# The model recommends continuing at dose 2 because the observed outcomes
# perfectly match the desired escalation path.

fit2 <- model1 %>% fit('1NNN 2NT')
fit2 %>% recommended_dose()
fit2 %>% continue()
# Uh oh. Toxicity has now been seen, the outcomes diverge from the sought
# path, hence this class recommends no dose now.
# At this point, we can hand over dose selection decisions to another class
# by chaining them together, like:
model2 <- follow_path(path = '1NNN 2NNN 3NNN 4NNN') %>%
  get_dfcrm(skeleton = c(0.05, 0.1, 0.25, 0.4, 0.6), target = 0.25)
fit3 <- model2 %>% fit('1NNN 2NT')
# Now the CRM model is using all of the outcomes to calculate the next dose:
fit3 %>% recommended_dose()
fit3 %>% continue()
```

```
get_boin
```

Get an object to fit the BOIN model using the BOIN package.

Description

Get an object to fit the BOIN model using the BOIN package.

Usage

```
get_boin(num_doses, target, use_stopping_rule = TRUE, ...)
```

Arguments

num_doses	Number of doses under investigation.
target	We seek a dose with this probability of toxicity.
use_stopping_rule	TRUE to use the toxicity stopping rule described in Yan et al. (2019). FALSE to suppress the authors' stopping rule, with the assumption being that you will test the necessity to stop early in some other way.
...	Extra args are passed to get.boundary .

Value

an object of type [selector_factory](#) that can fit the BOIN model to outcomes.

References

Yan, F., Pan, H., Zhang, L., Liu, S., & Yuan, Y. (2019). BOIN: An R Package for Designing Single-Agent and Drug-Combination Dose-Finding Trials Using Bayesian Optimal Interval Designs. *Journal of Statistical Software*, 27(November 2017), 0–35. <https://doi.org/10.18637/jss.v000.i00>

Liu, S., & Yuan, Y. (2015). Bayesian optimal designs for Phase I clinical trials. *J. R. Stat. Soc. C*, 64, 507–523. <https://doi.org/10.1111/rssc.12089>

Examples

```
target <- 0.25
model1 <- get_boin(num_doses = 5, target = target)

outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()
```

get_dfcrm

Get an object to fit the CRM model using the dfcrm package.

Description

This function returns an object that can be used to fit a CRM model using methods provided by the dfcrm package.

Dose selectors are designed to be daisy-chained together to achieve different behaviours. This class is a **resumptive** selector, meaning it carries on when the previous dose selector, where present, has elected not to continue. For example, this allows instances of this class to be preceded by a selector that follows a fixed path in an initial escalation plan, such as that provided by [follow_path](#). In this example, when the observed trial outcomes deviate from that initial plan, the selector following the fixed path elects not to continue and responsibility passes to this class. See Examples.

Usage

```
get_dfcrm(parent_selector_factory = NULL, skeleton, target, ...)
```

Arguments

parent_selector_factory	optional object of type <code>selector_factory</code> that is in charge of dose selection before this class gets involved. Leave as <code>NULL</code> to just use CRM from the start.
skeleton	Dose-toxicity skeleton, a non-decreasing vector of probabilities.
target	We seek a dose with this probability of toxicity.
...	Extra args are passed to <code>crm</code> .

Value

an object of type `selector_factory` that can fit the CRM model to outcomes.

References

Cheung, K. 2019. `dfcrm`: Dose-Finding by the Continual Reassessment Method. R package version 0.2-2.1. <https://CRAN.R-project.org/package=dfcrm>

Cheung, K. 2011. Dose Finding by the Continual Reassessment Method. Chapman and Hall/CRC. ISBN 9781420091519

O'Quigley J, Pepe M, Fisher L. Continual reassessment method: a practical design for phase 1 clinical trials in cancer. *Biometrics*. 1990;46(1):33-48. doi:10.2307/2531628

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model1 <- get_dfcrm(skeleton = skeleton, target = target)

# By default, dfcrm fits the empiric model:
outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()

# But we can provide extra args to get_dfcrm that are than passed onwards to
# the call to dfcrm::crm to override the defaults. For example, if we want
# the one-parameter logistic model:
model2 <- get_dfcrm(skeleton = skeleton, target = target, model = 'logistic')
model2 %>% fit(outcomes) %>% recommended_dose()
# dfcrm does not offer a two-parameter logistic model but other classes do.

# We can use an initial dose-escalation plan, a pre-specified path that
# should be followed until trial outcomes deviate, at which point the CRM
# model takes over. For instance, if we want to use two patients at each of
# the first three doses in the absence of toxicity, irrespective the model's
# advice, we would run:
model1 <- follow_path('1NN 2NN 3NN') %>%
  get_dfcrm(skeleton = skeleton, target = target)

# If outcomes match the desired path, the path is followed further:
model1 %>% fit('1NN 2N') %>% recommended_dose()
```

```
# But when the outcomes diverge:
model1 %>% fit('1NN 2T') %>% recommended_dose()

# Or the pre-specified path comes to an end:
model1 %>% fit('1NN 2NN 3NN') %>% recommended_dose()
# The CRM model takes over.
```

get_dose_paths	<i>Calculate future dose paths.</i>
----------------	-------------------------------------

Description

A dose-escalation design exists to select doses in response to observed outcomes. The entire space of possible responses can be calculated to show the behaviour of a design in response to all feasible outcomes. This function performs that task.

Usage

```
get_dose_paths(selector_factory, cohort_sizes, ...)
```

Arguments

selector_factory	Object of type selector_factory .
cohort_sizes	Integer vector representing sizes of
...	Extra args are passed onwards.

Value

Object of type [dose_paths](#).

Examples

```
# Calculate paths for a 3+3 design for the next two cohorts of three patients
paths <- get_three_plus_three(num_doses = 5) %>%
  get_dose_paths(cohort_sizes = c(3, 3))
```

```
get_empiric_crm_skeleton_weights
```

Get posterior model weights for several empiric CRM skeletons.

Description

Get posterior model weights for several empiric CRM skeletons, assuming a normal prior on the beta model parameter

Usage

```
get_empiric_crm_skeleton_weights(
  skeletons,
  events_at_dose,
  n_at_dose,
  prior = rep(1, nrow(skeletons))
)
```

Arguments

skeletons	matrix with one skeleton per row, so that the number of columns is the number of doses under investigation.
events_at_dose	integer vector of number of events at doses
n_at_dose	integer vector of number of patients at doses
prior	vector of prior model weights. Length should be same as number of rows in skeletons. Default is equal weighting.

Value

numerical vector, posterior weights of the skeletons.

Examples

```
# TODO
```

```
get_mtpi
```

Get an object to fit the mTPI dose-finding model.

Description

The modified toxicity probability interval (mTPI) is a dose-escalation design by Ji et al. As the name suggests, it is an adaptation of the TPI design.

Usage

```
get_mtpi(
  parent_selector_factory = NULL,
  num_doses,
  target,
  epsilon1,
  epsilon2,
  exclusion_certainty,
  alpha = 1,
  beta = 1,
  ...
)
```

Arguments

parent_selector_factory	Object of type selector_factory .
num_doses	Number of doses under investigation.
target	We seek a dose with this probability of toxicity.
epsilon1	This parameter determines the lower bound of the equivalence interval. See Details.
epsilon2	This parameter determines the upper bound of the equivalence interval. See Details.
exclusion_certainty	Numeric, threshold posterior certainty required to exclude a dose for being excessively toxic. The authors discuss values in the range 0.7 - 0.95. Set to a value > 1 to suppress the dose exclusion mechanism. The authors use the Greek letter ξ for this parameter.
alpha	First shape parameter of the beta prior distribution on the probability of toxicity.
beta	Second shape parameter of the beta prior distribution on the probability of toxicity.
...	Extra args are passed onwards.

Value

an object of type [selector_factory](#) that can fit the TPI model to outcomes.

Details

The design seeks a dose with probability of toxicity p_i close to a target probability p_T by iteratively calculating the interval

$$p_T - \epsilon_1 < p_i < p_T + \epsilon_2$$

In this model, ϵ_1 and ϵ_2 are specified constants. p_i is estimated by a Bayesian beta-binomial conjugate model

$$p_i | data \sim \text{Beta}(\alpha + x_1, \beta + n_i - x_i),$$

where x_i is the number of toxicities observed and n_i is the number of patients treated at dose i , and α and β are hyperparameters for the beta prior on p_i . A dose is excluded as inadmissible if

$$P(p_i > p_T | data) > \xi$$

The trial commences at a starting dose, possibly dose 1. If dose i has just been evaluated in patient(s), dose selection decisions proceed by calculating the unit probability mass of the true toxicity rate at dose i using the partition of the probability space $p_i < p_T - \epsilon_1$, $p_T - \epsilon_1 < p_i < p_T + \epsilon_2$, and $p_i > p_T + \epsilon_2$. The unit probability mass (UPM) of an interval is the posterior probability that the true toxicity rate belongs to the interval divided by the width of the interval. The interval with maximal UPM determines the recommendation for the next patient(s), with the intervals corresponding to decisions to escalate, stay, and de-escalate dose, respectively. Further to this are rules that prevent escalation to an inadmissible dose. In their paper, the authors demonstrate acceptable operating performance using $\alpha = \beta = 1$, $K_1 = 1$, $K_2 = 1.5$ and $\xi = 0.95$. See the publications for full details.

References

- Ji, Y., Liu, P., Li, Y., & Bekele, B. N. (2010). A modified toxicity probability interval method for dose-finding trials. *Clinical Trials*, 7(6), 653-663. <https://doi.org/10.1177/1740774510382799>
- Ji, Y., & Yang, S. (2017). On the Interval-Based Dose-Finding Designs, 1-26. Retrieved from <https://arxiv.org/abs/1706.03277>

Examples

```
target <- 0.25
model1 <- get_mtpi(num_doses = 5, target = target, epsilon1 = 0.05,
  epsilon2 = 0.05, exclusion_certainty = 0.95)

outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()
```

```
get_mtpi2
```

Get an object to fit the mTPI-2 dose-finding model.

Description

The modified toxicity probability interval 2 (mTPI-2) is a dose-escalation design by Guo et al. As the name suggests, it is an adaptation of the mTPI design.

Usage

```
get_mtpi2(
  parent_selector_factory = NULL,
  num_doses,
  target,
  epsilon1,
```

```

    epsilon2,
    exclusion_certainty,
    alpha = 1,
    beta = 1,
    ...
)

```

Arguments

parent_selector_factory	Object of type selector_factory .
num_doses	Number of doses under investigation.
target	We seek a dose with this probability of toxicity.
epsilon1	This parameter determines the lower bound of the equivalence interval. See Details.
epsilon2	This parameter determines the upper bound of the equivalence interval. See Details.
exclusion_certainty	Numeric, threshold posterior certainty required to exclude a dose for being excessively toxic. The authors discuss values in the range 0.7 - 0.95. Set to a value > 1 to suppress the dose exclusion mechanism. The authors use the Greek letter ξ for this parameter.
alpha	First shape parameter of the beta prior distribution on the probability of toxicity.
beta	Second shape parameter of the beta prior distribution on the probability of toxicity.
...	Extra args are passed onwards.

Value

an object of type [selector_factory](#) that can fit the mTPI-2 model to outcomes.

Details

The design seeks a dose with probability of toxicity p_i close to a target probability p_T by iteratively calculating the interval

$$p_T - \epsilon_1 < p_i < p_T + \epsilon_2$$

In this model, ϵ_1 and ϵ_2 are specified constants. p_i is estimated by a Bayesian beta-binomial conjugate model

$$p_i|data \sim Beta(\alpha + x_i, \beta + n_i - x_i),$$

where x_i is the number of toxicities observed and n_i is the number of patients treated at dose i , and α and β are hyperparameters for the beta prior on p_i . A dose is excluded as inadmissible if

$$P(p_i > p_T|data) > \xi$$

The trial commences at a starting dose, possibly dose 1. If dose i has just been evaluated in patient(s), dose selection decisions proceed by calculating the unit probability mass of the true toxicity rate at dose i using the partition of the probability space into subintervals with equal length

given by $(\epsilon_1 + \epsilon_2)$. EI is the equivalence interval $p_T - \epsilon_1, p_T - \epsilon_2$, with LI the set of all intervals below, and HI the set of all intervals above. The unit probability mass (UPM) of an interval is the posterior probability that the true toxicity rate belongs to the interval divided by the width of the interval. The interval with maximal UPM determines the recommendation for the next patient(s), with the intervals corresponding to decisions to escalate, stay, and de-escalate dose, respectively. Further to this are rules that prevent escalation to an inadmissible dose. In the original mTPI paper, the authors demonstrate acceptable operating performance using $\alpha = \beta = 1$, $K_1 = 1$, $K_2 = 1.5$ and $\xi = 0.95$. The authors of the mTPI-2 approach show desirable performance as compared to the original mTPI method, under particular parameter choices. See the publications for full details.

References

- Ji, Y., Liu, P., Li, Y., & Bekele, B. N. (2010). A modified toxicity probability interval method for dose-finding trials. *Clinical Trials*, 7(6), 653–663. <https://doi.org/10.1177/1740774510382799>
- Ji, Y., & Yang, S. (2017). On the Interval-Based Dose-Finding Designs, 1–26. Retrieved from <https://arxiv.org/abs/1706.03277>
- Guo, W., Wang, S.J., Yang, S., Lynn, H., Ji, Y. (2017). A Bayesian Interval Dose-Finding Design Addressing Ockham’s Razor: mTPI-2. <https://doi.org/10.1016/j.cct.2017.04.006>

Examples

```
target <- 0.25
model1 <- get_mtpi2(num_doses = 5, target = target, epsilon1 = 0.05,
  epsilon2 = 0.05, exclusion_certainty = 0.95)

outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()
```

get_random_selector *Get an object to fit a dose-selector that randomly selects doses.*

Description

Get an object to fit a dose-selector that randomly selects doses. Whilst this design is unlikely to pass the ethical hurdles when investigating truly experimental treatments, this class is useful for illustrating methods and can be useful for benchmarking.

Usage

```
get_random_selector(
  parent_selector_factory = NULL,
  prob_select,
  supports_efficacy = FALSE,
  ...
)
```

Arguments

parent_selector_factory
 optional object of type `selector_factory` that is in charge of dose selection before this class gets involved. Leave as NULL to just select random doses from the start.

prob_select vector of probabilities, the probability of selecting dose 1...n

supports_efficacy
 TRUE to monitor toxicity and efficacy outcomes; FALSE (by default) to just monitor toxicity outcomes.

... Extra args are ignored.

Value

an object of type `selector_factory`.

Examples

```
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select)
fit <- model %>% fit('1NTN')
fit %>% recommended_dose() # This is random
# We could also precede this selector with a set path:
model <- follow_path('1NN 2NN 3NN') %>%
  get_random_selector(prob_select = prob_select)
fit <- model %>% fit('1NN')
fit %>% recommended_dose() # This is not-random; it comes from the path.
fit <- model %>% fit('1NN 2NT')
fit %>% recommended_dose() # This is random; the path is discarded.
```

`get_three_plus_three` *Get an object to fit the 3+3 model.*

Description

Get an object to fit the 3+3 model.

Usage

```
get_three_plus_three(num_doses, allow_deescalate = FALSE, ...)
```

Arguments

num_doses Number of doses under investigation.

allow_deescalate
 TRUE to allow de-escalation, as described by Korn et al. Default is FALSE.

... Extra args are not currently used.

Value

an object of type `selector_factory` that can fit the 3+3 model to outcomes.

References

Storer BE. Design and Analysis of Phase I Clinical Trials. *Biometrics*. 1989;45(3):925-937. doi:10.2307/2531693

Korn EL, Midthune D, Chen TT, Rubinstein LV, Christian MC, Simon RM. A comparison of two phase I trial designs. *Statistics in Medicine*. 1994;13(18):1799-1806. doi:10.1002/sim.4780131802

Examples

```
model <- get_three_plus_three(num_doses = 5)

fit1 <- model %>% fit('1NNN 2NTN')
fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 <- model %>% fit('1NNN 2NTN 2NNT')
fit2 %>% recommended_dose()
fit2 %>% continue()
```

`get_tpi`*Get an object to fit the TPI dose-finding model.*

Description

The toxicity probability interval (TPI) is a dose-escalation design by Ji et al.

Usage

```
get_tpi(  
  num_doses,  
  target,  
  k1,  
  k2,  
  exclusion_certainty,  
  alpha = 0.005,  
  beta = 0.005,  
  ...  
)
```

Arguments

num_doses	Number of doses under investigation.
target	We seek a dose with this probability of toxicity.
k1	The K1 parameter in TPI determines the upper bound of the equivalence interval. See Details.
k2	The K2 parameter in TPI determines the lower bound of the equivalence interval. See Details.
exclusion_certainty	Numeric, threshold posterior certainty required to exclude a dose for being excessively toxic. The authors discuss values in the range 0.7 - 0.95. Set to a value > 1 to suppress the dose exclusion mechanism. The authors use the Greek letter xi for this parameter.
alpha	First shape parameter of the beta prior distribution on the probability of toxicity.
beta	Second shape parameter of the beta prior distribution on the probability of toxicity.
...	Extra args are passed onwards.

Value

an object of type `selector_factory` that can fit the TPI model to outcomes.

Details

The design seeks a dose with probability of toxicity p_i close to a target probability p_T by iteratively calculating the interval

$$p_T - K_2\sigma_i < p_i < p_T + K_1\sigma_i$$

In this model, K_1 and K_2 are specified constants and σ_i is the standard deviation of p_i arising from a Bayesian beta-binomial conjugate model

$$p_i|data \sim Beta(\alpha + x_i, \beta + n_i - x_i),$$

where x_i is the number of toxicities observed and n_i is the number of patients treated at dose i , and α and β are hyperparameters for the beta prior on p_i . A dose is excluded as inadmissible if

$$P(p_i > p_T|data) > \xi$$

The trial commences at a starting dose, possibly dose 1. If dose i has just been evaluated in patient(s), dose selection decisions proceed by calculating the posterior probability that the true toxicity rate at dose i belongs to the three partition regions $p_i < p_T - K_2\sigma_i$, $p_T - K_2\sigma_i < p_i < p_T + K_1\sigma_i$, and $p_i > p_T + K_2\sigma_i$, corresponding to decisions escalate, stay, and de-escalate dose, respectively. Further to this are rules that prevent escalation to an inadmissible dose. In their paper, the authors demonstrate acceptable operating performance using $\alpha = \beta = 0.005$, $K_1 = 1$, $K_2 = 1.5$ and $\xi = 0.95$. See the publications for full details.

References

- Ji, Y., Li, Y., & Bekele, B. N. (2007). Dose-finding in phase I clinical trials based on toxicity probability intervals. *Clinical Trials*, 4(3), 235–244. <https://doi.org/10.1177/1740774507079442>
- Ji, Y., & Yang, S. (2017). On the Interval-Based Dose-Finding Designs, 1–26. Retrieved from <https://arxiv.org/abs/1706.03277>

Examples

```
target <- 0.25
model1 <- get_tpi(num_doses = 5, target = target, k1 = 1, k2 = 1.5,
  exclusion_certainty = 0.95)

outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()
```

get_trialr_crm

Get an object to fit the CRM model using the trialr package.

Description

This function returns an object that can be used to fit a CRM model using methods provided by the trialr package.

Dose selectors are designed to be daisy-chained together to achieve different behaviours. This class is a **resumptive** selector, meaning it carries on when the previous dose selector, where present, has elected not to continue. For example, this allows instances of this class to be preceded by a selector that follows a fixed path in an initial escalation plan, such as that provided by [follow_path](#). In this example, when the observed trial outcomes deviate from that initial plan, the selector following the fixed path elects not to continue and responsibility passes to this class. See Examples.

Usage

```
get_trialr_crm(parent_selector_factory = NULL, skeleton, target, model, ...)
```

Arguments

parent_selector_factory	optional object of type selector_factory that is in charge of dose selection before this class gets involved. Leave as NULL to just use CRM from the start.
skeleton	Dose-toxicity skeleton, a non-decreasing vector of probabilities.
target	We seek a dose with this probability of toxicity.
model	character string identifying which model form to use. Options include empiric, logistic, logistic2. The model form chosen determines which prior hyperparameters are required. See stan_crm for more details.
...	Extra args are passed to stan_crm .

Value

an object of type [selector_factory](#) that can fit the CRM model to outcomes.

References

Kristian Brock (2020). trialr: Clinical Trial Designs in 'rstan'. R package version 0.1.5. <https://github.com/brockk/trialr>

Kristian Brock (2019). trialr: Bayesian Clinical Trial Designs in R and Stan. arXiv preprint arXiv:1907.00161.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
# The model to use must be specified in trialr:
model1 <- get_trialr_crm(skeleton = skeleton, target = target,
                        model = 'empiric', beta_sd = 1.34)
# Refer to the trialr documentation for more details on model forms.
outcomes <- '1NNN 2NTN'
model1 %>% fit(outcomes) %>% recommended_dose()

# But we can provide extra args to trialr that are then passed onwards to
# the call to trialr::stan_crm to override the defaults.
# For example, if we want the one-parameter logistic model, we run:
model2 <- get_trialr_crm(skeleton = skeleton, target = target,
                        model = 'logistic', a0 = 3,
                        beta_mean = 0, beta_sd = 1)
model2 %>% fit(outcomes) %>% recommended_dose()
# And, if we want the two-parameter logistic model, we run:
model3 <- get_trialr_crm(skeleton = skeleton, target = target,
                        model = 'logistic2',
                        alpha_mean = 0, alpha_sd = 2,
                        beta_mean = 0, beta_sd = 1)
model3 %>% fit(outcomes) %>% recommended_dose()

# We can use an initial dose-escalation plan, a pre-specified path that
# should be followed until trial outcomes deviate, at which point the CRM
# model takes over. For instance, if we want to use two patients at each of
# the first three doses in the absence of toxicity, irrespective of the model's
# advice, we would run:
model1 <- follow_path('1NN 2NN 3NN') %>%
  get_trialr_crm(skeleton = skeleton, target = target, model = 'empiric',
                beta_sd = 1.34)

# If outcomes match the desired path, the path is followed further:
model1 %>% fit('1NN 2N') %>% recommended_dose()

# But when the outcomes diverge:
model1 %>% fit('1NN 2T') %>% recommended_dose()

# Or the pre-specified path comes to an end:
model1 %>% fit('1NN 2NN 3NN') %>% recommended_dose()
# ...the CRM model takes over.
```

get_trialr_efftox *Get an object to fit the EffTox model using the trialr package.*

Description

This function returns an object that can be used to fit the EffTox model for phase I/II dose-finding using methods provided by the trialr package.

Usage

```
get_trialr_efftox(
  parent_selector_factory = NULL,
  real_doses,
  efficacy_hurdle,
  toxicity_hurdle,
  p_e,
  p_t,
  eff0,
  tox1,
  eff_star,
  tox_star,
  priors,
  ...
)
```

Arguments

parent_selector_factory	optional object of type selector_factory that is in charge of dose selection before this class gets involved. Leave as NULL to just use EffTox from the start.
real_doses	A vector of numbers, the doses under investigation. They should be ordered from lowest to highest and be in consistent units. E.g. to conduct a dose-finding trial of doses 10mg, 20mg and 50mg, use c(10, 20, 50).
efficacy_hurdle	Minimum acceptable efficacy probability. A number between 0 and 1.
toxicity_hurdle	Maximum acceptable toxicity probability. A number between 0 and 1.
p_e	Certainty required to infer a dose is acceptable with regards to being probably efficacious; a number between 0 and 1.
p_t	Certainty required to infer a dose is acceptable with regards to being probably tolerable; a number between 0 and 1.
eff0	Efficacy probability required when toxicity is impossible; a number between 0 and 1 (see Details).
tox1	Toxicity probability permitted when efficacy is guaranteed; a number between 0 and 1 (see Details).

eff_star	Efficacy probability of an equi-utility third point (see Details).
tox_star	Toxicity probability of an equi-utility third point (see Details).
priors	instance of class <code>trialr{efftox_priors}</code> , the hyperparameters for normal priors on the six model parameters.
...	Extra args are passed to <code>stan_efftox</code> .

Value

an object of type `selector_factory` that can fit the EffTox model to outcomes.

References

Thall, P., & Cook, J. (2004). Dose-Finding Based on Efficacy-Toxicity Trade-Offs. *Biometrics*, 60(3), 684-693. <https://doi.org/10.1111/j.0006-341X.2004.00218.x>

Thall, P., Herrick, R., Nguyen, H., Venier, J., & Norris, J. (2014). Effective sample size for computing prior hyperparameters in Bayesian phase I-II dose-finding. *Clinical Trials*, 11(6), 657-666. <https://doi.org/10.1177/1740774514547397>

Brock, K. (2020). `trialr`: Clinical Trial Designs in 'rstan'. R package version 0.1.5. <https://github.com/brockk/trialr>

Brock, K. (2019). `trialr`: Bayesian Clinical Trial Designs in R and Stan. arXiv preprint arXiv:1907.00161.

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
  beta_mean = 1.5482, beta_sd = 3.5018,
  gamma_mean = 0.7367, gamma_sd = 2.5423,
  zeta_mean = 3.4181, zeta_sd = 2.4406,
  eta_mean = 0, eta_sd = 0.2,
  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
  efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
  p_e = 0.1, p_t = 0.1,
  eff0 = 0.5, tox1 = 0.65,
  eff_star = 0.7, tox_star = 0.25,
  priors = p, iter = 1000, chains = 1, seed = 2020)
```

get_trialr_nbg	<i>Get an object to fit the NBG dose-finding model using the trialr package.</i>
----------------	--

Description

This function returns an object that can be used to fit a Neuenschwander, Branson and Gsponer (NBG) model for dose-finding using methods provided by the `trialr` package.

Usage

```

get_trialr_nbg(
  parent_selector_factory = NULL,
  real_doses,
  d_star,
  target,
  alpha_mean,
  alpha_sd,
  beta_mean,
  beta_sd,
  ...
)

```

Arguments

parent_selector_factory	optional object of type selector_factory that is in charge of dose selection before this class gets involved. Leave as NULL to just use this model from the start.
real_doses	Doses under investigation, a non-decreasing vector of numbers.
d_star	Numeric, reference dose for calculating the covariate $\log(\text{dose} / d_star)$ when fitting the model. Sometimes (but not always) taken to be the max dose in real_doses.
target	We seek a dose with this probability of toxicity.
alpha_mean	Prior mean of intercept variable for normal prior. See Details. Also see documentation for trialr package for further details.
alpha_sd	Prior standard deviation of intercept variable for normal prior. See Details. Also see documentation for trialr package for further details.
beta_mean	Prior mean of gradient variable for normal prior. See Details. Also see documentation for trialr package for further details.
beta_sd	Prior standard deviation of slope variable for normal prior. See Details. Also see documentation for trialr package for further details.
...	Extra args are passed to stan_nbg .

Details

The model form implemented in trialr is:

$$F(x_i, \alpha, \beta) = 1 / (1 + \exp -(\alpha + \exp(\beta) \log(x_i / d_*)))$$

with normal priors on alpha and beta.

Dose selectors are designed to be daisy-chained together to achieve different behaviours. This class is a **resumptive** selector, meaning it carries on when the previous dose selector, where present, has elected not to continue. For example, this allows instances of this class to be preceded by a selector that follows a fixed path in an initial escalation plan, such as that provided by [follow_path](#). In this example, when the observed trial outcomes deviate from that initial plan, the selector following the fixed path elects not to continue and responsibility passes to this class. See examples under [get_dfcrm](#).

Value

an object of type `selector_factory` that can fit the NBG model to outcomes.

References

- Neuenschwander, B., Branson, M., & Gsponer, T. (2008). Critical aspects of the Bayesian approach to phase I cancer trials. *Statistics in Medicine*, 27, 2420–2439. <https://doi.org/10.1002/sim.3230>
- Brock, K. (2020). `trialr`: Clinical Trial Designs in 'rstan'. R package version 0.1.5. <https://github.com/brockk/trialr>
- Brock, K. (2019). `trialr`: Bayesian Clinical Trial Designs in R and Stan. arXiv preprint arXiv:1907.00161.

Examples

```
real_doses <- c(5, 10, 25, 40, 60)
d_star <- 60
target <- 0.25

model <- get_trialr_nbg(real_doses = real_doses, d_star = d_star,
                       target = target,
                       alpha_mean = 2, alpha_sd = 1,
                       beta_mean = 0.5, beta_sd = 1)
# Refer to the trialr documentation for more details on model & priors.
outcomes <- '1NNN 2NTN'
fit <- model %>% fit(outcomes)
fit %>% recommended_dose()
fit %>% mean_prob_tox()
```

`get_wages_and_tait` *Get an object to fit Wages & Tait's model for phase I/II dose-finding.*

Description

This function returns an object that can be used to fit Wages & Tait's model for phase I/II dose-finding, i.e. it selects doses according to efficacy and toxicity outcomes. This function delegates prior-to-posterior calculations to the `dferm` package.

Usage

```
get_wages_and_tait(
  parent_selector_factory = NULL,
  tox_skeleton,
  eff_skeletons,
  eff_skeleton_weights = rep(1, nrow(eff_skeletons)),
  tox_limit,
  eff_limit,
  num_randomise,
  ...
)
```

Arguments

<code>parent_selector_factory</code>	optional object of type <code>selector_factory</code> that is in charge of dose selection before this class gets involved. Leave NULL to just use this model from the start.
<code>tox_skeleton</code>	Dose-toxicity skeleton, a non-decreasing vector of probabilities.
<code>eff_skeletons</code>	Matrix of dose-efficacy skeletons, with the skeletons in rows. I.e. number of cols is equal to number of doses, and number of rows is equal to number of efficacy skeletons under consideration.
<code>eff_skeleton_weights</code>	numerical vector, prior weights to efficacy skeletons. Should have length equal to number of rows in <code>eff_skeletons</code> . Default is equal weights.
<code>tox_limit</code>	We seek a dose with probability of toxicity no greater than this. Value determines the admissible set. See Wages & Tait (2015).
<code>eff_limit</code>	We seek a dose with probability of efficacy no less than this.
<code>num_randomise</code>	integer, maximum number of patients to use in the adaptive randomisation phase of the trial.
<code>...</code>	Extra args are passed onwards.

Value

an object of type `selector_factory`.

References

Wages, N. A., & Tait, C. (2015). Seamless Phase I/II Adaptive Design for Oncology Trials of Molecularly Targeted Agents. *Journal of Biopharmaceutical Statistics*, 25(5), 903–920. <https://doi.org/10.1080/10543406.2015.10543406>

Examples

```
# Example in Wages & Tait (2015)
tox_skeleton = c(0.01, 0.08, 0.15, 0.22, 0.29, 0.36)
eff_skeletons = matrix(nrow=11, ncol=6)
eff_skeletons[1,] <- c(0.60, 0.50, 0.40, 0.30, 0.20, 0.10)
eff_skeletons[2,] <- c(0.50, 0.60, 0.50, 0.40, 0.30, 0.20)
eff_skeletons[3,] <- c(0.40, 0.50, 0.60, 0.50, 0.40, 0.30)
eff_skeletons[4,] <- c(0.30, 0.40, 0.50, 0.60, 0.50, 0.40)
eff_skeletons[5,] <- c(0.20, 0.30, 0.40, 0.50, 0.60, 0.50)
eff_skeletons[6,] <- c(0.10, 0.20, 0.30, 0.40, 0.50, 0.60)
eff_skeletons[7,] <- c(0.20, 0.30, 0.40, 0.50, 0.60, 0.60)
eff_skeletons[8,] <- c(0.30, 0.40, 0.50, 0.60, 0.60, 0.60)
eff_skeletons[9,] <- c(0.40, 0.50, 0.60, 0.60, 0.60, 0.60)
eff_skeletons[10,] <- c(0.50, 0.60, 0.60, 0.60, 0.60, 0.60)
eff_skeletons[11,] <- c(rep(0.60, 6))
eff_skeleton_weights = rep(1, nrow(eff_skeletons))
tox_limit = 0.33
eff_limit = 0.05
model <- get_wages_and_tait(tox_skeleton = tox_skeleton,
```

```

                                eff_skeletons = eff_skeletons,
                                tox_limit = tox_limit, eff_limit = eff_limit,
                                num_randomise = 20)
fit <- model %>% fit('1NN 2EN 3BE')
fit %>% recommended_dose()
fit %>% is_randomising()
fit %>% dose_admissible()
fit %>% prob_administer()

```

graph_paths

Visualise dose-paths as a graph

Description

Visualise dose-paths as a graph

Usage

```
graph_paths(paths, viridis_palette = "viridis", RColorBrewer_palette = NULL)
```

Arguments

paths Object of type [dose_paths](#)

viridis_palette optional name of a colour palette in the viridis package.

RColorBrewer_palette optional name of a colour palette in the RColorBrewer package.

Details

The viridis package supports palettes: viridis, magma, plasma, inferno, and cividis. The RColorBrewer package supports many palettes. Refer to those packages on CRAN for more details.

Examples

```

paths <- get_three_plus_three(num_doses = 5) %>%
  get_dose_paths(cohort_sizes = c(3, 3, 3))
## Not run:
graph_paths(paths)
graph_paths(paths, viridis_palette = 'plasma')
graph_paths(paths, RColorBrewer_palette = 'YlOrRd')

## End(Not run)

```

is_randomising	<i>Is this selector currently randomly allocating doses?</i>
----------------	--

Description

Get the percentage of patients evaluated at each dose under investigation.

Usage

```
is_randomising(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

a logical value

Examples

```
outcomes <- '1NNN 2NTN'
fit <- get_random_selector(prob_select = c(0.1, 0.6, 0.3)) %>%
  fit(outcomes)
fit %>% is_randomising()
```

mean_prob_eff	<i>Mean efficacy rate at each dose.</i>
---------------	---

Description

Get the estimated mean efficacy rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate efficacy probabilities in different ways. If no model-based estimate of the mean is available, this function will return a vector of NAs.

Usage

```
mean_prob_eff(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

a numerical vector

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
                  beta_mean = 1.5482, beta_sd = 3.5018,
                  gamma_mean = 0.7367, gamma_sd = 2.5423,
                  zeta_mean = 3.4181, zeta_sd = 2.4406,
                  eta_mean = 0, eta_sd = 0.2,
                  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
                           efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
                           p_e = 0.1, p_t = 0.1,
                           eff0 = 0.5, tox1 = 0.65,
                           eff_star = 0.7, tox_star = 0.25,
                           priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
mean_prob_eff(x)
```

mean_prob_tox	<i>Mean toxicity rate at each dose.</i>
---------------	---

Description

Get the estimated mean toxicity rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate toxicity probabilities in different ways. If no model-based estimate of the mean is available, this function will return a vector of NAs.

Usage

```
mean_prob_tox(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

a numerical vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% mean_prob_tox()
```

median_prob_eff	<i>Median efficacy rate at each dose.</i>
-----------------	---

Description

Get the estimated median efficacy rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate efficacy probabilities in different ways. If no model-based estimate of the median is available, this function will return a vector of NAs.

Usage

```
median_prob_eff(x, ...)
```

Arguments

x	Object of class selector
...	arguments passed to other methods

Value

a numerical vector

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
                 beta_mean = 1.5482, beta_sd = 3.5018,
                 gamma_mean = 0.7367, gamma_sd = 2.5423,
                 zeta_mean = 3.4181, zeta_sd = 2.4406,
                 eta_mean = 0, eta_sd = 0.2,
                 psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
                         efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
                         p_e = 0.1, p_t = 0.1,
                         eff0 = 0.5, tox1 = 0.65,
                         eff_star = 0.7, tox_star = 0.25,
                         priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
median_prob_eff(x)
```

median_prob_tox	<i>Median toxicity rate at each dose.</i>
-----------------	---

Description

Get the estimated median toxicity rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate toxicity probabilities in different ways. If no model-based estimate of the median is available, this function will return a vector of NAs.

Usage

```
median_prob_tox(x, ...)
```

Arguments

x	Object of class selector
...	arguments passed to other methods

Value

a numerical vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% median_prob_tox()
```

model_frame	<i>Model data-frame.</i>
-------------	--------------------------

Description

Get the model data-frame for a dose-finding analysis, including columns for patient id, cohort id, dose administered, and toxicity outcome. In some scenarios, further columns are provided.

Usage

```
model_frame(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

`tibble`, which acts like a `data.frame`.

Examples

```
# In a toxicity-only setting:
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% model_frame()

# In an efficacy-toxicity setting
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select,
                             supports_efficacy = TRUE)
x <- model %>% fit('1NTN 2EN 5BB', supports_efficacy = TRUE)
fit %>% model_frame()
```

num_cohort_outcomes *Number of different possible outcomes for a cohort of patients*

Description

Number of different possible outcomes for a cohort of patients, each of which will experience one of a number of discrete outcomes. For instance, in a typical phase I dose-finding trial, each patient will experience: no-toxicity (N); or toxicity (T). The number of possible outcomes per patient is two. For a cohort of three patients, the number of cohort outcomes is four: NNN, NNT, NTT, TTT. Consider a more complex example: in a seamless phase I/II trial with efficacy and toxicity outcomes, an individual patient will experience one of four distinct outcomes: efficacy only (E); toxicity only (T); both efficacy and toxicity (B) or neither. How many different outcomes are there for a cohort of three patients? The answer is 20 but it is non-trivial to see why. This convenience function calculates that number using the formula for the number of combinations with replacement,

Usage

```
num_cohort_outcomes(num_patient_outcomes, cohort_size)
```

Arguments

```
num_patient_outcomes
  integer, number of distinct possible outcomes for each single patient
cohort_size
  integer, number of patients in the cohort
```

Value

integer, number of distinct possible cohort outcomes

Examples

```
# As described in example, N or T in a cohort of three:
num_cohort_outcomes(num_patient_outcomes = 2, cohort_size = 3)
# Also described in example, E, T, B or N in a cohort of three:
num_cohort_outcomes(num_patient_outcomes = 4, cohort_size = 3)
```

num_doses	<i>Number of doses.</i>
-----------	-------------------------

Description

Get the number of doses under investigation in a dose-finding trial.

Usage

```
num_doses(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

integer

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% num_doses()
```

num_dose_path_nodes	<i>Number of nodes in dose-paths analysis</i>
---------------------	---

Description

Number of possible nodes in an exhaustive analysis of dose-paths in a dose-finding trial. The number of nodes at depth i is the the number of nodes at depth $i-1$ multiplied by the number of possible cohort outcomes at depth i . For instance, if there were 16 nodes at the previous depth and four possible cohort outcomes at the current depth, then there are 64 possible nodes at the current depth. Knowing the number of nodes in a dose-paths analysis helps the analyst decide whether simulation or dose-paths are a better tool for assessing operating characteristics of a dose-finding design.

Usage

```
num_dose_path_nodes(num_patient_outcomes, cohort_sizes)
```

Arguments

```
num_patient_outcomes    integer, number of distinct possible outcomes for each single patient
cohort_sizes            integer vector of cohort sizes
```

Value

integer vector, number of nodes at increasing depths. The total number of nodes is the sum of this vector.

Examples

```
# In a 3+3 design, there are two possible outcomes for each patient and
# patients are evaluated in cohorts of three. In an analysis of dose-paths in
# the first two cohorts of three, how many nodes are there?
num_dose_path_nodes(num_patient_outcomes = 2, cohort_sizes = rep(3, 2))
# In contrast, using an EffTox design there are four possible outcomes for
# each patient. In a similar analysis of dose-paths in the first two cohorts
# of three, how many nodes are there now?
num_dose_path_nodes(num_patient_outcomes = 4, cohort_sizes = rep(3, 2))
```

num_eff	<i>Total number of efficacies seen.</i>
---------	---

Description

Get the number of efficacies seen in a dose-finding trial.

Usage

```
num_eff(x, ...)
```

Arguments

```
x                Object of type selector.
...              Extra args are passed onwards.
```

Value

integer

Examples

```
prob_select = c(0.1, 0.3, 0.5, 0.07, 0.03)
model <- get_random_selector(prob_select = prob_select,
                             supports_efficacy = TRUE)
x <- model %>% fit('1NTN 2EN 5BB')
num_eff(x)
```

num_patients	<i>Number of patients evaluated.</i>
--------------	--------------------------------------

Description

Get the number of patients evaluated in a dose-finding trial.

Usage

```
num_patients(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

integer

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% num_patients()
```

num_tox	<i>Total number of toxicities seen.</i>
---------	---

Description

Get the number of toxicities seen in a dose-finding trial.

Usage

```
num_tox(x, ...)
```

Arguments

x Object of type [selector](#).
... Extra args are passed onwards.

Value

integer

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% num_tox()
```

n_at_dose	<i>Number of patients treated at each dose.</i>
-----------	---

Description

Get the number of patients evaluated at each dose under investigation.

Usage

```
n_at_dose(x, ...)
```

Arguments

x Object of class [selector](#)
... arguments passed to other methods

Value

an integer vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% n_at_dose()
```

n_at_recommended_dose *Number of patients treated at the recommended dose.*

Description

Get the number of patients evaluated at the recommended dose.

Usage

```
n_at_recommended_dose(x, ...)
```

Arguments

x Object of class `selector`
 ... arguments passed to other methods

Value

an integer

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% n_at_recommended_dose()
```

parse_phase1_2_outcomes

Parse a string of phase I/II dose-finding outcomes to vector notation.

Description

Parse a string of phase I/II dose-finding outcomes to a binary vector notation necessary for model invocation.

The outcome string describes the doses given, outcomes observed and groups patients into cohorts. The format of the string is described in Brock et al. (2017). See Examples.

The letters E, T, N and B are used to represent patients that experienced (E)fficacy only, (T)oxicity only, (B)oth efficacy and toxicity, and (N)either. These letters are concatenated after numerical dose-levels to convey the outcomes of cohorts of patients. For instance, 2ETB represents a cohort of three patients that were treated at dose-level 2, and experienced efficacy, toxicity and both events, respectively. The results of cohorts are separated by spaces. Thus, 2ETB 1NN extends our previous example, where the next cohort of two were treated at dose-level 1 and both patients experienced neither efficacy nor toxicity. See Examples.

Usage

```
parse_phase1_2_outcomes(outcomes, as_list = TRUE)
```

Arguments

`outcomes` character string, conveying doses given and outcomes observed.
`as_list` TRUE (the default) to return a list; FALSE to return a data.frame

Value

If `as_list == TRUE`, a list with elements `eff`, `tox`, `dose` and `num_patients`. If `as_list == FALSE`, a data.frame with columns `eff`, `tox` and `dose`.

References

Brock, K., Billingham, L., Copland, M., Siddique, S., Sirovica, M., & Yap, C. (2017). Implementing the EffTox dose-finding design in the Matchpoint trial. *BMC Medical Research Methodology*, 17(1), 112. <https://doi.org/10.1186/s12874-017-0381-x>

Examples

```
x = parse_phase1_2_outcomes('1NNE 2EEN 3TBB')
# Three cohorts of three patients. The first cohort was treated at dose 1 and
# had no toxicity with one efficacy, etc.
x$num_patients # 9
x$dose         # c(1, 1, 1, 2, 2, 2, 3, 3, 3)
x$eff          # c(0, 0, 1, 1, 1, 0, 0, 1, 1)
sum(x$eff)     # 5
x$tox          # c(0, 0, 0, 0, 0, 0, 1, 1, 1)
sum(x$tox)     # 3

# The same information can be parsed to a data-frame:
y = parse_phase1_2_outcomes('1NNE 2EEN 3TBB', as_list = FALSE)
y
```

`parse_phase1_outcomes` *Parse a string of phase I dose-finding outcomes to vector notation.*

Description

Parse a string of phase I dose-finding outcomes to a binary vector notation necessary for model invocation.

The outcome string describes the doses given, outcomes observed and groups patients into cohorts. The format of the string is described in Brock (2019), and that itself is the phase I analogue of the similar idea described in Brock et al. (2017). See Examples.

The letters T and N are used to represent patients that experienced (T)oxicity and (N)o toxicity. These letters are concatenated after numerical dose-levels to convey the outcomes of cohorts of

patients. For instance, 2NNT represents a cohort of three patients that were treated at dose-level 2, one of whom experienced toxicity, and two that did not. The results of cohorts are separated by spaces. Thus, 2NNT 1NN extends our previous example, where the next cohort of two were treated at dose-level 1 and neither experienced toxicity. See examples.

Usage

```
parse_phase1_outcomes(outcomes, as_list = TRUE)
```

Arguments

outcomes	character string, conveying doses given and outcomes observed.
as_list	TRUE (the default) to return a list; FALSE to return a data.frame

Value

If `as_list == TRUE`, a list with elements `tox`, `doses` and `num_patients`. If `as_list == FALSE`, a `data.frame` with columns `tox` and `doses`.

References

Brock, K. (2019). *trialr: Bayesian Clinical Trial Designs in R and Stan*. arXiv:1907.00161 [stat.CO]

Brock, K., Billingham, L., Copland, M., Siddique, S., Sirovica, M., & Yap, C. (2017). Implementing the EffTox dose-finding design in the Matchpoint trial. *BMC Medical Research Methodology*, 17(1), 112. <https://doi.org/10.1186/s12874-017-0381-x>

Examples

```
x = parse_phase1_outcomes('1NNN 2NTN 3TTT')
# Three cohorts of three patients. The first cohort was treated at dose 1 and
# none had toxicity. The second cohort was treated at dose 2 and one of the
# three had toxicity. Finally, cohort three was treated at dose 3 and all
# patients had toxicity.
x$num_patients # 9
x$doses        # c(1, 1, 1, 2, 2, 2, 3, 3, 3)
x$tox          # c(0, 0, 0, 0, 1, 0, 1, 1, 1)
sum(x$tox)     # 4

# The same information can be parsed to a data-frame:
y = parse_phase1_outcomes('1NNN 2NTN 3TTT', as_list = FALSE)
y
```

phase1_2_outcomes_to_cohorts

Break a phase I/II outcome string into a list of cohort parts.

Description

Break a phase I/II outcome string into a list of cohort parts.

Break a phase I/II outcome string into a list of cohort parts.

The outcome string describes the doses given, outcomes observed and the timing of analyses that recommend a dose. The format of the string is described in Brock *et al.* (2017).

The letters E, T, N & B are used to represent patients that experienced (E)fficacy, (T)oxicity, (N)either and (B)oth. These letters are concatenated after numerical dose-levels to convey the outcomes of cohorts of patients. For instance, 2NET represents a cohort of three patients that were treated at dose-level 2, one of whom experienced toxicity only, one that experienced efficacy only, and one that had neither. The results of cohorts are separated by spaces and it is assumed that a dose-finding decision takes place at the end of a cohort. Thus, 2NET 1NN builds on our previous example, where the next cohort of two were treated at dose-level 1 and neither of these patients experienced either event. See examples.

Usage

```
phase1_2_outcomes_to_cohorts(outcomes)
```

Arguments

outcomes	character string representing the doses given, outcomes observed, and timing of analyses. See Description.
----------	--

Value

a list with a slot for each cohort. Each cohort slot is itself a list, containing elements: * dose, the integer dose delivered to the cohort; * outcomes, a character string representing the E, T N or B outcomes for the patients in this cohort.

References

Brock, K., Billingham, L., Copland, M., Siddique, S., Sirovica, M., & Yap, C. (2017). Implementing the EffTox dose-finding design in the Matchpoint trial. *BMC Medical Research Methodology*, 17(1), 112. <https://doi.org/10.1186/s12874-017-0381-x>

Examples

```
x = phase1_2_outcomes_to_cohorts('1NEN 2ENT 3TB')
length(x)
x[[1]]$dose
x[[1]]$outcomes
x[[2]]$dose
```

```
x[[2]]$outcomes
x[[3]]$dose
x[[3]]$outcomes
```

```
phase1_outcomes_to_cohorts
```

Break a phase I outcome string into a list of cohort parts.

Description

Break a phase I outcome string into a list of cohort parts.

Break a phase I outcome string into a list of cohort parts.

The outcome string describes the doses given, outcomes observed and the timing of analyses that recommend a dose. The format of the string is described in Brock (2019), and that itself is the phase I analogue of the similar idea described in Brock *et al.* (2017).

The letters T and N are used to represent patients that experienced (T)oxicity and (N)o toxicity. These letters are concatenated after numerical dose-levels to convey the outcomes of cohorts of patients. For instance, 2NNT represents a cohort of three patients that were treated at dose-level 2, one of whom experienced toxicity, and two that did not. The results of cohorts are separated by spaces and it is assumed that a dose-finding decision takes place at the end of a cohort. Thus, 2NNT 1NN builds on our previous example, where the next cohort of two were treated at dose-level 1 and neither of these patients experienced toxicity. See examples.

Usage

```
phase1_outcomes_to_cohorts(outcomes)
```

Arguments

outcomes	character string representing the doses given, outcomes observed, and timing of analyses. See Description.
----------	--

Value

a list with a slot for each cohort. Each cohort slot is itself a list, containing elements: * dose, the integer dose delivered to the cohort; * outcomes, a character string representing the T or N outcomes for the patients in this cohort.

References

Brock, K. (2019). *trialr: Bayesian Clinical Trial Designs in R and Stan*. arXiv:1907.00161 [stat.CO]
 Brock, K., Billingham, L., Copland, M., Siddique, S., Sirovica, M., & Yap, C. (2017). Implementing the EffTox dose-finding design in the Matchpoint trial. *BMC Medical Research Methodology*, 17(1), 112. <https://doi.org/10.1186/s12874-017-0381-x>

Examples

```
x = phase1_outcomes_to_cohorts('1NNN 2NNT 3TT')
length(x)
x[[1]]$dose
x[[1]]$outcomes
x[[2]]$dose
x[[2]]$outcomes
x[[3]]$dose
x[[3]]$outcomes
```

prob_administer	<i>Percentage of patients treated at each dose.</i>
-----------------	---

Description

Get the percentage of patients evaluated at each dose under investigation.

Usage

```
prob_administer(x, ...)
```

Arguments

x	Object of class <code>selector</code>
...	arguments passed to other methods

Value

a numerical vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% prob_administer()
```

prob_eff_quantile	<i>Quantile of the efficacy rate at each dose.</i>
-------------------	--

Description

Get the estimated quantile of the efficacy rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate efficacy probabilities in different ways. If no model-based estimate of the median is available, this function will return a vector of NAs.

Usage

```
prob_eff_quantile(x, p, ...)
```

Arguments

x	Object of class selector
p	quantile probability, decimal value between 0 and 1
...	arguments passed to other methods

Value

a numerical vector

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
                  beta_mean = 1.5482, beta_sd = 3.5018,
                  gamma_mean = 0.7367, gamma_sd = 2.5423,
                  zeta_mean = 3.4181, zeta_sd = 2.4406,
                  eta_mean = 0, eta_sd = 0.2,
                  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
                          efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
                          p_e = 0.1, p_t = 0.1,
                          eff0 = 0.5, tox1 = 0.65,
                          eff_star = 0.7, tox_star = 0.25,
                          priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
prob_tox_quantile(x, p = 0.9)
```

prob_recommend *Probability of recommendation*

Description

Get the probabilities that each of the doses under investigation is recommended.

Usage

```
prob_recommend(x, ...)
```

Arguments

x Object of type [simulations](#).
 ... arguments passed to other methods

Value

vector of probabilities

Examples

```
true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)
sims <- get_three_plus_three(num_doses = 5) %>%
  simulate_trials(num_sims = 50, true_prob_tox = true_prob_tox)
sims %>% prob_recommend
```

prob_tox_exceeds *Probability that the toxicity rate exceeds some threshold.*

Description

Get the probability that the toxicity rate at each dose exceeds some threshold.

Get the probability that the efficacy rate at each dose exceeds some threshold.

Usage

```
prob_tox_exceeds(x, threshold, ...)
```

```
prob_eff_exceeds(x, threshold, ...)
```

Arguments

x Object of type [selector](#)
 threshold Probability that efficacy rate exceeds what?
 ... arguments passed to other methods

Value

numerical vector of probabilities
numerical vector of probabilities

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
# What is probability that tox rate at each dose exceeds target by >= 10%?
fit %>% prob_tox_exceeds(threshold = target + 0.1)
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
                  beta_mean = 1.5482, beta_sd = 3.5018,
                  gamma_mean = 0.7367, gamma_sd = 2.5423,
                  zeta_mean = 3.4181, zeta_sd = 2.4406,
                  eta_mean = 0, eta_sd = 0.2,
                  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
                          efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
                          p_e = 0.1, p_t = 0.1,
                          eff0 = 0.5, tox1 = 0.65,
                          eff_star = 0.7, tox_star = 0.25,
                          priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
prob_tox_exceeds(x, threshold = 0.45)
```

prob_tox_quantile	<i>Quantile of the toxicity rate at each dose.</i>
-------------------	--

Description

Get the estimated quantile of the toxicity rate at each dose under investigation. This is a set of modelled statistics. The underlying models estimate toxicity probabilities in different ways. If no model-based estimate of the median is available, this function will return a vector of NAs.

Usage

```
prob_tox_quantile(x, p, ...)
```

Arguments

x	Object of class <code>selector</code>
p	quantile probability, decimal value between 0 and 1
...	arguments passed to other methods

Value

a numerical vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% prob_tox_quantile(p = 0.9)
```

prob_tox_samples	<i>Get samples of the probability of toxicity.</i>
------------------	--

Description

Get samples of the probability of toxicity. For instance, a Bayesian approach that supports sampling would be expected to return posterior samples of the probability of toxicity. If this class does not support sampling, this function will raise an error. You can check whether this class supports sampling by calling [supports_sampling](#).

Get samples of the probability of efficacy For instance, a Bayesian approach that supports sampling would be expected to return posterior samples of the probability of toxicity. If this class does not support sampling, this function will raise an error. You can check whether this class supports sampling by calling [supports_sampling](#).

Usage

```
prob_tox_samples(x, tall = FALSE, ...)
```

```
prob_eff_samples(x, tall = FALSE, ...)
```

Arguments

x	Object of type selector
tall	logical, if FALSE, a wide data-frame is returned with columns pertaining to the doses and column names the dose indices. If TRUE, a tall data-frame is returned with data for all doses stacked vertically. In this mode, column names will include dose and prob_eff.
...	arguments passed to other methods

Value

data-frame like object

data-frame like object

Examples

```

# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% prob_tox_samples()
fit %>% prob_tox_samples(tall = TRUE)
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
                  beta_mean = 1.5482, beta_sd = 3.5018,
                  gamma_mean = 0.7367, gamma_sd = 2.5423,
                  zeta_mean = 3.4181, zeta_sd = 2.4406,
                  eta_mean = 0, eta_sd = 0.2,
                  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
                          efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
                          p_e = 0.1, p_t = 0.1,
                          eff0 = 0.5, tox1 = 0.65,
                          eff_star = 0.7, tox_star = 0.25,
                          priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
prob_tox_samples(x, tall = TRUE)

```

recommended_dose	<i>Recommended dose for next patient or cohort.</i>
------------------	---

Description

Get the dose recommended for the next patient or cohort in a dose-finding trial.

Usage

```
recommended_dose(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

integer

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% recommended_dose()
```

selector

Dose selector.

Description

This is a core class in this package. It encapsulates that an object (e.g. a CRM model, a 3+3 model) is able to recommend doses, keep track of how many patients have been treated at what doses, what toxicity outcomes have been seen, and whether a trial should continue. It offers a consistent interface to many dose-finding methods, including CRM, TPI, mTPI, BOIN, EffTox, 3+3, and more.

Once you have a standardised interface, modularisation offers a powerful way to adorn dose-finding methods with extra desirable behaviour. `selector` objects can be daisy-chained together using `magrittr`'s pipe operator. For instance, the CRM fitting method in `dfcrm` is fantastic because it runs quickly and is simple to call. However, it does not recommend that a trial stops if a dose is too toxic or if `n` patients have already been treated at the recommended dose. Each of these behaviours can be bolted on via additional selectors. Furthermore, those behaviours and more can be bolted on to any dose selector because of the modular approach implemented in `escalation`. See Examples.

`selector` objects are obtained by calling the `fit` function on a `selector_factory` object. A `selector_factory` object is obtained by initially calling a function like `get_dfcrm`, `get_three_plus_three` or `get_boin`. Users may then add desired extra behaviour with subsequent calls to functions like `stop_when_n_at_dose` or `stop_when_too_toxic`.

The `selector` class also supports that an object will be able to perform inferential calculations on the rates of toxicity via functions like `mean_prob_tox`, `median_prob_tox`, and `prob_tox_exceeds`. However, naturally the sophistication of those calculations will vary by model implementation. For example, a full MCMC method will be able to quantify any probability you like by working with posterior samples. In contrast, a method like the `crm` function in `dfcrm` that uses the plug-in method to estimate posterior dose-toxicity curves cannot natively estimate the median probability of tox.

Usage

```
selector()
```

Details

Every `selector` object implements the following functions:

- `tox_target`
- `num_patients`
- `cohort`
- `doses_given`

- `tox`
- `num_tox`
- `model_frame`
- `num_doses`
- `dose_indices`
- `recommended_dose`
- `continue`
- `n_at_dose`
- `n_at_recommended_dose`
- `is_randomising`
- `prob_administer`
- `tox_at_dose`
- `empiric_tox_rate`
- `mean_prob_tox`
- `median_prob_tox`
- `dose_admissible`
- `prob_tox_quantile`
- `prob_tox_exceeds`
- `supports_sampling`
- `prob_tox_samples`

Some selectors also add:

- `tox_limit`
- `eff_limit`
- `eff`
- `num_eff`
- `eff_at_dose`
- `empiric_eff_rate`
- `mean_prob_eff`
- `median_prob_eff`
- `prob_eff_quantile`
- `prob_eff_exceeds`
- `prob_eff_samples`

See Also

`selector_factory`

Examples

```

# Start with a simple CRM model
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model1 <- get_dfcrm(skeleton = skeleton, target = target)

# Add a rule to stop when 9 patients are treated at the recommended dose
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 9, dose = 'recommended')

# Add a rule to stop if toxicity rate at lowest dose likely exceeds target
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 9, dose = 'recommended') %>%
  stop_when_too_toxic(dose = 1, tox_threshold = target, confidence = 0.5)

# We now have three CRM models that differ in their stopping behaviour.
# Let's fit each to some outcomes to see those differences:

outcomes <- '1NNN 2NTT 1NNT'
fit1 <- model1 %>% fit(outcomes)
fit2 <- model2 %>% fit(outcomes)
fit3 <- model3 %>% fit(outcomes)

fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 %>% recommended_dose()
fit2 %>% continue()

fit3 %>% recommended_dose()
fit3 %>% continue()
# Already model3 wants to stop because of excessive toxicity.

# Let's carry on with models 1 and 2 by adding another cohort:

outcomes <- '1NNN 2NTT 1NNT 1NNN'
fit1 <- model1 %>% fit(outcomes)
fit2 <- model2 %>% fit(outcomes)

fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 %>% recommended_dose()
fit2 %>% continue()

# Model1 wants to continue - in fact it will never stop.
# In contrast, model2 has seen 9 at dose 1 so, rather than suggest dose 1
# again, it suggests the trial should stop.

# For contrast, let us consider a BOIN model on the same outcomes
boin_fitter <- get_boin(num_doses = length(skeleton), target = target)

```

```
fit4 <- boin_fitter %>% fit(outcomes)
fit4 %>% recommended_dose()
fit4 %>% continue()

# Full selector interface:
fit <- fit2
fit %>% tox_target()
fit %>% num_patients()
fit %>% cohort()
fit %>% doses_given()
fit %>% tox()
fit %>% num_tox()
fit %>% model_frame()
fit %>% num_doses()
fit %>% dose_indices()
fit %>% recommended_dose()
fit %>% continue()
fit %>% n_at_dose()
fit %>% n_at_recommended_dose()
fit %>% is_randomising()
fit %>% prob_administer()
fit %>% tox_at_dose()
fit %>% empiric_tox_rate()
fit %>% mean_prob_tox()
fit %>% median_prob_tox()
fit %>% dose_admissible()
fit %>% prob_tox_quantile(0.9)
fit %>% prob_tox_exceeds(0.5)
fit %>% supports_sampling()
fit %>% prob_tox_samples()
```

selector_factory *Dose selector factory.*

Description

Along with [selector](#), this is the second core class in the escalation package. It exists to do one thing: fit outcomes from dose-finding trials to the models we use to select doses.

A [selector_factory](#) object is obtained by initially calling a function like [get_dfcrm](#), [get_three_plus_three](#) or [get_boin](#). Users may then add desired extra behaviour with subsequent calls to functions like [stop_when_n_at_dose](#) or [stop_when_too_toxic](#). [selector](#) objects are obtained by calling the [fit](#) function on a [selector_factory](#) object. Refer to examples to see how this works.

Usage

```
selector_factory()
```

See Also

[selector](#)

Examples

```

# Start with a simple CRM model
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model1 <- get_dfcrm(skeleton = skeleton, target = target)

# Add a rule to stop when 9 patients are treated at the recommended dose
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 9, dose = 'recommended')

# Add a rule to stop if toxicity rate at lowest dose likely exceeds target
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 9, dose = 'recommended') %>%
  stop_when_too_toxic(dose = 1, tox_threshold = target, confidence = 0.5)

# We now have three CRM models that differ in their stopping behaviour.
# Let's fit each to some outcomes to see those differences:

outcomes <- '1NNN 2NTT 1NNT'
fit1 <- model1 %>% fit(outcomes)
fit2 <- model2 %>% fit(outcomes)
fit3 <- model3 %>% fit(outcomes)

fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 %>% recommended_dose()
fit2 %>% continue()

fit3 %>% recommended_dose()
fit3 %>% continue()
# Already model3 wants to stop because of excessive toxicity.

# Let's carry on with models 1 and 2 by adding another cohort:

outcomes <- '1NNN 2NTT 1NNT 1NNN'
fit1 <- model1 %>% fit(outcomes)
fit2 <- model2 %>% fit(outcomes)

fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 %>% recommended_dose()
fit2 %>% continue()

# Model1 wants to continue - in fact it will never stop.
# In contrast, model2 has seen 9 at dose 1 so, rather than suggest dose 1
# again, it suggests the trial should stop.

# For contrast, let us consider a BOIN model on the same outcomes
boin_fitter <- get_boin(num_doses = length(skeleton), target = target)

```



```
fit4 <- boin_fitter %>% fit(outcomes)
fit4 %>% recommended_dose()
fit4 %>% continue()
```

select_boin_mtd	<i>Select dose by BOIN's MTD-choosing algorithm.</i>
-----------------	--

Description

This method selects dose by the algorithm for identifying the maximum tolerable dose (MTD) described in Yan et al. (2019). This class is intended to be used when a BOIN trial has reached its maximum sample size. Thus, it intends to make the final dose recommendation after the regular BOIN dose selection algorithm, as implemented by `get_boin`, has gracefully concluded a dose-finding trial. However, the class can be used in any scenario where there is a target toxicity rate. See Examples. Note - this class will not override the parent dose selector when the parent is advocating no dose. Thus this class will not reinstate a dangerous dose.

Usage

```
select_boin_mtd(
  parent_selector_factory,
  when = c("finally", "always"),
  target = NULL,
  ...
)
```

Arguments

parent_selector_factory	Object of type selector_factory .
when	Either of: 'finally' to select dose only when the parent dose-selector has finished, by returning <code>continue() == FALSE</code> ; or 'always' to use this dose-selection algorithm for every dose decision. As per the authors' original intentions, the default is 'finally'.
target	We seek a dose with this probability of toxicity. If not provided, the value will be sought from the parent dose-selector.
...	Extra args are passed to select.mtd .

Value

an object of type [selector_factory](#).

References

Yan, F., Pan, H., Zhang, L., Liu, S., & Yuan, Y. (2019). BOIN: An R Package for Designing Single-Agent and Drug-Combination Dose-Finding Trials Using Bayesian Optimal Interval Designs. *Journal of Statistical Software*, 27(November 2017), 0–35. <https://doi.org/10.18637/jss.v000.i00>

Examples

```
# This class is intended to make the final dose selection in a BOIN trial:
target <- 0.25
model <- get_boin(num_doses = 5, target = target) %>%
  stop_at_n(n = 12) %>%
  select_boin_mtd()

outcomes <- '1NNN 2NTN 2NNN 3NTT'
model %>% fit(outcomes) %>% recommended_dose()

# However, we can use this method to select dose at every dose decision:
model2 <- get_boin(num_doses = 5, target = target) %>%
  select_boin_mtd(when = 'always')
model2 %>% fit('1NNT') %>% recommended_dose()
model2 %>% fit('1NNN 2NNT') %>% recommended_dose()

# and with any underlying model:
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  select_boin_mtd(when = 'always')
model3 %>% fit('1NNT') %>% recommended_dose()
model3 %>% fit('1NNN 2NNT') %>% recommended_dose()
```

select_dose_by_cibp *Select dose by the CIBP selection criterion.*

Description

This method selects dose by the convex infinite bounds penalisation (CIBP) criterion of Mozgunov & Jaki. Their method is mindful of the uncertainty in the estimates of the probability of toxicity and uses an asymmetry parameter to penalise escalation to risky doses.

Usage

```
select_dose_by_cibp(parent_selector_factory, a, target = NULL)
```

Arguments

parent_selector_factory	Object of type selector_factory .
a	Number between 0 and 2, the asymmetry parameter. See References.
target	We seek a dose with this probability of toxicity. If not provided, the value will be sought from the parent dose-selector.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

References

Mozgunov P, Jaki T. Improving safety of the continual reassessment method via a modified allocation rule. *Statistics in Medicine*.1-17. doi:10.1002/sim.8450

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.33

# Let's compare escalation behaviour of a CRM model without CIBP criterion:
model1 <- get_dfcrm(skeleton = skeleton, target = target)
# To one with the CIBP criterion:
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  select_dose_by_cibp(a = 0.3)

# Despite one-in-three tox at first dose, regular model is ready to escalate:
model1 %>% fit('1NTN') %>% recommended_dose()
# But the model using CIBP is more risk averse:
model2 %>% fit('1NTN') %>% recommended_dose()
```

simulate_trials *Simulate clinical trials.*

Description

This function takes a [selector_factory](#), such as that returned by [get_dfcrm](#), [get_boin](#) or [get_three_plus_three](#), and conducts many notional clinical trials. We conduct simulations to learn about the operating characteristics of adaptive trial designs.

Usage

```
simulate_trials(
  selector_factory,
  num_sims,
  true_prob_tox,
  true_prob_eff = NULL,
  ...
)
```

Arguments

selector_factory	Object of type selector_factory .
num_sims	integer, number of trial iterations to simulate.
true_prob_tox	numeric vector of true but unknown toxicity probabilities
true_prob_eff	numeric vector of true but unknown efficacy probabilities. NULL if efficacy not analysed.
...	Extra args are passed onwards.

Details

By default, dose decisions in simulated trials are made after each cohort of 3 patients. This can be changed by providing a function that simulates the arrival of new patients. The new patients will be added to the existing patients and the model will be fit to the set of all patients. The function that simulates patient arrivals should take as a single parameter a data-frame with one row for each existing patient and columns including cohort, patient, dose, tox, time (and possibly also eff and weight, if a phase I/II or time-to-event method is used). The provision of data on the existing patients allows the patient sampling function to be adaptive. The function should return a data-frame with a row for each new patient and a column for time_delta, the time between the arrival of this patient and the previous, as in `cohorts_of_n`. See Examples.

This method can simulate the culmination of trials that are partly completed. We just have to specify the outcomes already observed via the `previous_outcomes` parameter. Each simulated trial will commence from those outcomes seen thus far. See Examples.

We can specify the immediate next dose by specifying `next_dose`. If omitted, the next dose is calculated by invoking the model on the outcomes seen thus far.

Designs must eventually choose to stop the trial. However, some selectors like those derived from `get_dfcrm` offer no default stopping method. You may need to append stopping behaviour to your selector via something like `stop_at_n` or `stop_when_n_at_dose`, etc. To safeguard against simulating runaway trials that never end, the function will halt a simulated trial after 30 invocations of the dose-selection decision. To breach this limit, specify `i_like_big_trials = TRUE` in the function call. However, when you forego the safety net, the onus is on you to write selectors that will eventually stop the trial! See Examples.

The model is fit to the prevailing data at each dose selection point. By default, only the final model fit for each simulated trial is retained. This is done to conserve memory. With a high number of simulated trials, storing many model fits per trial may cause the executing machine to run out of memory. However, you can force this method to retain all model fits by specifying `return_all_fits = TRUE`. See Examples.

Value

Object of type `simulations`.

See Also

`simulations`
`selector_factory`
`get_dfcrm`
`get_boin`
`get_three_plus_three`
`cohorts_of_n`

Examples

```
true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)

# Regular usage examples, for 3+3:
```

```

sims <- get_three_plus_three(num_doses = 5) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox)
# and continual reassessment method:
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox)

# Lots of useful information is contained in the returned object:
sims %>% num_patients()
sims %>% num_doses()
sims %>% dose_indices()
sims %>% n_at_dose()
sims %>% n_at_recommended_dose()
sims %>% tox_at_dose()
sims %>% num_tox()
sims %>% recommended_dose()
sims %>% prob_administer()
sims %>% prob_recommend()
sims %>% trial_duration()

# By default, dose decisions are made after each cohort of 3 patients. See
# Details. To override, specify an alternative function via the
# sample_patient_arrivals parameter. E.g. to use cohorts of 2, we run:
patient_arrivals_func <- function(current_data) cohorts_of_n(n = 2)
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox,
    sample_patient_arrivals = patient_arrivals_func)

# To simulate the culmination of trials that are partly completed, specify
# the outcomes already observed via the previous_outcomes parameter:
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox,
    previous_outcomes = '1NTN')
# Outcomes can be described by above outcome string method or data-frame:
previous_outcomes <- data.frame(
  patient = 1:3,
  cohort = c(1, 1, 1),
  tox = c(0, 1, 0),
  dose = c(1, 1, 1)
)
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox,
    previous_outcomes = previous_outcomes)

# We can specify the immediate next dose:
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox,

```

```

        next_dose = 5)

# By default, the method will stop simulated trials after 30 dose selections.
# To suppress this, specify i_like_big_trials = TRUE. However, please take
# care to specify selectors that will eventually stop!
sims <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 99) %>%
  simulate_trials(num_sims = 1, true_prob_tox = true_prob_tox,
                 i_like_big_trials = TRUE)

# By default, only the final model fit is retained for each simulated trial.
# To retain all interim model fits, specify return_all_fits = TRUE.
sims <- get_three_plus_three(num_doses = 5) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox,
                 return_all_fits = TRUE)
# Verify that there are now many analyses per trial with:
sapply(sims$fits, length)

```

simulations

Simulated trials.

Description

This class encapsulates that many notional or virtual trials can be simulated. Each recommends a dose (or doses), keeps track of how many patients have been treated at what doses, what toxicity outcomes have been seen, and whether a trial advocates continuing, etc. We run simulations to learn about the operating characteristics of a trial design.

Computationally, the `simulations` class supports much of the same interface as `selector`, and a little more. Thus, many of the same generic functions are supported - see Examples. However, compared to `selectors`, the returned objects reflect that there are many trials instead of one, e.g. `num_patients(sims)`, returns as an integer vector the number of patients used in the simulated trials.

Usage

```
simulations(fits, true_prob_tox, true_prob_eff = NULL, ...)
```

Arguments

<code>fits</code>	Simulated model fits, arranged as list of lists.
<code>true_prob_tox</code>	vector of true toxicity probabilities
<code>true_prob_eff</code>	vector of true efficacy probabilities, optionally NULL if efficacy not analysed.
<code>...</code>	Extra args

Details

The simulations object implements the following functions:

- `num_patients`
- `num_doses`
- `dose_indices`
- `n_at_dose`
- `tox_at_dose`
- `num_tox`
- `recommended_dose`
- `prob_administer`
- `prob_recommend`
- `trial_duration`

Value

list with slots: `fits` containing model fits; and `true_prob_tox`, containing the assumed true probability of toxicity.

See Also

[selector](#)

[simulate_trials](#)

Examples

```
# Simulate performance of the 3+3 design:
true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)
sims <- get_three_plus_three(num_doses = 5) %>%
  simulate_trials(num_sims = 10, true_prob_tox = true_prob_tox)
# The returned object has type 'simulations'. The supported interface is:
sims %>% num_patients()
sims %>% num_doses()
sims %>% dose_indices()
sims %>% n_at_dose()
sims %>% tox_at_dose()
sims %>% num_tox()
sims %>% recommended_dose()
sims %>% prob_administer()
sims %>% prob_recommend()
sims %>% trial_duration()

# Access the list of model fits for the ith simulated trial using:
i <- 1
sims$fits[[i]]
# and the jth model fit for the ith simulated trial using:
j <- 1
```

```
sims$fits[[i]][[j]]
# and so on.
```

```
simulation_function    Get function for simulating trials.
```

Description

This function does not need to be called by users. It is used internally.

Usage

```
simulation_function(selector_factory)
```

Arguments

```
selector_factory
                Object of type selector\_factory.
```

Value

A function.

```
spread_paths            Spread the information in dose_finding_paths object to a wide data.frame format.
```

Description

Spread the information in dose_finding_paths object to a wide data.frame format.

Usage

```
spread_paths(df = NULL, dose_finding_paths = NULL, max_depth = NULL)
```

Arguments

```
df                      Optional data.frame like that returned by as_tibble(dose_finding_paths). Columns .depth, .node, .parent are required. All other columns are spread with a suffix reflecting depth.
dose_finding_paths      Optional instance of dose_finding_paths. Required if 'df' is null.
max_depth               integer, maximum depth of paths to traverse.
```

Value

A data.frame

Examples

```
## Not run:
# Calculate paths for the first two cohorts of three patients a CRM trial
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
cohort_sizes <- c(3, 3)
paths <- get_dfcrm(skeleton = skeleton, target = target) %>%
  get_dose_paths(cohort_sizes = cohort_sizes)

## End(Not run)
```

stop_at_n	<i>Stop when there are n patients in total.</i>
-----------	---

Description

This function adds a restriction to stop a trial when n patients have been evaluated. It does this by adding together the number of patients treated at all doses and stopping when that total exceeds n .

Dose selectors are designed to be daisy-chained together to achieve different behaviours. This class is a **greedy** selector, meaning that it prioritises its own behaviour over the behaviour of other selectors in the chain. That is, it will advocate stopping when the condition has been met, even if the selectors further up the chain would advocate to keep going. It can be interpreted as an overriding selector. This allows the decision to stop to be executed as soon as it is warranted. Be aware though, that there are other selectors that can be placed after this class that will override the stopping behaviour. See Examples.

Usage

```
stop_at_n(parent_selector_factory, n)
```

Arguments

parent_selector_factory	Object of type selector_factory .
n	Stop when there are this many patients.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# Create CRM model that will stop when 15 patients are evaluated:
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 15)
```

```

# With 12 patients, this trial should not stop:
fit1 <- model1 %>% fit('1NNN 2NTN 2TNN 2NNN')
fit1 %>% recommended_dose()
fit1 %>% continue()

# With 15 patients, this trial should stop:
fit2 <- model1 %>% fit('1NNN 2NTN 2TNN 2NNN 2NTT')
fit2 %>% recommended_dose()
fit2 %>% continue()

# The stopping behaviour can be overruled by the order of selectors.
# In model2, demanding 9 at recommended dose will trump stopping at 12:
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_at_n(n = 12) %>%
  demand_n_at_dose(dose = 'recommended', n = 9)

# In model3, stopping at 12 will trump demanding 9 at recommended dose:
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  demand_n_at_dose(dose = 'recommended', n = 9) %>%
  stop_at_n(n = 12)

# This model will continue because 9 have not been seen at recommended dose.
fit3 <- model2 %>% fit('1NNN 2NNN 2NNN 3NNN')
fit3 %>% recommended_dose()
fit3 %>% continue()

# This model will stop because 12 have been seen.
fit4 <- model3 %>% fit('1NNN 2NNN 2NNN 3NNN')
fit4 %>% recommended_dose()
fit4 %>% continue()

# With enough observations though, both models will advise stopping because
# both conditions have been met:
fit5 <- model2 %>% fit('1NNN 2NNN 2NNN 5NNN 5NNN 5NNN')
fit5 %>% recommended_dose()
fit5 %>% continue()

fit6 <- model3 %>% fit('1NNN 2NNN 2NNN 5NNN 5NNN 5NNN')
fit6 %>% recommended_dose()
fit6 %>% continue()

```

stop_when_n_at_dose *Stop when there are n patients at a dose.*

Description

This method stops a dose-finding trial when there are n patients at a dose. It can stop when the rule is triggered at the recommended dose, at a particular dose, or at any dose.

Usage

```
stop_when_n_at_dose(parent_selector_factory, n, dose)
```

Arguments

```
parent_selector_factory
    Object of type selector\_factory.

n
    Stop when there are n at a dose.

dose
    'any' to stop when there are n at any dose; 'recommended' to stop when there
    are n at the recommended dose; or an integer to stop when there are n at a
    particular dose-level.
```

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# This model will stop when 12 are seen at any dose:
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 12, dose = 'any')

# This model fit will not stop:
model1 %>% fit('1NNN 2NTN 2TNN 2NNN') %>% continue()
# But this model fit will stop:
model1 %>% fit('1NNN 2NTN 2TNN 2NNN 2NTT') %>% continue()

# This model will stop when 12 are seen at the recommended dose:
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_n_at_dose(n = 12, dose = 'recommended')

# This model fit will not stop:
fit2 <- model2 %>% fit('1NNN 2NTN 2TNN 2NNN')
fit2 %>% recommended_dose()
fit2 %>% continue()
# But this model fit will stop:
fit3 <- model2 %>% fit('1NNN 2NTN 2TNN 2NNN 2NNT')
fit3 %>% recommended_dose()
fit3 %>% continue()
```

stop_when_too_toxic *Stop trial and recommend no dose when a dose is too toxic.*

Description

This method stops a dose-finding trial and recommends no dose when sufficient probabilistic confidence is reached that the rate of toxicity at a dose exceeds some threshold. In other words, it stops when it is likely that a dose is too toxic. It can stop when the rule is triggered at the recommended dose, at a particular dose, or at any dose. See Details.

Usage

```
stop_when_too_toxic(parent_selector_factory, dose, tox_threshold, confidence)
```

Arguments

parent_selector_factory	Object of type selector_factory .
dose	'any' to stop when any dose is too toxic; 'recommended' to stop when the recommended dose is too toxic; or an integer to stop when a particular dose-level is too toxic.
tox_threshold	We are interested in toxicity probabilities greater than this threshold.
confidence	Stop when there is this much total probability mass supporting that the toxicity rate exceeds the threshold.

Details

The method for calculating probability mass for toxicity rates will ultimately be determined by the dose-finding model used and the attendant inferential mechanism. For instance, the `crm` function in the `dfcrm` package calculates the posterior expected mean and variance of the slope parameter in a CRM model. It does not use MCMC to draw samples from the posterior distribution. Thus, to perform inference on the posterior probability of toxicity, this package assumes the `dfcrm` slope parameter follows a normal distribution with the mean and variance calculated by `dfcrm`. In contrast, the `stan_crm` function in the `trialr` package needs no such assumption because it samples from the posterior parameter distribution and uses those samples to infer on the posterior probability of toxicity at each dose, dependent on the chosen model for the dose-toxicity curve.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# We compare a CRM model without a toxicity stopping rule to one with it:
model1 <- get_dfcrm(skeleton = skeleton, target = target)
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_too_toxic(dose = 'any', tox_threshold = 0.5, confidence = 0.7)

outcomes <- '1NNN 2NNN 3NNT 3NNN 3TNT 2NNN'
fit1 <- model1 %>% fit(outcomes)
```

```

fit2 <- model2 %>% fit(outcomes)

# Naturally the first does not advocate stopping:
fit1 %>% recommended_dose()
fit1 %>% continue()

# However, after the material toxicity at dose 3, the rule is fired:
fit2 %>% recommended_dose()
fit2 %>% continue()
# To verify the requirement to stop, let's calculate the probability that the
# toxicity rate exceeds 50%
fit2 %>% prob_tox_exceeds(0.5)

```

```
stop_when_tox_ci_covered
```

Stop when uncertainty interval of prob tox is covered.

Description

This method stops a dose-finding trial when the symmetric uncertainty interval for the probability of toxicity falls within a range. This allows trials to be stopped when sufficient precision on the probability of toxicity has been achieved. See Details.

Usage

```

stop_when_tox_ci_covered(
  parent_selector_factory,
  dose,
  lower,
  upper,
  width = 0.9
)

```

Arguments

parent_selector_factory	Object of type selector_factory .
dose	'any' to stop when the interval for any dose is covered; 'recommended' to stop when the interval for the recommended dose is covered ; or an integer to stop when the interval for a particular dose-level is covered.
lower	Stop when lower interval bound exceeds this value
upper	Stop when upper interval bound is less than this value
width	Width of the uncertainty interval. Default is 0.9, i.e. a range from the 5th to the 95th percentiles.

Details

The method for calculating probability mass for toxicity rates will ultimately be determined by the dose-finding model used and the attendant inferential mechanism. For instance, the `crm` function in the `dfcrm` package calculates the posterior expected mean and variance of the slope parameter in a CRM model. It does not use MCMC to draw samples from the posterior distribution. Thus, to perform inference on the posterior probability of toxicity, this package assumes the `dfcrm` slope parameter follows a normal distribution with the mean and variance calculated by `dfcrm`. In contrast, the `stan_crm` function in the `trialr` package needs no such assumption because it samples from the posterior parameter distribution and uses those samples to infer on the posterior probability of toxicity at each dose, dependent on the chosen model for the dose-toxicity curve.

Value

an object of type `selector_factory` that can fit a dose-finding model to outcomes.

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# We compare a CRM model without this stopping rule:
model1 <- get_dfcrm(skeleton = skeleton, target = target)
# To two with it, the first demanding a relatively tight CI:
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_tox_ci_covered(dose = 'recommended', lower = 0.15, upper = 0.35)
# and the second demanding a relatively loose CI:
model3 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_tox_ci_covered(dose = 'recommended', lower = 0.05, upper = 0.45)

outcomes <- '1NNN 2NNN 3NNT 3NNN 3TNT 2NNN'
fit1 <- model1 %>% fit(outcomes)
fit2 <- model2 %>% fit(outcomes)
fit3 <- model3 %>% fit(outcomes)

# Naturally the first does not advocate stopping:
fit1 %>% recommended_dose()
fit1 %>% continue()

# The second does not advocate stopping either:
fit2 %>% recommended_dose()
fit2 %>% continue()
# This is because the CI is too wide:
fit2 %>% prob_tox_quantile(p = 0.05)
fit2 %>% prob_tox_quantile(p = 0.95)

# However, the third design advocates stopping because the CI at the
# recommended dose is covered:
fit3 %>% recommended_dose()
fit3 %>% continue()
# To verify the veracity, inspect the quantiles:
fit3 %>% prob_tox_quantile(p = 0.05)
```

```
fit3 %>% prob_tox_quantile(p = 0.95)
```

```
supports_sampling      Does this selector support sampling of outcomes?
```

Description

Learn whether this selector supports sampling of outcomes. For instance, is it possible to get posterior samples of the probability of toxicity at each dose? If true, `prob_tox_samples` will return a data-frame of samples.

Usage

```
supports_sampling(x, ...)
```

Arguments

<code>x</code>	Object of type <code>selector</code>
<code>...</code>	arguments passed to other methods

Value

logical

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% supports_sampling()
```

```
three_plus_three      Fit the 3+3 model to some outcomes.
```

Description

Fit the 3+3 model to some outcomes.

Usage

```
three_plus_three(
  outcomes,
  num_doses,
  allow_deescalate = FALSE,
  strict_mode = TRUE
)
```

Arguments

outcomes	Outcomes observed. See parse_phase1_outcomes .
num_doses	Number of doses under investigation.
allow_deescalate	TRUE to allow de-escalation, as described by Korn et al. Default is FALSE.
strict_mode	TRUE to raise errors if it is detected that the 3+3 algorithm has not been followed.

Value

lists containing recommended_dose and a logical value continue saying whether the trial should continue.

References

Storer BE. Design and Analysis of Phase I Clinical Trials. Biometrics. 1989;45(3):925-937. doi:10.2307/2531693

Korn EL, Midthune D, Chen TT, Rubinstein LV, Christian MC, Simon RM. A comparison of two phase I trial designs. Statistics in Medicine. 1994;13(18):1799-1806. doi:10.1002/sim.4780131802

Examples

```
three_plus_three('2NNN 3NNT', num_doses = 7)
```

tox	<i>Binary toxicity outcomes.</i>
-----	----------------------------------

Description

Get a vector of the binary toxicity outcomes for evaluated patients.

Usage

```
tox(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

an integer vector

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% tox()
```

tox_at_dose	<i>Number of toxicities seen at each dose.</i>
-------------	--

Description

Get the number of toxicities seen at each dose under investigation.

Usage

```
tox_at_dose(x, ...)
```

Arguments

x	Object of class selector
...	arguments passed to other methods

Value

an integer vector

Examples

```
# CRM example
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
outcomes <- '1NNN 2NTN'
fit <- get_dfcrm(skeleton = skeleton, target = target) %>% fit(outcomes)
fit %>% tox_at_dose()
```

tox_limit	<i>Toxicity rate limit</i>
-----------	----------------------------

Description

Get the maximum permissible toxicity rate, if supported. NULL if not.

Usage

```
tox_limit(x, ...)
```

Arguments

x	Object of type selector .
...	Extra args are passed onwards.

Value

numeric

Examples

```
efftox_priors <- trialr::efftox_priors
p <- efftox_priors(alpha_mean = -7.9593, alpha_sd = 3.5487,
  beta_mean = 1.5482, beta_sd = 3.5018,
  gamma_mean = 0.7367, gamma_sd = 2.5423,
  zeta_mean = 3.4181, zeta_sd = 2.4406,
  eta_mean = 0, eta_sd = 0.2,
  psi_mean = 0, psi_sd = 1)
real_doses = c(1.0, 2.0, 4.0, 6.6, 10.0)
model <- get_trialr_efftox(real_doses = real_doses,
  efficacy_hurdle = 0.5, toxicity_hurdle = 0.3,
  p_e = 0.1, p_t = 0.1,
  eff0 = 0.5, tox1 = 0.65,
  eff_star = 0.7, tox_star = 0.25,
  priors = p, iter = 1000, chains = 1, seed = 2020)
x <- model %>% fit('1N 2E 3B')
tox_limit(x)
```

tox_target	<i>Target toxicity rate</i>
------------	-----------------------------

Description

Get the target toxicity rate, if supported. NULL if not.

Usage

```
tox_target(x, ...)
```

Arguments

x Object of type [selector](#).
... Extra args are passed onwards.

Value

numeric

Examples

```
skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25
model <- get_dfcrm(skeleton = skeleton, target = target)
fit <- model %>% fit('1NNN 2NTN')
fit %>% tox_target()
```

trial_duration	<i>Duration of trials.</i>
----------------	----------------------------

Description

Get the length of time that trials take to recruit all patients.

Usage

```
trial_duration(x, ...)
```

Arguments

x Object of type [simulations](#).
... arguments passed to other methods

Value

vector of numerical times

Examples

```

true_prob_tox <- c(0.12, 0.27, 0.44, 0.53, 0.57)
sims <- get_three_plus_three(num_doses = 5) %>%
  simulate_trials(num_sims = 50, true_prob_tox = true_prob_tox)
sims %>% trial_duration

```

try_rescue_dose	<i>Demand that a rescue dose is tried before stopping is permitted.</i>
-----------------	---

Description

This method continues a dose-finding trial until a safety dose has been given to n patients. Once that condition is met, it delegates dose selecting and stopping responsibility to its parent dose selector, whatever that might be. This class is greedy in that it meets its own needs before asking any other selectors higher in the chain what they want. Thus, different behaviours may be achieved by nesting dose selectors in different orders. See examples.

Usage

```
try_rescue_dose(parent_selector_factory, n, dose)
```

Arguments

parent_selector_factory	Object of type selector_factory .
n	Continue at least until there are n at a dose.
dose	an integer to identify the sought rescue dose-level.

Value

an object of type [selector_factory](#) that can fit a dose-finding model to outcomes.

Examples

```

skeleton <- c(0.05, 0.1, 0.25, 0.4, 0.6)
target <- 0.25

# This model will demand the lowest dose is tried in at least two patients
# before the trial is stopped for excess toxicity
model1 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_too_toxic(dose = 1, tox_threshold = 0.35, confidence = 0.8) %>%
  try_rescue_dose(dose = 1, n = 2)

# In contrast, this model will stop for excess toxicity without trying dose 1
model2 <- get_dfcrm(skeleton = skeleton, target = target) %>%
  stop_when_too_toxic(dose = 1, tox_threshold = 0.35, confidence = 0.8)

# For non-toxic outcomes, both designs will continue at sensible doses:

```

```
fit1 <- model1 %>% fit('2NNN')
fit1 %>% recommended_dose()
fit1 %>% continue()

fit2 <- model2 %>% fit('2NNN')
fit2 %>% recommended_dose()
fit2 %>% continue()

# For toxic outcomes, the design 1 will use dose 1 before stopping is allowed
fit1 <- model1 %>% fit('2TTT')
fit1 %>% recommended_dose()
fit1 %>% continue()

# For toxic outcomes, however, design 2 will stop despite dose 1 being
# untested:
fit2 <- model2 %>% fit('2TTT')
fit2 %>% recommended_dose()
fit2 %>% continue()

# After dose 1 is given the requisite number of times, dose recommendation
# and stopping revert to being determined by the underlying dose selector:
fit1 <- model1 %>% fit('2TTT 1T')
fit1 %>% recommended_dose()
fit1 %>% continue()

fit1 <- model1 %>% fit('2TTT 1TT')
fit1 %>% recommended_dose()
fit1 %>% continue()
```

Index

`as_tibble.dose_paths`, 4

`calculate_probabilities`, 5

`cohort`, 6, 60

`cohorts_of_n`, 6, 68

`continue`, 7, 61

`crm`, 22, 60, 76, 78

`crystallised_dose_paths`, 8

`demand_n_at_dose`, 9

`dont_skip_doses`, 10

`dose_admissible`, 12, 61

`dose_indices`, 13, 61, 71

`dose_paths`, 4, 5, 8, 13, 23, 39

`dose_paths_function`, 14

`doses_given`, 11, 60

`eff`, 14, 61

`eff_at_dose`, 15, 61

`eff_limit`, 16, 61

`empiric_eff_rate`, 17, 61

`empiric_tox_rate`, 17, 61

`enforce_three_plus_three`, 18

`escalation (escalation-package)`, 4

`escalation-package`, 4

`fit`, 19, 60, 63

`follow_path`, 19, 21, 32, 36

`get.boundary`, 21

`get_boin`, 20, 60, 63, 65, 67, 68

`get_dfcrm`, 21, 36, 60, 63, 67, 68

`get_dose_paths`, 13, 23

`get_empiric_crm_skeleton_weights`, 24

`get_mtpi`, 24

`get_mtpi2`, 26

`get_random_selector`, 28

`get_three_plus_three`, 29, 60, 63, 67, 68

`get_tpi`, 30

`get_trialr_crm`, 32

`get_trialr_efftox`, 34

`get_trialr_nbg`, 35

`get_wages_and_tait`, 37

`graph_paths`, 39

`is_randomising`, 40, 61

`mean_prob_eff`, 40, 61

`mean_prob_tox`, 41, 60, 61

`median_prob_eff`, 42, 61

`median_prob_tox`, 43, 60, 61

`model_frame`, 43, 61

`n_at_dose`, 48, 61, 71

`n_at_recommended_dose`, 49, 61

`num_cohort_outcomes`, 44

`num_dose_path_nodes`, 45

`num_doses`, 45, 61, 71

`num_eff`, 46, 61

`num_patients`, 47, 60, 71

`num_tox`, 47, 61, 71

`parse_phase1_2_outcomes`, 49

`parse_phase1_outcomes`, 18–20, 50, 80

`phase1_2_outcomes_to_cohorts`, 52

`phase1_outcomes_to_cohorts`, 53

`prob_administer`, 54, 61, 71

`prob_eff_exceeds`, 61

`prob_eff_exceeds (prob_tox_exceeds)`, 56

`prob_eff_quantile`, 55, 61

`prob_eff_samples`, 61

`prob_eff_samples (prob_tox_samples)`, 58

`prob_recommend`, 56, 71

`prob_tox_exceeds`, 56, 60, 61

`prob_tox_quantile`, 57, 61

`prob_tox_samples`, 58, 61

`recommended_dose`, 59, 61, 71

`select.mtd`, 65

`select_boin_mtd`, 65

`select_dose_by_cibp`, 66

selector, [6](#), [7](#), [11–17](#), [19](#), [40–43](#), [45–49](#),
[54–59](#), [60](#), [63](#), [70](#), [71](#), [79–83](#)

selector_factory, [9](#), [10](#), [14](#), [19–23](#), [25](#), [27](#),
[29–32](#), [34–38](#), [60](#), [61](#), [63](#), [63](#), [65–68](#),
[72](#), [73](#), [75–78](#), [84](#)

simulate_trials, [67](#), [71](#)

simulation_function, [72](#)

simulations, [56](#), [68](#), [70](#), [83](#)

spread_paths, [72](#)

stan_crm, [32](#)

stan_efftox, [35](#)

stan_nbg, [36](#)

stop_at_n, [7](#), [68](#), [73](#)

stop_when_n_at_dose, [60](#), [63](#), [68](#), [74](#)

stop_when_too_toxic, [7](#), [60](#), [63](#), [75](#)

stop_when_tox_ci_covered, [77](#)

supports_sampling, [58](#), [61](#), [79](#)

three_plus_three, [79](#)

tibble, [4](#), [44](#)

tox, [61](#), [80](#)

tox_at_dose, [61](#), [71](#), [81](#)

tox_limit, [61](#), [82](#)

tox_target, [60](#), [83](#)

trial_duration, [71](#), [83](#)

trialr, [35](#)

try_rescue_dose, [84](#)