

Package ‘jinjar’

June 25, 2022

Title Template Engine Inspired by 'Jinja'

Version 0.2.0

Description Template engine powered by the 'inja' C++ library. Users write a template document, using syntax inspired by the 'Jinja' Python package, and then render the final document by passing data from R. The template syntax supports features such as variables, loops, conditions and inheritance.

License MIT + file LICENSE

URL <https://davidchall.github.io/jinjar/>,
<https://github.com/davidchall/jinjar>

BugReports <https://github.com/davidchall/jinjar/issues>

Imports cli, fs, jsonlite, rlang (>= 1.0.0)

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

LinkingTo cpp11

VignetteBuilder knitr

Config/testthat/edition 3

Encoding UTF-8

Language en-US

RoxygenNote 7.2.0

SystemRequirements C++11

NeedsCompilation yes

Author David Hall [aut, cre, cph] (<<https://orcid.org/0000-0002-2193-0480>>),
Lars Berscheid [cph] (Author of bundled inja library),
Niels Lohmann [cph] (Author of bundled json library)

Maintainer David Hall <david.hall.physics@gmail.com>

Repository CRAN

Date/Publication 2022-06-25 02:10:02 UTC

R topics documented:

jinjar_config	2
loader	3
parse	4
render	5

Index	7
--------------	----------

jinjar_config	<i>Configure the templating engine</i>
---------------	--

Description

Create an object to configure the templating engine behavior (e.g. customize the syntax). The default values have been chosen to match the Jinja defaults.

Usage

```
jinjar_config(
  loader = NULL,
  block_open = "{%",
  block_close = "%}",
  variable_open = "{{",
  variable_close = "}}",
  comment_open = "{#",
  comment_close = "#}",
  line_statement = NULL,
  trim_blocks = FALSE,
  lstrip_blocks = FALSE,
  ignore_missing_files = FALSE
)

default_config()
```

Arguments

loader How the engine discovers templates. Choices:

- NULL (default), disables search for templates.
- Path to template directory.
- A [loader](#) object.

block_open, block_close The opening and closing delimiters for control blocks. Default: "{%" and "%}".

variable_open, variable_close The opening and closing delimiters for print statements. Default: "{{" and "}}".

<code>comment_open</code> , <code>comment_close</code>	The opening and closing delimiters for comments. Default: "{#" and "#}".
<code>line_statement</code>	The prefix for an inline statement. If NULL (the default), inline statements are disabled.
<code>trim_blocks</code>	Remove first newline after a block. Default: FALSE.
<code>lstrip_blocks</code>	Remove inline whitespace before a block. Default: FALSE.
<code>ignore_missing_files</code>	Ignore include or extends statements when the auxiliary template cannot be found. If FALSE (default), then an error is raised.

Value

A "jinjar_config" object.

Note

The equivalent Jinja class is `Environment`, but this term has special significance in R (see `environment()`).

Examples

```
jinjar_config()
```

loader

Template loaders

Description

Loaders are responsible for exposing templates to the templating engine.

`path_loader()` loads templates from a directory in the file system.

`package_loader()` loads templates from a directory in an R package.

`list_loader()` loads templates from a named list.

Usage

```
path_loader(...)
```

```
package_loader(package, ...)
```

```
list_loader(x)
```

Arguments

<code>...</code>	Strings specifying path components.
<code>package</code>	Name of the package in which to search.
<code>x</code>	Named list mapping template names to template sources.

Value

A "jinjar_loader" object.

See Also

The loader is an argument to [jinjar_config\(\)](#).

Examples

```
path_loader(getwd())

package_loader("base", "demo")

list_loader(list(
  header = "Title: {{ title }}",
  content = "Hello {{ person }}!"
))
```

parse

Parse template

Description

Sometimes you want to render multiple copies of a template, using different sets of data variables. [parse_template\(\)](#) returns an intermediate version of the template, so you can [render\(\)](#) repeatedly without re-parsing the template syntax.

Usage

```
parse_template(.x, .config)

## S3 method for class 'character'
parse_template(.x, .config = default_config())

## S3 method for class 'fs_path'
parse_template(.x, .config = default_config())
```

Arguments

<code>.x</code>	The template. Choices: <ul style="list-style-type: none"> • A template string. • A path to a template file (use fs::path()).
<code>.config</code>	The engine configuration. The default matches Jinja defaults, but you can use jinjar_config() to customize things like syntax delimiters, whitespace control, and loading auxiliary templates.

Value

A "jinja_template" object.

See Also

- [render\(\)](#) to render the final document using data variables.
- [vignette\("template-syntax"\)](#) describes how to write templates.

Examples

```
x <- parse_template("Hello {{ name }}!")
render(x, name = "world")
```

render	<i>Render template</i>
--------	------------------------

Description

Data is passed to a template to render the final document.

Usage

```
render(.x, ...)

## S3 method for class 'character'
render(.x, ..., .config = default_config())

## S3 method for class 'fs_path'
render(.x, ..., .config = default_config())

## S3 method for class 'jinja_template'
render(.x, ...)
```

Arguments

.x	The template. Choices: <ul style="list-style-type: none"> • A template string. • A path to a template file (use fs::path()). • A parsed template (use parse_template()).
...	<dynamic-dots> Data passed to the template.
.config	The engine configuration. The default matches Jinja defaults, but you can use jinja_config() to customize things like syntax delimiters, whitespace control, and loading auxiliary templates.

Value

String containing rendered template.

See Also

- `parse_template()` supports parsing a template once and rendering multiple times with different data variables.
- `vignette("template-syntax")` describes how to write templates.

Examples

```
# pass data as arguments
render("Hello {{ name }}!", name = "world")

# pass data as list
params <- list(name = "world")
render("Hello {{ name }}!", !!!params)

# render template file
## Not run:
render(fs::path("template.txt"), name = "world")

## End(Not run)
```

Index

`default_config(jinja_config)`, 2

`environment()`, 3

`fs::path()`, 4, 5

`jinja_config`, 2

`jinja_config()`, 4, 5

`list_loader(loader)`, 3

`loader`, 2, 3

`package_loader(loader)`, 3

`parse`, 4

`parse_template(parse)`, 4

`parse_template()`, 4–6

`path_loader(loader)`, 3

`render`, 5

`render()`, 4, 5