

Package ‘lddmm’

June 6, 2023

Type Package

Title Longitudinal Drift-Diffusion Mixed Models (LDDMM)

Version 0.4.0

Date 2023-06-03

Description Implementation of the drift-diffusion mixed model for category learning as described in Paulon et al. (2021) <[doi:10.1080/01621459.2020.1801448](https://doi.org/10.1080/01621459.2020.1801448)>.

Depends R (>= 4.1.0)

Language en-US

License MIT + file LICENSE

Encoding UTF-8

Imports Rcpp (>= 1.0.6), RcppProgress, rgen, gtools, LaplacesDemon, dplyr, plyr, tidyr, ggplot2, latex2exp, reshape2, RColorBrewer

LazyData true

LinkingTo Rcpp, RcppArmadillo, RcppProgress, rgen

RoxygenNote 7.2.3

Suggests rmarkdown, knitr

VignetteBuilder knitr

NeedsCompilation yes

Author Giorgio Paulon [aut, cre],
Abhra Sarkar [aut, ctb]

Maintainer Giorgio Paulon <giorgio.paulon@utexas.edu>

Repository CRAN

Date/Publication 2023-06-06 13:20:05 UTC

R topics documented:

B_basis	2
compute_WAIC	2
data	3

extract_post_draws	3
extract_post_mean	4
H_ball	5
LDDMM	5
log_likelihood	7
log_likelihood_ind	7
plot_accuracy	8
plot_post_pars	9
plot_RT	9
P_smooth1	10

Index	11
--------------	-----------

B_basis	<i>Spline Basis Functions</i>
---------	-------------------------------

Description

Construct the J basis functions for the splines evaluated on a grid.

Usage

```
B_basis(xgrid, knots)
```

Arguments

xgrid	grid where we want to evaluate the spline functions (vector of length n)
knots	vector of knots for the splines (vector of length K)

Value

n x (K+1) - matrix representing the value of each basis function evaluated on xgrid

compute_WAIC	<i>Calculate WAIC</i>
--------------	-----------------------

Description

Function to compute the Watanabe-Akaike information criterion (Gelman, Hwang, Vehtari, 2014), which estimates the expected out-of-sample-prediction error using a bias-corrected adjustment of within-sample error.

Usage

```
compute_WAIC(model_fit)
```

Arguments

`model_fit` results of a model fit from the `lddmm` function

Value

A scalar indicating the WAIC (smaller WAIC denotes better fit)

<code>data</code>	<i>Example dataset</i>
-------------------	------------------------

Description

A toy dataset in the correct format for the LDDMM function call. This dataset has two possible response categories.

Usage

```
data
```

Format

A data frame with 24,254 rows and 6 columns

Details

- `subject`: vector of size `n` containing the participant labels
- `block`: vector of size `n` containing the training blocks (longitudinal units)
- `s`: vector of size `n` containing the stimuli
- `d`: vector of size `n` containing the decisions
- `r_time`: vector of size `n` containing the response times (log transformed)
- `cens`: vector of size `n` containing the censoring indicators (1 censored, 0 non censored)

<code>extract_post_draws</code>	<i>Parameter posterior draws</i>
---------------------------------	----------------------------------

Description

Function to extract the posterior draws of the parameters of interest from a `lddmm` fit object.

Usage

```
extract_post_draws(data, fit, par = c("drift", "boundary"))
```

Arguments

<code>data</code>	dataframe with the following columns: <ul style="list-style-type: none"> • <code>subject</code>: vector of size <code>n</code> containing the participant labels • <code>block</code>: vector of size <code>n</code> containing the training blocks (longitudinal units) • <code>s</code>: vector of size <code>n</code> containing the stimuli • <code>d</code>: vector of size <code>n</code> containing the decisions • <code>r_time</code>: vector of size <code>n</code> containing the response times • <code>cens</code>: vector of size <code>n</code> containing the censoring indicators (1 censored, 0 non censored)
<code>fit</code>	fit from the <code>lddmm</code> function
<code>par</code>	parameter to output ('drift', or 'boundary')

Value

Matrix with the following columns:

- `subject`: participant labels
- `block`: training blocks
- `draw`: iteration of the MCMC estimates
- `par_s_d, ...`: posterior draws for the requested parameters

<code>extract_post_mean</code>	<i>Parameter posterior means</i>
--------------------------------	----------------------------------

Description

Function to extract the posterior means of the parameters of interest from a `lddmm` fit object.

Usage

```
extract_post_mean(data, fit, par = c("drift", "boundary"))
```

Arguments

<code>data</code>	dataframe with the following columns: <ul style="list-style-type: none"> • <code>subject</code>: vector of size <code>n</code> containing the participant labels • <code>block</code>: vector of size <code>n</code> containing the training blocks (longitudinal units) • <code>s</code>: vector of size <code>n</code> containing the stimuli • <code>d</code>: vector of size <code>n</code> containing the decisions • <code>r_time</code>: vector of size <code>n</code> containing the response times • <code>cens</code>: vector of size <code>n</code> containing the censoring indicators (1 censored, 0 non censored)
<code>fit</code>	fit from the <code>lddmm</code> function
<code>par</code>	parameter to output ('drift', or 'boundary')

Value

Matrix with the following columns:

- subject: participant labels
- block: training blocks
- par_s_d, ...: posterior means for the requested parameters

H_ball

Hamming Ball

Description

Computes the Hamming Ball centered at x with radius r.

Usage

```
H_ball(x, S, r)
```

Arguments

x	center of the Hamming Ball
S	number of states
r	radius of the Hamming Ball

Value

Hamming Ball

LDDMM

Drift Diffusion Model Fit

Description

Main function for the Gibbs sampler for the drift-diffusion model. Note that priors are noninformative and calibrated so that, for the most stable performance, the response times (variable r_time in the data dataframe) should lie between 0 and 10.

Usage

```
LDDMM(
  data,
  hypers,
  boundaries = "flexible",
  Niter = 5000,
  burnin = 2000,
  thin = 5
)
```

Arguments

data	dataframe with the following columns: <ul style="list-style-type: none"> • subject: vector of size n containing the participant labels • block: vector of size n containing the training blocks (longitudinal units) • s: vector of size n containing the stimuli • d: vector of size n containing the decisions • r_time: vector of size n containing the response times. To avoid numerical issues, the unit of measurement should be such that the numerical values of most response times should lie between 0 and 10 • cens: vector of size n containing the censoring indicators (1 censored, 0 non censored)
hypers	hyperparameters of the MCMC: list containing "s_sigma_mu" and "s_sigma_b", which are the smoothness parameters for drifts and boundaries, respectively)
boundaries	whether to fit the unrestricted model (flexible), assume constant boundaries over time (constant) or fix the boundaries to the same level across predictors (fixed)
Niter	total number of iterations
burnin	burnin of the chain
thin	thinning factor

Value

List with the following MCMC posterior samples:

- post_mean_delta: posterior samples for the population offset parameters
- post_mean_mu: posterior samples for the population drift parameters
- post_mean_b: posterior samples for the population boundary parameters
- post_ind_delta: posterior samples for the individual offset parameters
- post_ind_mu: posterior samples for the individual drift parameters
- post_ind_b: posterior samples for the individual boundary parameters
- sigma2_mu_us: posterior samples for the random effects drift smoothness parameters
- sigma2_mu_ua: posterior samples for the random effects drift variance parameters
- sigma2_b_us: posterior samples for the random effects boundary smoothness parameters
- sigma2_b_ua: posterior samples for the random effects boundary variance parameters
- sigma2_1_mu: posterior samples for the drift smoothness parameters
- sigma2_1_b: posterior samples for the boundary smoothness parameters
- pred_ans: predicted population-level categories
- pred_time: predicted population-level response times
- pred_ans_ind: predicted individual-level categories
- pred_time_ind: predicted individual-level response times

log_likelihood *Log-likelihood computation*

Description

Compute the log-likelihood for the drift-diffusion model, including the censored data contribution.

Usage

```
log_likelihood(tau, mu, b, delta, cens, D, log)
```

Arguments

tau	vector of size n containing the response times
mu	matrix of size (n x d1) containing the drift parameters corresponding to the n response times for each possible d1 decision
b	matrix of size (n x d1) containing the boundary parameters corresponding to the n response times for each possible d1 decision
delta	vector of size n containing the offset parameters corresponding to the n response times
cens	vector of size n containing censoring indicators (1 censored, 0 not censored) corresponding to the n response times
D	(n x 2) matrix whose first column has the n input stimuli, and whose second column has the n decision categories
log	should the results be returned on the log scale?

log_likelihood_ind *Log-likelihood computation for a single observation*

Description

Compute the log-likelihood for the drift-diffusion model, including the censored data contribution, for a single observation.

Usage

```
log_likelihood_ind(tau, mu, b, delta, cens, D)
```

Arguments

tau	vector of size n containing the response times
mu	matrix of size (n x d1) containing the drift parameters corresponding to the n response times for each possible d1 decision
b	matrix of size (n x d1) containing the boundary parameters corresponding to the n response times for each possible d1 decision
delta	vector of size n containing the offset parameters corresponding to the n response times
cens	vector of size n containing censoring indicators (1 censored, 0 not censored) corresponding to the n response times
D	(n x 2) matrix whose first column has the n input stimuli, and whose second column has the n decision categories

plot_accuracy

Descriptive plots

Description

Plot the accuracy of the raw data.

Usage

```
plot_accuracy(data)
```

Arguments

data	dataframe with the following columns: <ul style="list-style-type: none"> • subject: vector of size n containing the participant labels • block: vector of size n containing the training blocks (longitudinal units) • s: vector of size n containing the stimuli • d: vector of size n containing the decisions • r_time: vector of size n containing the response times • cens: vector of size n containing the censoring indicators (1 censored, 0 non censored)
------	---

Value

Individual and population level raw accuracies

plot_post_pars	<i>Plot posterior estimates</i>
----------------	---------------------------------

Description

Function to plot the posterior mean and credible intervals of the parameters of interest from a lddmm fit object.

Usage

```
plot_post_pars(data, fit, par = c("drift", "boundary"))
```

Arguments

data	dataframe with the following columns: <ul style="list-style-type: none"> • subject: vector of size n containing the participant labels • block: vector of size n containing the training blocks (longitudinal units) • s: vector of size n containing the stimuli • d: vector of size n containing the decisions • r_time: vector of size n containing the response times • cens: vector of size n containing the censoring indicators (1 censored, 0 non censored)
fit	fit from the lddmm function
par	parameter to output ('drift', or 'boundary')

Value

Posterior mean and 95% CI

plot_RT	<i>Descriptive plots</i>
---------	--------------------------

Description

Plot the mean response times of the raw data.

Usage

```
plot_RT(data)
```

Arguments

data dataframe with the following columns:

- subject: vector of size n containing the participant labels
- block: vector of size n containing the training blocks (longitudinal units)
- s: vector of size n containing the stimuli
- d: vector of size n containing the decisions
- r_time: vector of size n containing the response times
- cens: vector of size n containing the censoring indicators (1 censored, 0 non censored)

Value

Population level raw response times

<i>P_smooth1</i>	<i>Spline Penalty Matrix</i>
------------------	------------------------------

Description

Construct the covariance matrix P of the smoothness inducing prior for the spline coefficients

Usage

P_smooth1(K)

Arguments

K Number of spline knots

Value

Covariance of the smoothness inducing prior (penalizing first differences in the spline coefficients)

Index

* datasets

data, 3

B_basis, 2

compute_WAIC, 2

data, 3

extract_post_draws, 3

extract_post_mean, 4

H_ball, 5

LDDMM, 5

log_likelihood, 7

log_likelihood_ind, 7

P_smooth1, 10

plot_accuracy, 8

plot_post_pars, 9

plot_RT, 9