

Package ‘tinytable’

March 28, 2024

Type Package

Title Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats

Description Create highly customized tables with this simple and dependency-free package. Data frames can be converted to 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', or 'Typst' tables. The user interface is minimalist and easy to learn. The syntax concise. 'HTML' tables can be customized using the flexible 'Bootstrap' framework, and 'LaTeX' code with the 'tabulararray' package.

Version 0.2.1

Imports methods

Depends R (>= 4.1.0)

Enhances knitr

Suggests fansi, data.table (>= 1.15.2), ggplot2, marginaleffects, markdown, pandoc, rmarkdown, rstudioapi, scales, stringi, tibble, tinysnapshot, tinytest, tinytex, webshot2

URL <https://vincentarelbundock.github.io/tinytable/>

BugReports <https://github.com/vincentarelbundock/tinytable/issues>

License GPL (>= 3)

Encoding UTF-8

RoxygenNote 7.3.1

NeedsCompilation no

Author Vincent Arel-Bundock [aut, cre]
(<<https://orcid.org/0000-0003-2042-7063>>)

Maintainer Vincent Arel-Bundock <vincent.arel-bundock@umontreal.ca>

Repository CRAN

Date/Publication 2024-03-28 16:20:02 UTC

R topics documented:

tinytable-package	2
format_tt	3
group_tt	5
plot_tt	6
print.tinytable	8
rbind2,tinytable,ANY-method	9
save_tt	10
style_tt	11
theme_tt	15
tt	17

Index	20
--------------	-----------

tinytable-package *Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats*

Description

Create highly customized tables with this simple and dependency-free package. Data frames can be converted to 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', or 'Typst' tables. The user interface is minimalist and easy to learn. The syntax concise. 'HTML' tables can be customized using the flexible 'Bootstrap' framework, and 'LaTeX' code with the 'tabulararray' package.

Package Content

Index of help topics:

format_tt	Format columns of a data frame
group_tt	Spanning labels to identify groups of rows or columns
plot_tt	Insert images and inline plots into tinytable objects
print.tinytable	Print, display, or convert a tinytable object
rbind2,tinytable,ANY-method	Combine 'tinytable' objects by rows (vertically)
save_tt	Save a Tiny Table to File
style_tt	Style a Tiny Table
theme_tt	Themes for 'tinytable'
tinytable-package	Simple and Configurable Tables in 'HTML', 'LaTeX', 'Markdown', 'Word', 'PNG', 'PDF', and 'Typst' Formats
tt	Draw a Tiny Table

Maintainer

Vincent Arel-Bundock <vincent.arel-bundock@umontreal.ca>

Author(s)

Vincent Arel-Bundock [aut, cre] (<<https://orcid.org/0000-0003-2042-7063>>)

format_tt

Format columns of a data frame

Description

This function formats the columns of a data frame based on the column type (logical, date, numeric). It allows various formatting options like significant digits, decimal points, and scientific notation. It also includes custom formatting for date and boolean values. If this function is applied several times to the same cell, the last transformation is retained and the previous calls are ignored, except for the escape argument which can be applied to previously transformed data.

Usage

```
format_tt(  
  x,  
  i = NULL,  
  j = NULL,  
  digits = getOption("tinytable_format_digits", default = NULL),  
  num_fmt = getOption("tinytable_format_num_fmt", default = "significant"),  
  num_zero = getOption("tinytable_format_num_zero", default = FALSE),  
  num_suffix = getOption("tinytable_format_num_suffix", default = FALSE),  
  num_mark_big = getOption("tinytable_format_num_mark_big", default = ""),  
  num_mark_dec = getOption("tinytable_format_num_mark_dec", default = getOption("OutDec",  
    default = ".") ),  
  date = "%Y-%m-%d",  
  bool = function(column) tools::toTitleCase(tolower(column)),  
  other = as.character,  
  replace_na = "",  
  escape = FALSE,  
  markdown = FALSE,  
  fn = NULL,  
  sprintf = NULL  
)
```

Arguments

- | | |
|---|---|
| x | A data frame or a vector to be formatted. |
| i | Row indices where the formatting should be applied. |
| j | Column indices where the styling should be applied. Can be: |

	<ul style="list-style-type: none"> • Integer vectors indicating column positions. • Character vector indicating column names. • A single string specifying a Perl-style regular expression used to match column names.
<code>digits</code>	Number of significant digits or decimal places.
<code>num_fmt</code>	The format for numeric values; one of 'significant', 'significant_cell', 'decimal', or 'scientific'.
<code>num_zero</code>	Logical; if TRUE, trailing zeros are kept in "decimal" format (but not in "significant" format).
<code>num_suffix</code>	Logical; if TRUE display short numbers with <code>digits</code> significant digits and K (thousands), M (millions), B (billions), or T (trillions) suffixes.
<code>num_mark_big</code>	Character to use as a thousands separator.
<code>num_mark_dec</code>	Decimal mark character. Default is the global option 'OutDec'.
<code>date</code>	A string passed to the <code>format()</code> function, such as "%Y-%m-%d". See the "Details" section in <code>?strptime</code>
<code>bool</code>	A function to format logical columns. Defaults to title case.
<code>other</code>	A function to format columns of other types. Defaults to <code>as.character()</code> .
<code>replace_na</code>	String to display for missing values.
<code>escape</code>	Logical or "latex" or "html". If TRUE, escape special characters to display them as text in the format of the output of a <code>tt()</code> table. <ul style="list-style-type: none"> • If <code>i</code> is NULL, escape the <code>j</code> columns and column names. • If <code>i</code> and <code>j</code> are both NULL, escape all cells, column names, caption, notes, and spanning labels created by <code>group_tt()</code>.
<code>markdown</code>	Logical; if TRUE, render markdown syntax in cells. Ex: <code>_italicized text_</code> is properly italicized in HTML and LaTeX.
<code>fn</code>	Function for custom formatting. Accepts a vector and returns a character vector of the same length.
<code>sprintf</code>	String passed to the <code>?sprintf</code> function to format numbers or interpolate strings with a user-defined pattern (similar to the <code>glue</code> package, but using Base R).

Value

A data frame with formatted columns.

Examples

```
dat <- data.frame(
  a = rnorm(3, mean = 10000),
  b = rnorm(3, 10000))
tab <- tt(dat)
format_tt(tab,
  digits = 2,
  num_mark_dec = ",",
  num_mark_big = " ")
```

```

k <- tt(data.frame(x = c(0.000123456789, 12.4356789)))
format_tt(k, digits = 2, num_fmt = "significant_cell")

dat <- data.frame(
  a = c("Burger", "Halloumi", "Tofu", "Beans"),
  b = c(1.43202, 201.399, 0.146188, 0.0031),
  c = c(98938272783457, 7288839482, 29111727, 93945))
tt(dat) |>
  format_tt(j = "a", sprintf = "Food: %s") |>
  format_tt(j = 2, digits = 1, num_fmt = "decimal", num_zero = TRUE) |>
  format_tt(j = "c", digits = 2, num_suffix = TRUE)

y <- tt(data.frame(x = c(123456789.678, 12435.6789)))
format_tt(y, digits=3, num_mark_big=" ")

x <- tt(data.frame(Text = c("_italicized text_", "__bold text__")))
format_tt(x, markdown=TRUE)

tab <- data.frame(a = c(NA, 1, 2), b = c(3, NA, 5))
tt(tab) |> format_tt(replace_na = "-")

dat <- data.frame(
  "LaTeX" = c("Dollars $", "Percent %", "Underscore _"),
  "HTML" = c("<br>", "<sup>4</sup>", "<emph>blah</emph>")
)
tt(dat) |> format_tt(escape = TRUE)

```

group_tt*Spanning labels to identify groups of rows or columns***Description**

Spanning labels to identify groups of rows or columns

Usage

```
group_tt(x, i = NULL, j = NULL, indent = 1, ...)
```

Arguments

x	A data frame or data table to be rendered as a table.
i	A named list of row indices to group. The names of the list will be used as labels.
j	A named list of column indices to group. The names of the list will be used as labels. See examples below. Note: empty labels must be a space: " ".
indent	integer number of pt to use when indenting the non-labelled rows.
...	Other arguments are ignored.

Details

Warning: The `style_tt()` can normally be used to style the group headers, as expected, but that feature is not available for Markdown and Word tables.

Value

An object of class `tt` representing the table.

Examples

```
tt(mtcars[1:10, 1:5]) |>
  group_tt(
    i = list(
      "Hello" = 3,
      "World" = 8),
    j = list(
      "Foo" = 2:3,
      "Bar" = 4:5))

dat <- mtcars[1:9, 1:8]
tt(dat) |>
  group_tt(i = list(
    "I like (fake) hamburgers" = 3,
    "She prefers halloumi" = 4,
    "They love tofu" = 7))

tt(dat) |>
  group_tt(
    j = list(
      "Hamburgers" = 1:3,
      "Halloumi" = 4:5,
      "Tofu" = 7))

x <- mtcars[1:5, 1:6]
tt(x) |>
  group_tt(j = list("Hello" = 1:2, "World" = 3:4, "Hello"=5:6)) |>
  group_tt(j = list("Foo" = 1:3, "Bar" = 4:6))
```

Description

The `plot_tt()` function allows for the insertion of images and inline plots into tinytable objects. This function can handle both local and web-based images.

Usage

```
plot_tt(
  x,
  i = NULL,
  j = NULL,
  fun = NULL,
  data = NULL,
  color = "black",
  xlim = NULL,
  height = 1,
  asp = 1/3,
  images = NULL,
  assets = "tinytable_assets",
  ...
)
```

Arguments

x	A tinytable object.
i	Integer vector, the row indices where images are to be inserted. If NULL, images will be inserted in all rows.
j	Integer vector, the column indices where images are to be inserted. If NULL, images will be inserted in all columns.
fun	<p>String or function to generate inline plots.</p> <ul style="list-style-type: none"> • String: "histogram", "density", "bar", "line" • Functions that return ggplot2 objects. • Functions that return another function which generates a base R plot, ex: function(x) {function() hist(x)} • See the tutorial on the tinytable website for more information.
data	a list of data frames or vectors to be used by the plotting functions in fun.
color	string Name of color to use for inline plots (passed to the col argument base graphics plots in R).
xlim	Numeric vector of length 2.
height	Numeric, the height of the images in the table in em units.
asp	Numeric, aspect ratio of the plots (height / width).
images	Character vector, the paths to the images to be inserted. Paths are relative to the main table file or Quarto (Rmarkdown) document.
assets	Path to the directory where generated assets are stored. This path is relative to the location where a table is saved.
...	Extra arguments are passed to the function in fun. Important: Custom plotting functions must always have ... as an argument.

Details

The `plot_tt()` can insert images and inline plots into tables.

Value

A modified tinytable object with images or plots inserted.

print.tinytable *Print, display, or convert a tinytable object*

Description

This function is called automatically by R whenever a tinytable object is anprinted to the console or in an HTML viewer pane.

Usage

```
## S3 method for class 'tinytable'
print(x, output = getOption("tinytable_print_output", default = NULL), ...)
```

Arguments

- | | |
|---------------------|---|
| <code>x</code> | A data frame or data table to be rendered as a table. |
| <code>output</code> | format in which a Tiny Table is printed: NULL or one of "latex", "markdown", "html", "typst", "dataframe". If NULL, the output is chosen based on these rules: <ul style="list-style-type: none"> • When called from a script in non-interactive mode, the default is "markdown" (<code>interactive() == FALSE</code>). • When called interactively in RStudio, the default is to display an HTML table in the viewer pane. • When called interactively in another development environment, the default is "markdown". • The default print output can be changed for an entire R session by calling: <code>options(tinytable_print_output = "html")</code> • The default print output can be changed for a single tinytable object by modifying the <code>output</code> S4 slot. |
| <code>...</code> | Other arguments are ignored. |

Value

launch a browser window or cat() the table to console.

rbind2,tinytable,ANY-method

Combine tinytable objects by rows (vertically)

Description

Combine tinytable objects by rows (vertically)

Usage

```
## S4 method for signature 'tinytable,ANY'
rbind2(x, y, use_names = TRUE, headers = TRUE, ...)
```

Arguments

x	tinytable object
y	tinytable object
use_names	‘TRUE’ binds by matching column name, ‘FALSE’ by position
headers	Logical. TRUE inserts the colnames of y as an extra row between the two tables.
...	Additional arguments are ignored.

Details

`format_tt()` calls applied to x or y are evaluated before binding, to allow distinct formatting for each panel.

Calls to other `tinytable` functions such as `style_tt()` or `group_tt()` are ignored when applied to x or y. These functions should be applied to the final table instead.

Information in these S4 slots is carried over from x to the combined table:

- `x@output`
- `x@caption`
- `x@width`

Information in these S4 slots is concatenated and carried over to the combined table:

- `c(x@notes, y@notes)`

This function relies on the `rbindlist()` function from the `data.table` package.

Examples

```
library(tinytable)
x = tt(mtcars[1:3, 1:2], caption = "Combine two tiny tables.")
y = tt(mtcars[4:5, 8:10])

# rbind() does not support additional arguments
# rbind2() supports additional arguments

# basic combination
rbind(x, y)

rbind(x, y) |> format_tt(replace_na = "")

# omit y header
rbind2(x, y, headers = FALSE)

# bind by position rather than column names
rbind2(x, y, use_names = FALSE)
```

save_tt

Save a Tiny Table to File

Description

This function saves an object of class `tinytable` to a specified file and format, with an option to overwrite existing files.

Usage

```
save_tt(x, output, overwrite = FALSE)
```

Arguments

<code>x</code>	The <code>tinytable</code> object to be saved.
<code>output</code>	String or file path. <ul style="list-style-type: none"> If <code>output</code> is "markdown", "latex", "html", or "typst", the table is returned in a string as an R object. If <code>output</code> is a valid file path, the table is saved to file. The supported extensions are: .docx, .html, .png, .pdf, .tex, .typ, and .md (with aliases .txt, .Rmd and .qmd).
<code>overwrite</code>	A logical value indicating whether to overwrite an existing file.

Value

A string or TRUE when the table is written to file.

Examples

```
library(tinytable)
x <- mtcars[1:4, 1:5]

fn <- file.path(tempdir(), "test.html")
tt(x) |> save_tt(fn, overwrite = TRUE)

library(tinytable)
filename <- file.path(tempdir(), "table.tex")
tt(mtcars[1:4, 1:4]) |> save_tt(filename)
```

style_tt

Style a Tiny Table

Description

Style a Tiny Table

Usage

```
style_tt(
  x,
  i = NULL,
  j = NULL,
  bold = FALSE,
  italic = FALSE,
  monospace = FALSE,
  underline = FALSE,
  strikeout = FALSE,
  color = NULL,
  background = NULL,
  fontsize = NULL,
  width = NULL,
  align = NULL,
  alignv = NULL,
  colspan = NULL,
  rowspan = NULL,
  indent = 0,
  line = NULL,
  line_color = "black",
  line_width = 0.1,
  finalize = NULL,
  tabulararray_inner = NULL,
  tabulararray_outer = NULL,
  bootstrap_class = NULL,
  bootstrap_css = NULL,
```

```
bootstrap_css_rule = NULL,
...
)
```

Arguments

x	A table object created by <code>tt()</code> .
i	Row indices where the styling should be applied. Can be a single value or a vector. <code>i=0</code> is the header, and negative values are higher level headers. If <code>colspan</code> is used, <code>i</code> must be of length 1.
j	Column indices where the styling should be applied. Can be: <ul style="list-style-type: none"> • Integer vectors indicating column positions. • Character vector indicating column names. • A single string specifying a Perl-style regular expression used to match column names.
bold	Logical; if TRUE, text is styled in bold.
italic	Logical; if TRUE, text is styled in italic.
monospace	Logical; if TRUE, text is styled in monospace font.
underline	Logical; if TRUE, text is underlined.
strikeout	Logical; if TRUE, text has a strike through line.
color	Text color. There are several ways to specify colors, depending on the output format. <ul style="list-style-type: none"> • HTML: <ul style="list-style-type: none"> – Hex code composed of # and 6 characters, ex: #CC79A7. – Keywords: black, silver, gray, white, maroon, red, purple, fuchsia, green, lime, olive, yellow, navy, blue, teal, aqua • LaTeX: <ul style="list-style-type: none"> – Hex code composed of # and 6 characters, ex: "#CC79A7". See the section below for instructions to add in LaTeX preambles. – Keywords: black, blue, brown, cyan, darkgray, gray, green, lightgray, lime, magenta, olive, orange, pink, purple, red, teal, violet, white, yellow. – Color blending using xcolor, ex: white!80!blue, green!20!red`. – Color names with luminance levels from the ninecolors package (ex: "azure4", "magenta8", "teal2", "gray1", "olive3").
background	Background color. Specified as a color name or hexadecimal code. Can be NULL for default color.
fontsize	Font size in em units. Can be NULL for default size.
width	Width of column in em units. Can be NULL for default width.
align	A single character or a string with a number of characters equal to the number of columns in j. Valid characters include 'c' (center), 'l' (left), 'r' (right), 'd' (decimal). Decimal alignment is only available in LaTeX via the <code>siunitx</code> package. The width of columns is determined by the maximum number of digits to the left and to the right in all cells specified by i and j.

alignv	A single character specifying vertical alignment. Valid characters include 't' (top), 'm' (middle), 'b' (bottom).
colspan	Number of columns a cell should span. i and j must be of length 1.
<td>Number of rows a cell should span. i and j must be of length 1.</td>	Number of rows a cell should span. i and j must be of length 1.
indent	Text indentation in em units. Positive values only.
line	String determines if solid lines (rules or borders) should be drawn around the cell, row, or column. <ul style="list-style-type: none"> • "t": top • "b": bottom • "l": left • "r": right • Can be combined such as: "lbt" to draw borders at the left, bottom, and top.
line_color	Color of the line. See the color argument for details.
line_width	Width of the line in em units (default: 0.1).
finalize	A function applied to the table object at the very end of table-building, for post-processing. For example, the function could use regular expressions to add LaTeX commands to the text version of the table hosted in x@table_string, or it could programmatically change the caption in x@caption.
tabulararray_inner	A string that specifies the "inner" settings of a tabulararray LaTeX table.
tabulararray_outer	A string that specifies the "outer" settings of a tabulararray LaTeX table.
bootstrap_class	String. Bootstrap table class such as "table", "table table-dark" or "table table-dark table-hover". See the bootstrap documentation.
bootstrap_css	Character vector. CSS style declarations to be applied to every cell defined by i and j (ex: "font-weight: bold").
bootstrap_css_rule	String. Complete CSS rules (with curly braces, semicolon, etc.) that apply to the table class specified by the bootstrap_class argument.
...	extra arguments are ignored

Details

This function applies styling to a table created by `tt()`. It allows customization of text style (bold, italic, monospace), text and background colors, font size, cell width, text alignment, column span, and indentation. The function also supports passing native instructions to LaTeX (tabulararray) and HTML (bootstrap) formats.

Note: Markdown and Word tables only support these styles: italic, bold, strikeout. Moreover, the `style_tt()` function cannot be used to style headers inserted by the `group_tt()` function; instead, you should style the headers directly in the header definition using markdown syntax: `group_tt(i = list("*italic header*" = 2))`. These limitations are due to the fact that there is no markdown syntax for the other options, and that we create Word documents by converting a markdown table to .docx via the Pandoc software.

Value

An object of class `tt` representing the table.

LaTeX preamble

When rendering Quarto and Rmarkdown documents, `tinytable` will populate the LaTeX preamble automatically with all the required packages. For standalone LaTeX packages, these commands should be inserted in the preamble:

```
\usepackage{tabulararray}
\usepackage{float}
\usepackage{graphicx}
\usepackage[normalem]{ulem}
\UseTblrLibrary{booktabs}
\newcommand{\tinytableTabulararrayUnderline}[1]{\underline{#1}}
\newcommand{\tinytableTabulararrayStrikeout}[1]{\sout{#1}}
\NewTableCommand{\tinytableDefineColor}[3]{\definecolor{#1}{#2}{#3}}
```

Examples

```
if (knitr::is_html_output()) options(tinytable_print_output = "html")

library(tinytable)

tt(mtcars[1:5, 1:6])

# Alignment
tt(mtcars[1:5, 1:6]) |>
  style_tt(j = 1:5, align = "lcccr")

# Colors and styles
tt(mtcars[1:5, 1:6]) |>
  style_tt(i = 2:3, background = "black", color = "orange", bold = TRUE)

# column selection with `j``
tt(mtcars[1:5, 1:6]) |>
  style_tt(j = 5:6, background = "pink")

tt(mtcars[1:5, 1:6]) |>
  style_tt(j = "drat|wt", background = "pink")

tt(mtcars[1:5, 1:6]) |>
  style_tt(j = c("drat", "wt"), background = "pink")

tt(mtcars[1:5, 1:6], theme = "void") |>
  style_tt(
    i = 2, j = 2,
    colspan = 3,
    rowspan = 2,
```

```

    align="c",
    alignv = "m",
    color = "white",
    background = "black",
    bold = TRUE)

tt(mtcars[1:5, 1:6], theme = "void") |>
  style_tt(
    i=0:3,
    j=1:3,
    line="tblr",
    line_width=0.4,
    line_color="teal")

tt(mtcars[1:5, 1:6], theme = "bootstrap") |>
  style_tt(
    i = c(2,5),
    j = 3,
    strikeout = TRUE,
    fontsize = 0.7)

tt(mtcars[1:5, 1:6]) |>
  style_tt(bootstrap_class = "table table-dark table-hover")

inner <- "
column{1-4}={halign=c},
hlines = {fg=white},
vlines = {fg=white},
cell{1,6}{odd} = {bg=teal7},
cell{1,6}{even} = {bg=green7},
cell{2,4}{1,4} = {bg=red7},
cell{3,5}{1,4} = {bg=purple7},
cell{2}{2} = {r=4,c=2}{bg=azure7},
"
tt(mtcars[1:5, 1:4], theme = "void") |>
  style_tt(tabulararray_inner = inner)

```

Description

A theme is a function which applies a collection of transformations to a `tinytable` object. Whereas the other `tinytable` functions such as `format_tt()` and `style_tt()` aim to be output-agnostic, themes can be output-specific, only applying to LaTeX, HTML, or Typst, as needed.

Each theme can have specific arguments, which are passed to the `theme_tt()` function. See the "Arguments" section below.

Usage

```
theme_tt(x, theme, ...)
```

Arguments

x	A tinytable object
theme	<p>String. Name of the theme to apply. One of:</p> <ul style="list-style-type: none"> • "grid": Vertical and horizontal rules around each cell. • "void": No rules • "bootstrap": Similar appearance to the default Bootstrap theme in HTML • "striped": Grey stripes on alternating rows • "tabular": No table environment (LaTeX) or Javascript/CSS (HTML) • "resize": Scale a LaTeX tinytable to fit the width argument. • "multipage": Long tables continue on the next page (LaTeX only) • "placement": Position of the table environment (LaTeX)
...	Additional arguments passed the themeing function. See the "Arguments" section below for a list of supported arguments for each theme.

Value

A modified tinytable object

Arguments

resize	<ul style="list-style-type: none"> • width: A numeric value between 0.01 and 1, representing the proportion of the line width to use • direction: "down", "up", "both" A string indicating if the table should be scaled in one direction. For example, "down" will only resize the table if it exceeds \linewidth
multipage	<ul style="list-style-type: none"> • rowhead: Non-negative integer. The number of header rows to repeat on each page. • rowfoot: Non-negative integer. The number of footer rows to repeat on each page.
placement	<ul style="list-style-type: none"> • latex_float: String to insert in square brackets after the LaTeX table environment, ex: "H", "htbp". The default value is controlled by a global option: <ul style="list-style-type: none"> – options("tinytable_theme_placement_latex_float" = "H")

Examples

```
library(tinytable)

x <- mtcars[1:4, 1:4]

# equivalent calls
tt(x, theme = "striped")

tt(x) |> theme_tt("striped")

# resize w/ argument
x <- cbind(mtcars[1:10,], mtcars[1:10,])
tt(x) |>
  theme_tt("resize", width = .9) |>
  print("latex")
```

tt

Draw a Tiny Table

Description

The `tt` function renders a table in different formats with various styling options: HTML, Markdown, LaTeX, Word, PDF, PNG, or Typst. The table can be customized with additional functions:

- `style_tt()`: style fonts, colors, alignment, etc.
- `format_tt()`: format numbers, dates, strings, etc.
- `group_tt()`: row or column group labels.
- `theme_tt()`: apply a collection of transformations to a `tinytable`.
- `save_tt()`: save the table to a file or return the table as a string.
- `print()`: print to a specific format, ex: `print(x, "latex")`

`tinytable` attempts to determine the appropriate way to print the table based on interactive use, RStudio availability, and output format in RMarkdown or Quarto documents. Users can call `print(x, output="markdown")` to print the table in a specific format. Alternatively, they can set a global option: `options("tinytable_print_output"="markdown")`

Usage

```
tt(
  x,
  digits = getOption("tinytable_tt_digits", default = NULL),
  caption = NULL,
  notes = NULL,
  width = getOption("tinytable_tt_width", default = NULL),
  theme = getOption("tinytable_tt_theme", default = NULL),
  ...
)
```

Arguments

x	A data frame or data table to be rendered as a table.
digits	Number of significant digits to keep for numeric variables. When digits is an integer, tt() calls format_tt(x, digits = digits) before proceeding to draw the table. Users who need more control can use the format_tt() function.
caption	A string that will be used as the caption of the table.
notes	Notes to append to the bottom of the table. This argument accepts several different inputs: <ul style="list-style-type: none"> • Single string insert a single note: "blah blah" • Multiple strings insert multiple notes sequentially: list("Hello world", "Foo bar") • A named list inserts a list with the name as superscript: list("a" = list("Hello World")) • A named list with positions inserts markers as superscripts inside table cells: list("a" = list(i = 0:1, j = 2, text = "Hello World"))
width	A numeric value between 0 and 1 indicating the proportion of the line width that the table should cover.
theme	Function or string. <ul style="list-style-type: none"> • String: grid, resize, multipage, placement, striped, void, bootstrap, tabular • Function: Applied to the tinytable object.
...	Additional arguments are ignored

Value

An object of class tt representing the table.

The table object has S4 slots which hold information about the structure of the table. This meta-data can be accessed with the usual @ accessor. In general, modifying the content of these slots is not recommended, but it can be useful to some developers, such as those who want to force print to a specific output format without calling print().

LaTeX preamble

When rendering Quarto and Rmarkdown documents, tinytable will populate the LaTeX preamble automatically with all the required packages. For standalone LaTeX packages, these commands should be inserted in the preamble:

```
\usepackage{tabulararray}
\usepackage{float}
\usepackage{graphicx}
\usepackage[normalem]{ulem}
\UseTblrLibrary{booktabs}
\newcommand{\tinytableTabulararrayUnderline}[1]{\underline{#1}}
\newcommand{\tinytableTabulararrayStrikeout}[1]{\sout{#1}}
\NewTableCommand{\tinytableDefineColor}[3]{\definecolor{#1}{#2}{#3}}
```

Examples

```
library(tinytable)
x <- mtcars[1:4, 1:5]

tt(x)

tt(x,
  theme = "striped",
  width = 0.5,
  caption = "Data about cars.")

tt(x, notes = "Hello World!")

fn <- list(i = 0:1, j = 2, text = "Hello World!")
tab <- tt(x, notes = list("*" = fn))
print(tab, "latex")

k <- data.frame(x = c(0.000123456789, 12.4356789))
tt(k, digits=2)
```

Index

```
* package
  tinytable-package, 2

format_tt, 3

group_tt, 5

plot_tt, 6
print.tinytable, 8

rbind2 (rbind2, tinytable, ANY-method), 9
rbind2, tinytable, ANY-method, 9

save_tt, 10
style_tt, 11

theme_tt, 15
tinytable (tinytable-package), 2
tinytable-package, 2
tt, 17
```