

Package ‘utr.annotation’

October 12, 2022

Type Package

Title Annotate Variants in the Untranslated Regions

Version 1.0.4

Maintainer Yating Liu <yatinghust@gmail.com>

Description A fast, user-friendly tool for annotating potential deleterious variants in the untranslated regions for both human and mouse species. Y Liu, JD Dougherty (2021) <[doi:10.1101/2021.06.23.449510](https://doi.org/10.1101/2021.06.23.449510)>.

License GPL (>= 3)

Encoding UTF-8

SystemRequirements Linux or MacOS Intel chip tensorflow (1.14.0)

Depends R (>= 3.5.0)

Imports parallel, doParallel, data.table, readr, stringr, biomaRt, vcfR, Biostrings, dplyr, tidyr, keras, AnnotationHub, ensemblDb, AnnotationFilter, BiocGenerics, GenomicFeatures, GenomicRanges, IRanges, foreach, rtracklayer, stats, utils, xml2

Suggests testthat, knitr, rmarkdown, ggplot2

RoxygenNote 7.1.1

VignetteBuilder knitr

NeedsCompilation no

Author Yating Liu [aut, cre] (<<https://orcid.org/0000-0001-7425-0422>>), Joseph D. Dougherty [aut] (<<https://orcid.org/0000-0002-6385-3997>>)

Repository CRAN

Date/Publication 2021-08-23 06:40:02 UTC

R topics documented:

concatenateAnnotationResult	2
initUTRAnnotation	3
partitionVariantFile	4
runUTRAnnotation	5

concatenateAnnotationResult*Concatenate annotation result files into one file***Description**

concatenateAnnotationResult Concatenate annotation result files into one file

Usage

```
concatenateAnnotationResult(
  varResultPath,
  annotationFinalResult,
  cores = NULL,
  verbose = FALSE
)
```

Arguments

varResultPath	annotation result directory
annotationFinalResult	final annotation file
cores	(optional) number of cores you'd like to use, by default would use a single core.
verbose	Whether print diagnostic messages. The default is FALSE.

Value

write concatenated annotation file to annotationFinalResult

Examples

```
## Not run:
# After we run UTR annotation on all partition variant files and
# store the annotations in "partition_results" for example,
# we can concatenate the annotation results into one file and
# store it in concatenated_annotation.csv
concatenateAnnotationResult(varResultPath = "partition_results",
                            annotationFinalResult = "concatenated_annotation.csv")

## End(Not run)
```

initUTRAnnotation	<i>Query transcripts regions and sequences from Ensembl database</i>
-------------------	--

Description

initUTRAnnotation query transcripts regions, UTRs and coding sequences from Ensembl database, which will be used by runUTRAnnotation to do UTR annotation.

Usage

```
initUTRAnnotation(  
  variantFile,  
  species,  
  ensemblVersion,  
  getTranscript = TRUE,  
  format = "csv",  
  dataDir = NULL,  
  verbose = FALSE  
)
```

Arguments

variantFile	a CSV file with Chr, Pos, Ref, Alt
species	either human or mouse
ensemblVersion	(optional) a number specifying which version of Ensembl annotation you'd like to use, by default use the latest version
getTranscript	(optional) Whether to get ids of the transcripts that overlap with all the variants. If the number of variants is too large (for example > 100,000), set it to FALSE and do this in runUTRAnnotation on each partition in parallel.
format	(optional) csv or vcf, the default is csv
dataDir	(optional) path to the store the database information, if not specified will create a folder named as input variant file name with a "db_" prefix
verbose	Whether print diagnostic messages. The default is FALSE.

Value

A variant table with Transcript column which contains the ids of the transcripts that overlap with the variants

Examples

```
test_variant_file <- system.file("extdata", "variants_sample.csv", package = "utr.annotation")  
initUTRAnnotation(variantFile = test_variant_file,  
                  species = "human",  
                  ensemblVersion = 93,
```

```
    dataDir = "test_db")
```

partitionVariantFile *Partition the variant file to run in parallel*

Description

`partitionVariantFile` is used to partition the variant file into small partition files by user defined size or number

Usage

```
partitionVariantFile(  
  variantFile,  
  chunkSize = NULL,  
  chunkNum = NULL,  
  chunkPath = "chunks",  
  species,  
  ensemblVersion = NULL,  
  overwrite = FALSE,  
  dataDir = NULL,  
  getTranscript = TRUE,  
  format = "csv",  
  verbose = FALSE  
)
```

Arguments

<code>variantFile</code>	variant file in CSV format
<code>chunkSize</code>	Partition the variant file into chunk files, which has a certain number of rows
<code>chunkNum</code>	Partition the variant file into a certain number of chunk files
<code>chunkPath</code>	(optional) A file directory to store all partition files. By default will output to "chunks" folder
<code>species</code>	human or mouse
<code>ensemblVersion</code>	(optional) a number specifying which version of Ensembl annotation you'd like to use, by default use the latest version
<code>overwrite</code>	(optional) If chunkPath already exists and not empty, whether or not to overwrite it. By default, do not overwrite and will raise error.
<code>dataDir</code>	(optional) path to store database information, if not specified will create a folder named as input variant file name with a "db_" prefix
<code>getTranscript</code>	(optional) Whether to get ids of the transcripts that overlap with all the variants. The default value is TRUE. If the number of variants is too large (for example > 100,000), set it to FALSE and do this in runUTRAnnotation on each partition in parallel.
<code>format</code>	(optional) csv or vcf, the default is csv
<code>verbose</code>	Whether print diagnostic messages. The default is FALSE.

Value

a list of partition variant files

Examples

```
variants_sample <- system.file("extdata", "variants_sample.csv", package = "utr.annotation")

# Partition variants_sample file equally into 3 variant files
# and store them in user specified chunkPath folder
partitionVariantFile(variantFile = variants_sample,
                     chunkNum = 3,
                     chunkPath = "chunks_3",
                     species = "human",
                     ensemblVersion = 93,
                     dataDir = "db_all_variants")

# Partition variants_sample file into smaller variant files each of which contains 7 variants,
# and store them in user specified chunkPath folder
partitionVariantFile(variantFile = variants_sample,
                     chunkSize = 7,
                     chunkPath = "chunks_7_vars",
                     species = "human",
                     ensemblVersion = 93,
                     dataDir = "db_all_variants")
unlink("db_all_variants", recursive = TRUE)
unlink("chunks_3", recursive = TRUE)
unlink("chunks_7_vars", recursive = TRUE)
```

runUTRAnnotation

Run UTR annotation on a variant file

Description

Run UTR annotation on a variant file to check whether a variant alter any of the feature element in UTRs, return a CSV file with annotated information

Usage

```
runUTRAnnotation(
  variantFile,
  annotationResult,
  species,
  ensemblVersion = NULL,
  dataDir = NULL,
  conservationBwFiles = NULL,
  cores = NULL,
  format = "csv",
```

```
mrl_prediction = TRUE,
verbose = FALSE
)
```

Arguments

variantFile	a CSV file with Chr, Pos, Ref, Alt
annotationResult	output annotation file
species	species, either human or mouse
ensemblVersion	(optional) a number specifying which version of Ensembl annotation you'd like to use, by default use the latest version
dataDir	(optional) path to the store / extract database information, if not specified will create a folder named as input variant file name with a "db_" prefix
conservationBwFiles	(optional) path to a folder which contains one or more conservation bigWig files. If not set, will skip conservation analysis.
cores	(optional) number of cores to use for parallel computing. If not specified, use a single core by default.
format	(optional) csv or vcf, the default is csv
mrl_prediction	(optional) Whether do MRL prediction and check if it increase or decrease. The default is TRUE.
verbose	Whether print diagnostic messages. The default is FALSE.

Value

A CSV file with annotated variants

Examples

```
test_variant_file <- system.file("extdata", "variants_sample.csv", package = "utr.annotation")

# run UTR annotation with 1 core and skip getting conservation scores for variant positions
runUTRAnnotation(variantFile = test_variant_file,
                  annotationResult = "annotated_variants_sample.csv",
                  species = "human",
                  ensemblVersion = 93,
                  dataDir = "test_db")
unlink("test_db", recursive = TRUE)
unlink("annotated_variants_sample.csv")

## Not run:
# Download BigWig format conservation track files hg38.phastCons100way.bw and hg38.phyloP100way.bw
# from UCSC Genome Browser to a folder (here we name it folder_store_conservation_bw_files)
Conservation_scores <- "folder_store_conservation_bw_files"
runUTRAnnotation(variantFile = test_variant_file,
                  annotationResult = "annotated_variants_sample.csv",
```

runUTRAnnotation

7

```
species = "human",
ensemblVersion = 93,
dataDir = "test_db",
cores = 8,
conservationBwFiles = Conservation_scores)

## End(Not run)
```

Index

concatenateAnnotationResult, [2](#)

initUTRAnnotation, [3](#)

partitionVariantFile, [4](#)

runUTRAnnotation, [5](#)